

J GAWRON 1960

4-5720

291

43

Remonumentation of Certain Original Corner Points, T. 13 S., R. 8 W.

Chains

(Remonumenting the Corner Point Established By Edward F. Sharp, in 1897)

The 1/4 sec. cor. of Sections 26 and 27, determined at record bearing and distance from the only remaining original bearing tree:

A fir snag, 6 ins. diam., bears S. 87° E., 275 lks. dist., mkd. 1/4 S.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 13 S R 8 W
S 27 | S 26
1960

from which

A fir, 8 ins. diam., bears S. 75° E., 39 lks. dist., mkd. 1/4 S26 BT.

A fir, 8 ins. diam., bears S. 33° W., 71 lks. dist., mkd. 1/4 S27 BT.

(Remonumenting the Corner Point Established By Edward F. Sharp, in 1897)

The corner of Sections 22, 23, 26 and 27, determined at record bearing and distance from three remaining original bearing trees:

A fir, 30 ins. diam., bears N. 16° E., 54 lks. dist., mkd. with a healed blaze.

A fir, 24 ins. diam., bears S. 72° W., 59 lks. dist., mkd. with a healed blaze.

A hemlock, 24 ins. diam., bears N. 15° W., 60 lks. dist., mkd. T12 R8S on exposed face of partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 13 S R 8 W
S 22 | S 23
S 27 | S 26
1960

from which

A fir, 18 ins. diam., bears N. 75° E., 45 lks. dist., mkd. T13S R8W S23 BT.

A fir, 14 ins. diam., bears S. 75° E., 13 lks. dist., mkd. T13S R8W S26 BT.

A fir, 22 ins. diam., bears S. 2° W., 74 lks. dist., mkd. T13S R8W S27 BT.

A fir, 16 ins. diam., bears N. 42° W., 31 lks. dist., mkd. T13S R8W S22 BT.

138500 240

