

C.S. #224 $\frac{1}{4}$ Sec. Cor. bet. secs. 29 & 30. T. 12 S., R. 4 W. W. M.
 witnesses Set $\frac{1}{2}$ " x 30" iron pipe from which
 Chas. Lead better W. Oak 12" in diam. bears N. 47° E. 360 chs. dist. standing
 G. W. Shock. W. Oak 12" " " S 2° 30' W. 471 " " New

" W.C. to M.C. at 1716 on line bet. secs. 30 & 31. T. 12 S. R. 4 W. W. M.
 W.C. is at 1466. M.C. falls in Channel
 Set $\frac{1}{2}$ " x 36" pipe from which
 Maple 18" in diam. bears N. 47° 35' W. 1.011 chs. dist.
 Maple 18" " " " S. 17° 30' W. .531 " "

Note - This cor. may be 0.90 chs. North of its true position, the position from the trees as above is correct.

" M.C. at 37.16 on line between secs. 30 & 31. T. 12 S., R. 4 W.
 Set $\frac{1}{2}$ " x 32" Iron pipe at 36.974 chs. from which
 Balm 12" in diam. bears N. 53 $\frac{1}{4}$ ° E. .292 chs. dist
 " 24" " " " S 35° E. .766 " "

" The $\frac{1}{4}$ sec. cor. bet. secs. 30 and 31. T. 12 S. R. 4 W.
 Set by proportion measurement. 77.80 : 37.80 :: 78.542 : 38.161
 Set a $\frac{1}{2}$ " x 32" iron pipe at 38.161 chs. from which
 Willow 9" in diam. bears S. 55° W. 398 chs. dist.
 Balm 18" " " " N. 80 $\frac{1}{2}$ ° E. .769 " "
 Note - This is not a reestablishment but is recorded for convenience

" M.C. and W.C. to $\frac{1}{4}$ at 40.05 on line between secs. 30 and 31. T. 12 S. R. 4 W.
 Set by proportional measurement. 77.80 : 40.05 :: 78.542 : 40.432
 Set $\frac{1}{2}$ " x 32" pipe at 40.432 from which
 Balm 15" in diam. bears S. 21 $\frac{1}{4}$ ° E. .247 chs. dist
 " 24" " " " N. 44° W. .430 " "

C.S. #225 $\frac{1}{4}$ Sec. Cor. bet. secs. 35 and 36. T. 10 S. R. 4 W. Will. Mer.
 witnessed by Set $\frac{1}{8}$ " x 7" x 19" Strap iron with two stones 3' x 5' x 4' 10" below surface of ground.
 Murray B. Cole A wire fence is East .050 chs. dist.
 C. O. R. Anderson Center line of wagon road is South 5.220 chs. dist.

" The Corner of secs. 25, 26, 35 & 36. T. 10 S. R. 4 W. W. M.
 Set broken moldboard of plow 10" below surface of ground, from which
 Cottonwood 16" in diam. bears S 32° 50' E. 2.383 chs. dist
 Intersection of E & W fence and $\frac{1}{2}$ of ditch bears N 53° E. 1.004 chs. dist
 " " fences from N. S. E. & W. " N. 76° W. 2.773 " "
 " " " " N. S. & W. " N. 82° 20' E. 4.696 " "

" No witnesses present The Standard $\frac{1}{4}$ sec. cor. on South line of sec. 35. T. 10 S. R. 4 W.
 Set $\frac{3}{8}$ " x 30" bolt. from which
 Fir 16" in diam. bears N 40 $\frac{1}{2}$ ° E. 1.265 chs. dist.
 Oak anchor post " N 87° 45' W. .285 " "
 " " " " S. 61° 45' W. .415 " "

C.S. #225
 witnessed by
 Murray B. Cole
 C. O. R. Anderson

" No Witness present

C.S. 226
 witnessed by
 L. Mitchell

C.S. #168
 Continued from
 65 this book.

C.S. #168

The corner of sections 25, 26, 35 and 36, Twp. 10 S., R. 4 W. W. M.

Reestablishment by ~~W. G. Galloway~~ *

Date ~~4-20-192~~
8/8/1916

Set broken moldboard of plow 10" below surface of ground

Cottonwood 16" in diam bears S 32° 50' E 2.383 chains

Intersection of E. & W. fence and angle of ditch bears N 53
1.084 chains dist.

Intersection of fences from N.S.E.&W. bears N 76° W 2.773 ch

Intersection of fences from N,S, & W. bears N 82°20'E 4.696

* BURT WILKES, SEE FIELD BOOK NO. 19, INSIDE COVER AND PAGE 34 (CJL 5/21/1992).

26/25
35/36

-112
54

CORNER HISTORY		T 10 S, R 4 W		SECTION 25 D.L.C.		CORNER SW CORNER		# 800200
NO.	DATE	SOURCE	SURVEYOR	MONUMENTS AND ACCESSORIES		COMMENTS		
①	12/17/1852	ORIG. GLO	JAMES FREEMAN	SET POST @ 2 OAK B.T.'S + TRENCH				1
								2
②	8/8/1916	CS# 560	BURT WILKES	SET BROKEN MOULBOARD OF PLOW 10" BS @ 4 B.D.'S		FB 19/34		3
								4
③	NAME GIVEN	OLD COR. REST- BK. #1 PG. 112	" "	" " " " " " " " " " " "				5
								6
④	8/8/1916	REST- 54	" "	" " " " " " " " " " " "		TRANS. COPY @ E+O		7
⑤	4/28/1920	MAP NO. 10-4-00016	W.C. GALLOWAY	1/2" IRON OR STEEL ROD + MOULBOARD .034 E @ ABOUT 10 ACRES.		MAP NO. 10-4-00016		8
⑥	NONE GIVEN	MAP NO. 10-4-00024	BENTON COUNTY SURVEYOR'S OFFICE	MOULBOARD OF PLOW " " "				9
								10
⑦	2/23/1922	CS# 819	WALTER W. LARSEN	PLOW SHEAR		FB 32/3		11
								12
⑧	9/23/1946	CS# 1813	BENTON COUNTY SURVEYOR'S OFFICE	1/2" I. ROD @ ABOUT 5 ACRES.		FB 91/45, 46		13
								14
	6/1992		C.J. LIESENFELT	FIND EVID. OF A DITCH + AN E-W FNC. BUT FUTURE TIES TO OTHER WCG MONS. SHOULD YIELD A BETTER POSITION				15
								16
								17
								18
								19
								20
								21
								22
								23
								24
								25
								26
								27
								28
								29
								30
								31

TOWNSHIP 10 SOUTH, RANGE 4 WEST, WILLAMETTE MERIDIAN; SECTION 25 CORNER SOUTHWEST
DONATION LAND CLAIM _____ CORNER _____**COMMON CORNER(S):**

SOUTHEAST CORNER OF SECTION 26.
NORTHEAST CORNER OF SECTION 35.
NORTHWEST CORNER OF SECTION 36.

UPDATES AND REVISIONS:**CORNER RECORDS (PREVIOUS RENEWALS, SURVEYS, ETC.)**

- [01] ORIGINAL GLO SURVEY BY JAMES FREEMAN DATED DECEMBER 17, 1852.
- [02] COUNTY SURVEY NO. 560 BY BURT WILKES DATED AUGUST 8, 1916 (FIELD BOOK NO. 19, PAGE 34).
- [03] OLD CORNER RESTORATION BOOK NO. 1 PAGE 112 BY BURT WILKES (NO DATE GIVEN).
- [04] CORNER RESTORATION NO. 54 BY BURT WILKES DATED AUGUST 8, 1916.
- [05] MAP NO. 10-4-00016 BY W.C. GALLOWAY DATED APRIL 28, 1920.
- [06] MAP NO. 10-4-00024 BY BENTON COUNTY SURVEYOR'S OFFICE (NO DATE GIVEN).
- [07] COUNTY SURVEY NO. 819 BY WALTER W. LARSEN DATED FEBRUARY 23, 1922 (FIELD BOOK NO. 32, PAGE 3).
- [08] COUNTY SURVEY NO. 1813 BY BENTON COUNTY SURVEYOR'S OFFICE DATED SEPTEMBER 23, 1946 (FIELD BOOK NO. 91, PAGES 45, 46).

COMMENTS/LOCATION/ETC:

RECORD [04] IS A TRANSCRIBED COPY OF RECORD [03] AND MAY CONTAIN ERRORS AND OMISSIONS.

IN JUNE OF 1992 CURT LIESENFELT AND MARK ANDERSON FOUND EVIDENCE OF A DITCH AND AN EAST-WEST FENCE LINE, BUT CONCLUDED THAT TIES TO OTHER MONUMENTS WOULD PROBABLY YIELD A BETTER POSITION. NOTHING ELSE WAS RECOVERED OR SET.

NOTES:

THIS IS A MICROSOFT WORD (VERSION 5.0) DOCUMENT NAMED "04600200" CREATED FROM A BOILER PLATE DOCUMENT NAMED "HISTORY", WHICH HAS A STYLESHEET NAMED "CORNER" ATTACHED TO IT.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVER AVE. CORVALLIS OR 97333; PH. 757-6821
RESEARCH BY: CURTIS J. LIESENFELT/MARK E. ANDERSON
DATA ENTRY BY: MARK E. ANDERSON