

**104866030**

DATE 05/23/2014TOWNSHIP 10 SOUTH, RANGE 4 WEST, WILLAMETTE MERIDIAN; SECTION 8, CORNER N/A  
DONATION LAND CLAIM JOHN RODGERS NO. 66 CORNER SOUTHWESTCOMMON CORNER(S):  
POINT ON THE SOUTH LINE OF SECTION 8

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)  
BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES OF THE JOHN RODGERS DONATION LAND CLAIM NO. 66 BY DAVID STUMP, D.S., DATED DECEMBER 3, 1854. ***DROVE DOWN A CHARRED STAKE, MARKED AND SET POST, RAISED MOUND, DUG QUADRANGULAR TRENCH AS PER INSTRUCTIONS.***
- [02] ANDREW PORTER BOOK OF SURVEYS, PAGE 69, SURVEY NO. 48, BY ANDREW L. PORTER, C.S., DATED OCTOBER 17, 1889. ***CORNER TIED BUT NOT DESCRIBED.***
- [03] BENTON COUNTY SURVEY NO. 520 (OLD NO. 223) FIELD NOTES (FIELD BOOK 19, PAGE 24) BY BURT WILKES, D.C.S., DATED MAY 29, 1915. ***SET CORNER.***
- [04] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 95, BY BURT WILKES, D.C.S., DATED JUNE 3, 1915. ***SET 1-7/16" X 60" SHAFT FOR CORNER. 31.756 CHAINS (2095.90 FEET) EAST (SHOULD BE WEST) OF SOUTHEAST CORNER OF SAID CLAIM.***
- [05] BENTON COUNTY CORNER RESTORATION NO. 122. ***TRANSCRIBED FROM RECORD [04] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.***
- [06] BENTON COUNTY SURVEY NO. 520 (OLD NO. 223) BY BURT WILKES, D.C.S., DATED JUNE 3, 1915. ***SET 1-7/16" SHAFT 5 FEET LONG. 3/4" IRON ROD 20 FEET SOUTH.***
- [07] BENTON COUNTY MAP NO. 10-4-00003 BY BURT WILKES, D.C.S., DATED JUNE 3, 1915. ***SET 1-7/16" SHAFT 5 FEET LONG. 3/4" IRON ROD 20 FEET SOUTH. CHANNEL IRON 20 FEET NORTH. B. WALNUT 5" DIA BEARS S7-3/4°W, 0.366 CHAINS (24.16 FEET).***

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE  
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
RESEARCH BY: DAVID L. MALONE, P.L.S.  
DATA ENTRY BY: SAME

## CAMEL RESTORATION BOOK NO. 1

CS. #223

B. Wilkes  
Deeds

1/4 sec. cor. bet. secs. 5 & 8 T. 10 S., R. 4 W.  
Set 3/8" X 36" shaft with 3 sprocket on top, from which  
Oak 4-8" in diam. bears North 3-76 chs. dist stump.  
Oak 10" 5 1/2" W. 182 3/4" W. 1231 " " New.  
Oak 5" " " 189 1/4" W. 606 " " "  
Witness O.T. Murphy

June 2, 1915

S.E. Corner of Andrew Chamberlain C1 N<sup>o</sup> 65 T. 10 S. R. 4 W.

Set 3/8" X 40" rod From which  
Oak 2 1/2" in diam. bears N 38° W. 2.87 Chs. dist. Standing  
Fir 20" " " N 10 3/4° W. 1.372 " " New.  
Witnesses. O.T. Murphy, Joseph Ridders, Edw. Thurston.

June 2, 1915

N.W. Corner Amon Ryburn C1 N<sup>o</sup> 67 T. 10 S. R. 4 W.

Set 3/8" X 30" shaft, From which  
Oak 30" in diam. bears N. 1 1/2° W. .58 Chs. dist. stump-down  
Oak 12" " " N. 1 1/4° W. .270 " " New.  
Witnesses as above.

June 2, 1915

S.W. Corner John Rodgers, C1 N<sup>o</sup> 66 T. 10 S. R. 4 W.

Set 1 1/8" X 60" shaft for corner; 31.756 Chs. E. of S.E. Cor. of said C1 66  
Witness O.T. Murphy

June 3, 1915

1/4 sec. cor. bet. secs. 7 &amp; 8 T. 10 S. R. 4 W.

Set 1 1/2" X 48" Pipe From which  
Oak 2 1/4" in diam. bears N. 10° W. 28 Chs. dist. Standing  
Witness O.T. Murphy

June 3, 1915

S.W. Corner Amon Ryburn C1 N<sup>o</sup> 67 T. 10 S. R. 4 W.

Set 5" X 5 1/8" Stone for corner.  
Two Northerly trees standing, Southernly Tree down.  
Witnesses O.T. Murphy, Joseph Ridders, Edw. Thurston.

June 2, 1915

CS# 240

1/4 sec. cor. between secs. 22 & 27 T. 11 S. R. 7 W.  
Set Stone 6" X 8" X 20" R. stumps no marks but exact check.  
Fir 8" bears S. 84° 30' E. 1.297 chs.  
" 8" " S. 1° 15' W. 3.246 " "

May 24, 1915.

1/4 sec. cor. between secs. 27 & 28 T. 11 S. R. 7 W.  
Stone 6" X 8" X 16" already set both trees down wind fall.  
Fir 18" bears S. 74° 10' E. 1.519 chs.  
" 8" " N. 28° 35' W. .826 "

Witnesses F.M. Zeller J.G. Ingebritson May 26, 1915.

Cor. to Secs. 21, 22, 27 &amp; 28 T. 11 S. R. 7 W.

Set 1 1/2" cast pipe  
Burnt fir 40" bears N 53° E. 1.35 chs. std. snag.  
" 4" " S. 89° E. .240 "  
" 30" " S. 74° W. 3.846 " "  
stump of " 30" " N 37° W. .73 " "

Witnesses F.M. Zeller, J. G. Ingebritson &amp; J.C. Whitney May 27, 1915.

S. W. corner John Rodgers Cl 66, Twp. 10 S., R. 4 W.  
Reestablishment by W. C. Galloway

June 3, 1915

122

Set 1 7/16" x 60" shaft      31.756 chs. E. of S. E. corner of said Cl. 66

Witness O. T. Murphy