

105200200

CORNER FILE TRACKING

S:\Survey Corners\CORNERS\Templates\Filetrac2.doc
10/04/2010

CORNER NUMBER
105200200

STEP	HISTORY	RESTORATION
Form Prepared, DB	6/14/13	
Field Inspection, DB		
Finish index (count unit)	6/14/13	
Counter Index		
GIS Index Form		
Checked, DB		
Form Edited, DB		
Form Signed, DB		
Authorize Payment, DB		
Archive Digital Files		
Collect Documents		
PDF File		
Copy For Filming		
Scanned (pdf to laserfiche)		
Filmed (Archived), DB		
Filed, DB		

(DB) = Entry needed in database (Access).

COMMENTS:

DATE 06/14/2013

TOWNSHIP 10 SOUTH, RANGE 5 WEST, WILLAMETTE MERIDIAN; SECTION 29 CORNER SOUTHWEST DONATION LAND CLAIM N/A CORNER N/A

COMMON CORNER(S):

SOUTHEAST CORNER SECTION 30
NORTHEAST CORNER SECTION 31
NORTHWEST CORNER SECTION 32

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

[01] GENERAL LAND OFFICE (GLO) NOTES BY GEORGE MERCER, D.S., DATED MAY 13, 1882. SET POST 4 FEET LONG AND 4 INCHES SQUARE WITH MARKED STONE 12" IN THE GROUND FOR CORNER TO SECTION MARKED "T10S S29" ON NORTHEAST FACE; "R5W S32" ON SOUTHEAST FACE; "S31" ON SOUTHWEST FACE; AND "S30" ON NORTHWEST FACE WITH 1 NOTCH ON SOUTH EDGE AND 5 NOTCHES ON EAST EDGE FROM WHICH A MAPLE 6" DIA BEARS N35°E, 18 LINKS (11.88 FEET) MARKED "T10S R5W S29 BT"; A FIR 24" DIA BEARS S45°E, 30 LINKS (19.80 FEET) MARKED "T10S R5W S32 BT"; A FIR 30" DIA BEARS S40°W, 18 LINKS (11.88 FEET) MARKED "T10S R5W S31 BT"; A FIR 20" DIA BEARS N40°W, 15 LINKS (9.90 FEET) MARKED "T10S R5W S30 BT".

[02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY LYNN M. ROSEBERRY, CADASTRAL SURVEYOR, DATED JULY 2, 1963. CORNER DETERMINED AT RECORD BEARING AND DISTANCE FROM A SAWED FIR STUMP 38" DIA (GLO BT) BEARS S45°E, 30 LINKS (19.80 FEET) WITH SCRIBE MARK "T" VISIBLE ON OPENED BLAZE. SET A 2-1/2" DIA IRON POST, 28" LONG, 24" IN THE GROUND WITH BRASS CAP MARKED "T10S R5W S30 S29 S31 S32 1963" FROM WHICH A MAPLE 17" DIA BEARS N25-1/2°E, 136 LINKS (89.76 FEET) MARKED "T10S R5W S29 BT"; A FIR 53" DIA BEARS S27-1/2°E, 180 LINKS (118.80 FEET) MARKED "T10S R5W S32 BT"; A MAPLE 11" DIA BEARS S53-3/4°W, 42 LINKS (27.72 FEET) MARKED "T10S R5W S31 BT"; AND A FIR 51" DIA BEARS N49°W, 164 LINKS (108.24 FEET) MARKED "T10S R5W S30 BT".

[03] BENTON COUNTY PARTITION PLAT NO. 1992-27 BY THEODORE JAMES LANGTON, P.L.S., DATED APRIL 20, 1992. CORNER NOT TIED OR DESCRIBED.

[04] BENTON COUNTY PARTITION PLAT NO. 2008-25 BY WILLIAM L. LAUER, P.L.S., DATED AUGUST 18, 2008. CORNER NOT TIED OR DESCRIBED.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS OR 97333; PH. 766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME