

**105240200**

## CORNER FILE TRACKING

S:\Survey Corners\CORNERS\Templates\Filetrac2.doc  
10/04/2010

<b>CORNER NUMBER</b>
<b>105240200</b>

<b>STEP</b>	<b>HISTORY</b>	<b>RESTORATION</b>
Form Prepared, DB	6/14/13	
Field Inspection, DB		
Finish index (count unit)	6/14/13	
Counter Index		
GIS Index Form		
Checked, DB		
Form Edited, DB		
Form Signed, DB		
Authorize Payment, DB		
Archive Digital Files		
Collect Documents		
PDF File		
Copy For Filming		
Scanned (pdf to laserfiche)		
Filmed (Archived), DB		
Filed, DB		

(DB) = Entry needed in database (Access).

### COMMENTS:

**BENTON COUNTY CORNER HISTORY FORM, PAGE 1 OF 1, 105240200H**

DATE 06/14/2013

TOWNSHIP 10 SOUTH, RANGE 5 WEST, WILLAMETTE MERIDIAN; SECTION 29 CORNER SOUTH 1/4  
DONATION LAND CLAIM N/A CORNER N/A

**COMMON CORNER(S):**

NORTH 1/4 CORNER SECTION 32

**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY GEORGE MERCER, D.S., DATED MAY 13, 1882. SET POST 3 FEET LONG AND 3 INCHES SQUARE WITH MARKED STONE 12" IN THE GROUND FOR 1/4 SECTION CORNER MARKED "1/4S" ON NORTH FROM WHICH A FIR 10" DIA BEARS S60°W, 8 LINKS (5.28 FEET) MARKED "1/4S BT"; A FIR 8" DIA BEARS N30°E, 22 LINKS (14.52 FEET) MARKED "1/4S BT".
- [02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY LYNN M. ROSEBERRY, CADASTRAL SURVEYOR, DATED JULY 2, 1963. CORNER DETERMINED AT RECORD BEARING AND DISTANCE FROM A SAWED AND ROTTED FIR STUMP 20" DIA (GLO BT) BEARS S60°W, 8 LINKS (5.28 FEET) WITH SCRIBE MARKS "BT" VISIBLE ON OPENED BLAZE. SET A 2-1/2" DIA IRON POST, 28" LONG, 24" IN THE GROUND WITH BRASS CAP MARKED "T10S R5W 1/4 S29 S32 1963" FROM WHICH A FIR 25" DIA BEARS N31°W, 41 LINKS (27.06 FEET) MARKED "1/4 S29 BT"; A FIR 25" DIA BEARS S47°E, 56 LINKS (36.96 FEET) MARKED "1/4 S32 BT".
- [03] BENTON COUNTY PARTITION PLAT NO. 1992-27 BY THEODORE JAMES LANGTON, P.L.S., DATED APRIL 20, 1992. CORNER NOT TIED OR DESCRIBED.
- [04] BENTON COUNTY SURVEY NO. 9936 BY JIM S. PETERSON, P.L.S., DATED JANUARY 5, 1999. FOUND 3-1/4" BLM 1963 BRASS CAP. A FIR 30" DIA (BLM BT) BEARS N31°W, 41 LINKS (27.06 FEET) WITH HEALED FACE; A FIR 32" DIA (BLM BT) BEARS S47°E, 56 LINKS (36.96 FEET) WITH HEALED FACE; ROTTED FIR REMAINS (GLO BT) BEAR S60°W, 8 LINKS (5.28 FEET) WITH SCRIBING VISIBLE.
- [05] BENTON COUNTY SURVEY NO. 9924 BY JIM S. PETERSON, P.L.S., DATED APRIL 29, 1999. FOUND 3-1/4" BLM 1963 BRASS CAP. A FIR 30" DIA (BLM BT) BEARS N31°W, 41 LINKS (27.06 FEET) WITH HEALED FACE; A FIR 32" DIA (BLM BT) BEARS S47°E, 56 LINKS (36.96 FEET) WITH HEALED FACE; ROTTED FIR REMAINS (GLO BT) BEAR S60°W, 8 LINKS (5.28 FEET) WITH SCRIBING VISIBLE.
- [06] BENTON COUNTY PARTITION PLAT NO. 2008-25 BY WILLIAM L. LAUER, P.L.S., DATED AUGUST 18, 2008. CORNER NOT TIED OR DESCRIBED.

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS OR 97333; PH. 766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME