

**105240300**

## CORNER FILE TRACKING

S:\Survey Corners\CORNERS\Templates\Filetrac2.doc  
10/04/2010

|                      |
|----------------------|
| <b>CORNER NUMBER</b> |
| <b>105240300</b>     |

| <b>STEP</b>                 | <b>HISTORY</b> | <b>RESTORATION</b> |
|-----------------------------|----------------|--------------------|
| Form Prepared, DB           | 5/31/13        |                    |
| Field Inspection, DB        |                |                    |
| Finish index (count unit)   | 5/31/13        |                    |
| Counter Index               |                |                    |
| GIS Index Form              |                |                    |
| Checked, DB                 |                |                    |
| Form Edited, DB             |                |                    |
| Form Signed, DB             |                |                    |
| Authorize Payment, DB       |                |                    |
| Archive Digital Files       |                |                    |
| Collect Documents           |                |                    |
| PDF File                    |                |                    |
| Copy For Filming            |                |                    |
| Scanned (pdf to laserfiche) |                |                    |
| Filmed (Archived), DB       |                |                    |
| Filed, DB                   |                |                    |

(DB) = Entry needed in database (Access).

### COMMENTS:

DATE 05/31/2013TOWNSHIP 10 SOUTH, RANGE 5 WEST, WILLAMETTE MERIDIAN; SECTION 20 CORNER SOUTH 1/4  
DONATION LAND CLAIM N/A CORNER N/ACOMMON CORNER(S):  
NORTH 1/4 CORNER SECTION 29**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

[01] GENERAL LAND OFFICE (GLO) NOTES BY GEORGE MERCER, D.S., DATED MAY 13, 1882. SET POST 3 FEET LONG AND 3 INCHES SQUARE WITH STONE 12 INCHES IN THE GROUND FOR 1/4 SECTION CORNER, MARKED "1/4S" ON THE NORTH FROM WHICH A FIR 24" DIA BEARS S35°W, 20 LINKS (13.20 FEET) MARKED "1/4S BT"; A FIR 20" DIA BEARS N20°E, 51 LINKS (33.66 FEET) MARKED "1/4S BT".

[02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY LYNN M. ROSEBERRY, CADASTRAL SURVEYOR, DATED JULY 2, 1963. CORNER DETERMINED AT RECORD DISTANCE FROM A SAWED FIR STUMP 33" DIA (GLO BT) BEARS N22°E, 51 LINKS (33.66 FEET) WITH SCRIBE MARKS "BT" VISIBLE ON OPENED BLAZE AND A SAWED FIR STUMP 43" DIA (GLO BT) BEARS S45°W, 20 LINKS (13.20 FEET) WITH SCRIBE MARKS "4 S BT" VISIBLE ON OPENED BLAZE. SET A 2-1/2" DIA IRON POST, 28" LONG, 24" IN THE GROUND WITH BRASS CAP MARKED "T10S R5W 1/4 S20 S29 1963" FROM WHICH A FIR 5" DIA BEARS N10-1/2°W, 29 LINKS (19.14 FEET) MARKED "1/4 S20 BT"; A FIR 4" DIA BEARS S56°E, 15 LINKS (9.90 FEET) MARKED "1/4 S29 BT".

[03] BENTON COUNTY SURVEY NO. 8491 BY THEODORE JAMES LANGTON, P.L.S., DATED FEBRUARY 5, 1991. FOUND 3-1/4" BLM BRASS CAP ON 2" PIPE. FIR STUMP 33" DIA (GLO BT) BEARS N22°E, 33.66 FEET, OPEN FACE WITH SCRIBING; FIR STUMP 43" DIA (GLO BT) BEARS S45°W, 13.20 FEET; FIR STUMP 16" DIA (BLM BT) BEARS N10°30'W, 19.14 FEET WITH HEALED FACE; FIR STUMP 18" DIA (BLM BT) BEARS S56°E, 9.90 FEET WITH HEALED FACE.

[04] BENTON COUNTY PARTITION PLAT NO. 1992-27 BY THEODORE JAMES LANGTON, P.L.S., DATED APRIL 20, 1992. CORNER NOT TIED OR DESCRIBED.

[05] BENTON COUNTY PARTITION PLAT NO. 2008-25 BY WILLIAM L. LAUER, P.L.S., DATED AUGUST 18, 2008. CORNER NOT TIED OR DESCRIBED.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE  
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS OR 97333; PH. 766-6821  
RESEARCH BY: DAVID L. MALONE, P.L.S.  
DATA ENTRY BY: SAME