

**105500100**

DATE 01/09/2018TOWNSHIP 10 SOUTH, RANGE 5 WEST, WILLAMETTE MERIDIAN; SECTION 34 CORNER SOUTHEAST  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHWEST CORNER SECTION 35, TOWNSHIP 10 SOUTH, RANGE 5 WEST  
POINT ON NORTH LINE SECTION 3, TOWNSHIP 11 SOUTH, RANGE 5 WEST**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ROBERT ELDER, D.S., DATED FEBRUARY 26, 1853. *SET POST FROM WHICH A W. OAK 18" DIA BEARS N29°E, 105 LINKS (69.30 FEET); A W. OAK 16" DIA BEARS N43°W, 120 LINKS (79.20 FEET).*
- [02] BENTON COUNTY SURVEY NO. 189 (OLD NO. 91) FIELD NOTES (FIELD BOOK 7, PAGE 29) BY J. A. GANONG, D.C.S., DATED OCTOBER 24, 1910. *CORNER NOT DESCRIBED.*
- [03] BENTON COUNTY SURVEY NO. 189 (OLD NO. 91) MAP (RECORD OF PLATS BOOK 3, PAGE 84) BY UNKNOWN DRAFTSMAN, NO DATE GIVEN. *OAK STAKE. OAK 12" DIA BEARS N27°15'E, 2.17 CHAINS (143.22 FEET); OAK 10" DIA BEARS N54°30'W, 2.22 CHAINS (146.52 FEET).*
- [04] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 39, BY UNKNOWN DRAFTSMAN, NO DATE GIVEN. *SET 4" X 4" X 30" OAK STAKE FOR CORNER FROM WHICH AN OAK 12" DIA (CSBT) BEARS N27°15'E, 2.17 CHAINS (143.22 FEET); OAK 10" DIA (CSBT) BEARS N54°30'W, 2.22 CHAINS (146.52 FEET).*
- [05] BENTON COUNTY CORNER RESTORATION NO. 247. *TRANSCRIBED FROM RECORD [04] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.*
- [06] BENTON COUNTY SURVEY NO. 1189 (OLD NO. 337) FIELD NOTES (FIELD BOOK 83, PAGE 4) BY WALTER W. LARSEN, D.C.S., NO DATE GIVEN. *FOUND OAKS DOWN. FIR 14" DIA BEARS S77°W, 0.82 CHAINS (54.12 FEET); FIR 16" DIA BEARS S55°E, 0.625 CHAINS (41.25 FEET).*
- [07] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 39, BY UNKNOWN DRAFTSMAN, NO DATE GIVEN. *3/4" PIPE AND BRASS CAP. FIR 14" DIA (CSBT) BEARS S71-1/2°W, 0.844 CHAINS (55.70 FEET); FIR 16" DIA (CSBT) BEARS S49°E, 0.674 CHAINS (44.48 FEET).*
- [08] BENTON COUNTY CORNER RESTORATION NO. 247. *TRANSCRIBED FROM RECORD [07] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.*
- [09] BENTON COUNTY MAP NO. 10-5-00010 BY UNKNOWN DRAFTSMAN, NO DATE GIVEN. *3/4" PIPE AND BRASS CAP 0.122 CHAINS (8.05 FEET) SOUTH OF TOWNSHIP LINE. FIR 14" DIA (CSBT) BEARS S77°W, 0.82 CHAINS (54.12 FEET); FIR 16" DIA (CSBT) BEARS S55°E, 0.625 CHAINS (41.25 FEET).*
- [10] BENTON COUNTY SURVEY NO. 9041 BY UNKNOWN DRAFTSMAN, MARCH 30, 1927. *3/4" PIPE AND BRASS CAP. FIR 14" DIA (CSBT) BEARS S71-1/2°W, 0.844 CHAINS (55.70 FEET); FIR 16" DIA (CSBT) BEARS S49°E, 0.674 CHAINS (44.48 FEET).*
- [11] BENTON COUNTY SURVEY NO. 9218 BY HARVEY M. CHRISTENSEN, P.L.S., DATED JUNE 21, 1997. *FOUND 2.25" BRASS CAP MARKED "MCDONALD FOREST S34 S35", 2' ABOVE GROUND. D. FIR 14" DIA BEARS N14°E, 15.2 FEET, BLAZED AND SCRIBED "S35 BT"; D. FIR 20" DIA BEARS N74°W, 44.6 FEET, BLAZED AND SCRIBED "S34 BT"; D. FIR 21" DIA BEARS S66°W, 11.4 FEET, BLAZED AND SCRIBED "X" "BT"; D. FIR 19" DIA BEARS S43°E, 41.2 FEET, BLAZED AND SCRIBED "X" "BT".*

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME

CORNER RESTORATION BOOK NO. 1

For Road #302

Sec. cor. to sect 10, 11, 14 & 15 Tp. 11 S. R. 6. W.  
 Set a barrowtooth between two brick under a brick (35umps stl.)  
 Fir 6" in dia. bears S. 5° 40' W. 1798 chs.  
 Oak 16" " " N. 55° 43' W. 2.326 "  
 Witnessed W.H. Ellenburgh & A.C. Johnson June 27, 1912.

Cor. sec. 34 & 35 Tp 10 S. R. 5 W.  
 Set 4" x 4" x 30" Oak stake for cor. from which  
 an Oak 12" dia. br. N 17° 15' E 2.17 lbs dist.  
 an Oak 10" " " N 54° 30' W 2.22 "

1/4 cor. sec. 34 Tp 10 S R 5 W Tp line  
 Set 4x4x30" Oak stake for cor. from which  
 an Oak 30" dia. br. N 30° 45' E 78 lbs dist.  
 a fir 4" dia. br. N 29° 30' W 2.27 " "

1912.  
 Cor. sec. 33 & 34 Tp. 10 S. R. 5 W. Tp. line  
 Set 4x8x8" stone for cor. from which  
 an Oak 10" dia. br. N 79° 25' E 98 lbs dist.  
 " " 8" " " N 34° 45' W 69.3 " "

1912.  
 1/4 cor. sec. 33 Tp 11 S R 5 W Tp line  
 Set a 4x4x30" Oak stake from which  
 an Oak } N 56° W. 65 ch  
 " Oak } all original notes.  
 " " } S 50° W .366

1912.  
 1/4 cor. sec. 2 & 3 Tp. 11 S R 5 W.  
 Set 4x4x36" Oak stake from which  
 an Oak 24" dia. br. N. 92° 45' E 27.45 lbs dist.  
 " Fir 17" 18" " " N 27° 30' W 2.60 " "  
 " 24" " " " N 20° E .044 " "  
 " " " " S 47° E .158 " "

1912.  
 1/4 cor. sec. 3 & 4 T. 11 S R. 5 W.  
 Set 5x5x36" Yew stake for cor. from which  
 a Maple 4" dia. br. S 27° 30' E 97.4 lbs dist.  
 NW original tree standing

1912.  
 W.C.G.  
 1911 103  
 1/4 sec. cor. sec. 4 & 5 T. 11 S. R. 5 W.  
 Removed stone & Set 2" x 30" Cor. axle in place of stone; stone removed and axle set.  
 Set a stone 8x8x16" for cor. from which  
 an Oak 3" dia. br. N 85° 45' E 2.14 lbs dist.  
 " " 4" " " N 7° 30' W 68.4 " "  
 " " 12" " " N 57° 15' E 1.783 stumps stl.  
 " " 14" " " "

1912.  
 1/4 sec. cor. sec. 5 & 6 T 11 S R 5 W  
 Set 4x4x36" fir limit for cor. from which  
 a Maple 12" dia. br. S 12° 20' E 63.3 lbs dist.  
 NW original standing

1912.  
 1/4 cor. sec. 5 Tp. line Tp 11 S R 5 W  
 Set 4x4x30" fir stake for cor. from which  
 a fir 6" dia. br. N 23° E 2.74 lbs dist.  
 Both original trees standing

Corner sections 34 and 35 Twp. 10 S R 5 W

27 247

Reestablishment by W. C. Galloway

June 1912

Set 4 x 4 x 30" Oak stake for corner

Oak 12" in diam bears N 27° 15' E 2.17 lks dist.

Oak 10" in diam bears N 54° 30' W 2.22 lks dist.

-----  
Replacement

Date \_\_\_\_\_

3/4" pipe with brass cap

Fir 14" in diam bears S 71 $\frac{1}{2}$ ° W .844 chains

Fir 16" in diam bears S 49° E .674 chains