

C.S. #108
C.C. Hanson 2nd Co.
H.L. Boyer
L.A. Wells

Cor to Secs 20, 21, 28, & 29. Twp 13 S., R. 7 W.

Orig Stone 4 notches on E or 2 on S face

Fir 24" N. 18° W 0.70 Std.

" 12" N. 45° E 1.85 "

C.S. # 337

C.C. Hanson
H.L. Boyer
L.A. Wells
T.L. Wells
12-1-47

S. E. Cor. Jacob Modie D.L.C. # 46 Twp. 10 S., R. 5. W.

Orig Stone "C 46"

Fir 48" N 20° W 1.00 Std

Fir 36" N 82° 27' E 0.280

C.S. # 157

C.C. Hanson
H.L. Boyer
L.A. Wells
T.L. Wells
8--47

Cor to Secs 18 & 19 Twp. 14 S., R. 7 W., + 13 & 24 R. 7 W.

1/2" Pipe driven through Orig stake by Stratton (Native)

Fir 24" N. 32° 49' W 0.986

" 8" N 53° 19' E 0.491

" 16" S. 42° 25' W 0.297

" 68" S 1° 28' E 1.219 (Sprite)

1/4 Sec Cor between Secs 13 & 24 Twp. 14 S., R. 7 W.

7/8" Pin

N.E. of 3 Maples 14" S. 20° 37' W. 0.532

Cedar 28" N. 1° 05' W. 0.387

Cor to Secs 13, 14, 23 & 24 Twp. 14 S., R. 7 W.

1/8" Pin

Fir 24" (54") N 80° E 0.60 Std

" 24" (42") S 80° E 0.64 "

1/4 Sec Cor between Secs 23 & 24 Twp. 14 S., R. 7 W.

7/8" Pin

Fir 30" West (Mag.) 0.70 Stump Std

Fir 14" N. 19° 33' W 0.271

Fir 18" N. 41° 05' E 0.208

C.S. 131 for O.S.C.

Camp Adair

Feb. 20, 1947.

by KC Galloway C.S.

Witness Don Mullett

and Earl Lintz.

Most N. N.W. corner of Geo. W. Roberts D.L.C. #57 T. 10-5

Set a stone 7"x7"x20", 4" under the surface. High point, Iron bent over top

Set from 5 ash sprouts one of which is,

Ash 6" in dia, bears S. 40° W. 3.640

Oak 18" " " N. 63° E. 4.132

Point on Stone 2'x3'x? S. 10° 48' E. 2.069

Feb. 18, 1947

Roy W. Nelson

and Don Mullett

Most N. N.E. Cor. of Geo. W. Roberts D.L.C. 59 T10-4

Stone in place

Oak 15" S. 55° W. .53 is stump, Oak 13" bears S 3° E. .31 std.

C.S.
Nor
Halt
C.S.
by
and
June
C
As
C.
as
C.
as
C.
by
V.M.
C.
by
Apr
V.M.
hol
C
by
Apr.
V.M.

Most N. N. W. corner of George W. Roberts DLC 57, Twp. 10-5

318

Reestablishment by W. C. Galloway

February 20, 1947

Set a stone 7" x 7" x 20", 4" under the surface, high point, iron bent over
top/ Set from 5 Ash sprouts one of which is
Ash 6" in diam bears S 40° W 3.640 chains
Oak 18" in diam bears N 63° E 4.132 chains
Point on stone 2' x 3' x ? bears S 10°48' E. 2.069 chains

Witnesses Don Mullett and Earl Lintz

CORNER HISTORY T10 S, R5 W, SEC. 24; D.L.L.: GEORGE W. ROBERTS NO. 57 CORNER N-NW # 857030

318
1-240

	DATE	SOURCE	SURVEYOR	MONUMENT & ACCESSORIES	COMMENTS	
1	12/15/1860	ORIG. GLO	L. DAVIS	POST @ MOUND		1
2						2
3	2/20/1947	OLD COR. REST. BK. #1 PG. 244	W.C. GALLOWAY	SET A 7"x7"x20" STONE 4" BGS. HIGH PT. IRON BENT OVER TOP. SET FROM ASH SPROUTS @ 3 B.D.'S		3
4						4
5						5
6						6
7	4 " "	REST. 318	" "	" " " " " " " " " " " "	TRANS. COPY + MAY CONTAIN E + O	7
8						8
9	12/1991		C.J. LIESENFELT		DID NOT FIND BUT MAY @ TRAV. CTRL.	9
10						10
11						11
12						12
13						13
14						14
15						15
16						16
17						17
18						18
19						19
20						20
21						21
22						22
23						23
24						24
25						25
26						26
27						27
28						28
29						29
30						30
31						31

BENTON COUNTY CORNER HISTORY FORM, PAGE 1 OF 1,

105857030H
DATE 6/24/1993

TOWNSHIP 10 SOUTH, RANGE 5 WEST, WILLAMETTE MERIDIAN; SECTION 24 CORNER
DONATION LAND CLAIM GEORGE W. ROBERTS NO. 57 CORNER NORTH-NORTHWEST

COMMON CORNER(S):

THE EASTERLY LINE OF THE DAVID D. DAVIS DLC NO. 40

UPDATES AND REVISIONS:

CORNER RECORDS (PREVIOUS RENEWALS, SURVEYS, ETC.)

- [01] ORIGINAL GLO SURVEY BY L. DAVIS DATED DECEMBER 15, 1860.
- [02] OLD CORNER RESTORATION BOOK NO. 1 PAGE 244 BY W.C. GALLOWAY DATED FEBRUARY 20, 1947.
- [03] CORNER RESTORATION NO. 318 BY W.C. GALLOWAY DATED FEBRUARY 20, 1947.

COMMENTS/LOCATION/ETC:

RECORD [03] IS A TRANSCRIBED COPY OF RECORD [02] AND MAY CONTAIN ERRORS AND OMISSIONS.

IN DECEMBER OF 1991 CURT LIESENFELT AND MARK ANDERSON SEARCHED WITHOUT SUCCESS FOR THIS CORNER USING PHOTO IDENTIFICATION AS CONTROL. ANOTHER SEARCH SHOULD BE CONDUCTED WITH BETTER CONTROL.

NOTES:

THIS IS A MICROSOFT WORD (VERSION 5.0) DOCUMENT NAMED "05857030" CREATED FROM A BOILER PLATE DOCUMENT NAMED "HISTORY", WHICH HAS A STYLESHEET NAMED "CORNER" ATTACHED TO IT.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE. CORVALLIS OR 97333; PH. 757-6821
RESEARCH BY: CURTIS J. LIESENFELT/MARK E. ANDERSON
DATA ENTRY BY: MARK E. ANDERSON