

106240500

DATE 04/03/2006TOWNSHIP 10 SOUTH, RANGE 06 WEST, WILLAMETTE MERIDIAN; SECTION 08 CORNER SOUTH 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

NORTH 1/4 CORNER SECTION 17

RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY DANIEL MURPHY, D.S., DATED NOVEMBER 30, 1853. *SET POST FROM WHICH AN OAK 14" DIA BEARS N60°E, 197 LINKS (130.02 FEET); OAK 12" DIA BEARS S8-1/2°E, 47 LINKS (31.02 FEET).*
- [02] BENTON COUNTY SURVEY NO. 616 (OLD NO. 235) FIELD NOTES (FIELD BOOK 24, PAGE 59) BY BURT WILKES, D.C.S., DATED NOVEMBER 19, 1917. *OLD OAK POST. SET 1" X 30" STEEL TAPERED ROD. DEAD OAK 14" DIA (GLO BT) BEARS N60°E, 1.97 CHAINS (130.02 FEET). FIR 30" DIA BEARS S53-1/2°W, 0.409 CHAINS (26.99 FEET), SCRIBED "CS235BT"; W. FIR 26" DIA BEARS N14-1/2°W, 0.339 CHAINS (22.37 FEET), SCRIBED "CS235BT". TREE NOT DESCRIBED (GLO BT) BEARS S8-1/2°E, 45.5 LINKS (30.03 FEET).*
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 130 BY BURT WILKES, D.C.S., DATED NOVEMBER 21, 1917. *SET 1" X 30" STEEL ROD, TAPERED, FOR CORNER FROM WHICH DEAD OAK 14" DIA (GLO BT) BEARS N60°E, 1.97 CHAINS (130.02 FEET); DEAD OAK 12" DIA (GLO BT) BEARS S8-1/2°E, 0.47 CHAINS (31.02 FEET)(45.5 LINKS); FIR 30" DIA (CSBT) BEARS S53-1/2°W, 0.409 CHAINS (26.99 FEET); W. FIR 26" DIA (CSBT) BEARS N14-1/2°W, 0.339 CHAINS (22.37 FEET).*
- [04] BENTON COUNTY CORNER RESTORATION NO. 336. *TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.*
- [05] BENTON COUNTY SURVEY NO. 873 (OLD NO. 235) BY BURT WILKES, D.C.S., DATED DECEMBER 5, 1917. *SET 1" X 30" STEEL ROD. DEAD OAK 14" DIA (GLO BT) BEARS N60°E, 1.97 CHAINS (130.02 FEET); DEAD OAK 12" DIA (GLO BT) BEARS S8-1/2°E, 0.47 CHAINS (31.02 FEET); FIR 30" DIA (CSBT) BEARS S53-1/2°W, 0.409 CHAINS (26.99 FEET); W. FIR 26" DIA (CSBT) BEARS N14-1/2°W, 0.339 CHAINS (22.37 FEET).*
- [06] BENTON COUNTY MAP NO. 10-6-00006 BY BURT WILKES, D.C.S., DATED DECEMBER 5, 1917. *SET 1" X 30" STEEL ROD. DEAD OAK 14" DIA (GLO BT) BEARS N60°E, 1.97 CHAINS (130.02 FEET); DEAD OAK 12" DIA (GLO BT) BEARS S8-1/2°E, 0.47 CHAINS (31.02 FEET); FIR 30" DIA (CSBT) BEARS S53-1/2°W, 0.409 CHAINS (26.99 FEET); W. FIR 26" DIA (CSBT) BEARS N14-1/2°W, 0.339 CHAINS (22.37 FEET).*
- [07] BENTON COUNTY MAP NO. 10-6-00001 BY UNKNOWN DRAFTSMAN, NO DATE GIVEN. *1" X 30" STEEL ROD, TAPERED. DEAD OAK 14" DIA (GLO BT) BEARS N60°E, 1.94 CHAINS (128.04 FEET); DEAD OAK 12" DIA (GLO BT) BEARS S8-1/2°E, 0.47 CHAINS (31.02 FEET); FIR 30" DIA (CSBT) BEARS S53-1/2°W, 0.409 CHAINS (26.99 FEET); W. FIR 26" DIA (CSBT) BEARS N14-1/2°W, 0.339 CHAINS (22.37 FEET).*

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821**RESEARCH BY:** BERNARD S. ALTENBACH, ENGINEER/SURVEY TECH.**DATA ENTRY BY:** SAME

CORNER RESTORATION BOOK NO. 1

C.S. No. 227 Cont. The Corner of Secs 7, 12, 13 & 18 West boundary T. 105, R. 6 W

C.S. No. 2

- Set 1 1/2" X 36" Steel shaft for Cor from which
- " Fir in diam bears N 60° W .14 chs dist (ump 145 1/2° E)
- " Fir 18 " " " S 98° E .14 " " " " " "
- " Fir 16 " " " " S 2° W .03 " " " " " "
- " Fir " " " " N 40° W .03 " " " " " "
- Fir 20 " " " " N 1° W .169 " " " " " "
- Fir 30 " " " " N 5 1/2° E .55 " " " " " "

Witnessed by W.S. Alcorn, D.R. Kibbey, Jas Watson Nov 16, 1917

" The 1/4 Sec. Cor. between secs. 7 & 18 - T. 105, R. 6 W

- Set plow shear 15" under surface for Cor from which
- Oak 12" in diam bears N 42 3/4° E. 1.013 chs dist
- Oak 8 " " " " N 79 1/2° E. 1.080 " " "

Witnessed by W.S. Alcorn - Jas Watson Nov 24, 1917

C.S. No 235

The Corner of sections 7, 8, 17 & 18, T. 105, R. 6 W

- Set 1 1/2" X 36" Steel shaft with 8" Crank on bottom for Cor from which.
- " Double fit 12" (90) in diam bears S 10° W. 1.140 chs dist " Orig Tree
- " " Fir 10" (36) " " " N 51 1/2° W (97) .58 " " " "
- " " Fir 10" (90) " " " N 10° E. 3.52 " " " "
- " " " 5" (40) " " " S 20° E 1.34 " " " "

Witnessed by W.S. Alcorn, D.R. Kibbey, Jas Watson W.H.S. Smith & Sons Chas, Orville, Nov. 18, 1917

" The 1/4 Sec. Cor. between secs. 17 & 18 T. 105, R. 6 W.

C.S. No. 3

- Set 1 1/2" X 40" Steel shaft for Cor from which
- Oak 8" in diam bears S 87° W. 1.5 - Orig Tree (down)
- " 8 " " " " N 86° E 2.77 (275) " " (down)
- Fir 30" " " " " N 80 1/2° E. 1.223 chs dist - slope not noted.
- Fir 50" " " " " N 80 1/2° W. 1.423 " " " "

Witnessed by W.S. Alcorn, Jas Watson, D.R. Kibbey Nov 18, 1917

" The 1/4 Sec. Cor. between sections 8 & 17 T. 105, R. 6 W

- Set 1" X 30" steel rod - tapered - for Cor from which
- Oak 14" in diam. bears N 60° E. 1.97 chs dist (Orig Tree (down))
- Oak 12" " " " " S 8 1/2° E. 1.77 " " " "
- Fir 30" " " " " S 53 1/2° W. 1.409 " " " "
- White Fir 26" " " " " N 14 1/2° W. 3.39 " " " "

Present - W.S. Alcorn, Jas Watson, D.R. Kibbey, W.H. Smith. Nov. 21, 1917



$\frac{1}{4}$ -Section corner between sections 8 and 17, Twp. 10 S., R. 6 W.

330

Reestablishment by Burt Wilkes

November 21, 1917

Set 1" x 30" tapered steel rod

Oak 14" in diam bears N 60° E

1.97 chains

Oak 12" in diam bears S 8 $\frac{1}{2}$ ° E

.47 chains

Fir 30" in diam bears S 53 $\frac{1}{2}$ ° W

.409 chains

W. Fir 26" in diam bears N 14 $\frac{1}{2}$ ° W

.339 chains

Witnesses W. S. Alcorn, Jas. Watson, D. R. Kibby, W. H. Smith