

106300400

DATE 01/26/2018TOWNSHIP 10 SOUTH, RANGE 6 WEST, WILLAMETTE MERIDIAN; SECTION 16 CORNER SOUTHWEST
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHEAST CORNER SECTION 17
NORTHEAST CORNER SECTION 20
NORTHWEST CORNER SECTION 21**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY DANIEL MURPHY, D.S., DATED SEPTEMBER 22, 1854. *SET POST FROM WHICH AN OAK 36" DIA BEARS N25°E, 357 LINKS (235.62 FEET); AN OAK 9" DIA BEARS N80°W, 233 LINKS (153.78 FEET); WITH TRENCH AS PER INSTRUCTIONS.*
- [02] BENTON COUNTY SURVEY NO. 10180 (OLD NO. 204) FIELD NOTES (FIELD BOOK 34, PAGE 30) BY WALTER W. LARSEN, DATED JUNE 7, 1924. *SET 1/2" ROD AND PLATE IRON. OAK 12" DIA BEARS S74°W, 2.612 CHAINS (172.39 FEET); OAK 12" DIA BEARS N19-1/2°W, 3.488 CHAINS (230.21 FEET).*
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 173, BY WALTER W. LARSEN, D.C.S., DATED JUNE 7, 1924. *SET 1/2" IRON ROD AND PLATE. OAK 12" DIA (CSBT) BEARS S74°W, 2.612 CHAINS (172.39 FEET); OAK 12" DIA (CSBT) BEARS N19-1/2°W, 3.488 CHAINS (230.21 FEET).*
- [04] BENTON COUNTY CORNER RESTORATION NO. 349. *TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.*
- [05] BENTON COUNTY MAP NO. 10-6-00005 BY W. C. GALLOWAY, C.S., DATED FEBRUARY 24, 1917. *SET 1/2" ROD ON IRON PLATE. OAK 9" DIA (GLO BT) BEARS N80°W, 2.33 CHAINS (153.78 FEET); OAK 12" DIA (CSBT) BEARS S74°W, 2.612 CHAINS (172.39 FEET); OAK 12" DIA (CSBT) BEARS N19-1/2°W, 3.488 CHAINS (230.21 FEET).*

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME

W.W. Larsen
M.S. Woodcock.
Savage.
Mack

N.W. Cor. F.A. Horning Cl. 53 T.115 R.5W
Set stone from which a 3/4" pipe
bears south .303 chains.

W.W.L.
Howard. Parkes.

1/4 cor. betw. sec's. 2 & 3 T.115 R.4W.
Stone 8"x8"x18" on fence line.
Oak 1 1/2" in diameter bears N50°W. 1.135 chains
" post 12" " " south .030 "

C.S. 333

1/4 sec. cor. betw. sec's. 2 & 11 T.115 R.4W.
Set 1/2" pipe for witness 3.068 North + .51 West
of true corner
Fir 3 1/2" N. 75° W. 68
Maple 8" N 15° W .22

"

1/4 cor. between sec's. 1 & 2 T.115 R.4 W.
in cherry orchard - nothing set but falls
East 40.00 chains and south .604 chains
from a 1" pipe near the center of sec. 2.
and is also south 40.024 from a 3/4" pipe
at N.E. corner thereof.

R.4W

not orig. post

T.11-4

C.S. 204
June 7, 1924
Howard Bush
Bud. Alborn
Doc. + By Frantz

N.E. cor. sec. 20 ^{July 21} T.10 S R.6 W.
Set 1/2" iron rod + plate
Oak 12" 574°W. 2.612 chains.
" 12" in dia. bears N. 19 1/2° W. 3.488 chains

C.S. 334
July 29, 1924
W.W.L.
H.L. Mack
Byron Taylor.

S.W. Corner of Polly Belknap Cl. 39 T.14 S R.6 W.
Set 3/4" pipe
Ash 18" in dia bears S 46 1/2° E .658 chs. dis.
Fence west .430 " "

C.S. 335
Aug. 8, 1924
W.W.L.
Langelle

N.E. Cor. Sec. 10, T.115. R.7W
Set. Fir limb from which a
Fir 12" in dia. bears S. 78° W. .68 chs
all standing " 12" " " " N 84° W. .44 "
" 12" " " " " N 15° E. 1.15 "
" 15" " " " " S. 32° E. 1.20 "

1/4 cor. between Secs 3 & 10 T.115. R.7W.
Set 3/4" rod by post in place of orig
stake from which
a Fir 15" in dia bears N. 48° E. .804 chs.
" " " " " N 17° W gone
" " " " " S 84° E (4.30) 3.40

Sept 18, 1924
W.W.L.
H. Hubbard
Pete Whitaker

N.W. Cor. Wiley Winkle Cl. 48 T.13 S R.5 W
Set horse shoe + parts of orig stone
N.E. Cor Cl 50 bears south 9.739 chs.

Corner of Sections of 16, 17, 20 and 21 in 10-5

Reestablishment by W. C. Galloway

393

349

June 7, 1924

Set $\frac{1}{2}$ " iron rod and plate

Oak 12" S. 74° W.

Oak 12" N. $19\frac{1}{2}^{\circ}$ W.

2.612 chs.

3.488 chs.

Witnesses Howard Rush and Bud Alcorn