

**106300440**

DATE 01/26/2018TOWNSHIP 10 SOUTH, RANGE 6 WEST, WILLAMETTE MERIDIAN; SECTION 16 CORNER WEST 1/4  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

EAST 1/4 CORNER SECTION 17

**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY DANIEL MURPHY, D.S., DATED SEPTEMBER 22, 1854. *SET POST FROM WHICH AN OAK 12" DIA BEARS S55°E, 26 LINKS (17.16 FEET); AN ASH 8" DIA BEARS N84°W, 64 LINKS (42.24 FEET).*
- [02] BENTON COUNTY SURVEY NO. 616 (OLD NO. 235) FIELD NOTES (FIELD BOOK 24, PAGE 60) BY BURT WILKES, D.C.S., DATED NOVEMBER 21, 1917. *STONE 18" X 14" X 8" WITH "CS" ON WEST FACE AND "+" ON TOP. DEPOSIT GLASS AND BROKEN STOVE CASTINGS UNDERNEATH. ASH 8" DIA (GLO BT) BEARS N84°W, 0.64 CHAINS (42.24 FEET), NO MARKS ELIGIBLE; OAK 4" DIA BEARS S34°W, 0.294 CHAINS (19.40 FEET), "CS235 BT"; OAK 5" DIA BEARS S31°35'E, 0.730 CHAINS (48.20 FEET), "CS235 BT".*
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 131, BY BURT WILKES, D.C.S., DATED NOVEMBER 21, 1917. *SET STONE 18" X 14" X 8" MARKED "CS" ON WEST FACE AND "+" ON TOP. DEPOSIT BROKEN GLASS AND STOVE CASTINGS UNDERNEATH. ASH 8" (24") DIA BEARS N84°W, 0.64 CHAINS (42.24 FEET), "ORIGINAL TREE?"; OAK 4" DIA (CSBT) BEARS S34°W, 0.294 CHAINS (19.40 FEET); OAK 5" DIA (CSBT) BEARS S31-1/2°E, 0.730 CHAINS (48.20 FEET).*
- [04] BENTON COUNTY CORNER RESTORATION NO. 348. *TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.*
- [05] BENTON COUNTY SURVEY NO. 873 (OLD NO. 235) BY BURT WILKES, D.C.S., DATED DECEMBER 5, 1917. *SET SANDSTONE 18" X 14" X 8". DEPOSIT GLASS AND CAST IRON. ASH 8" (24") DIA (GLO BT) BEARS N84°W, 0.64 CHAINS (42.24 FEET), STUMP; OAK 4" DIA (CSBT) BEARS S34°W, 0.294 CHAINS (19.40 FEET); OAK 5" DIA (CSBT) BEARS S31-1/2°E, 0.730 CHAINS (48.20 FEET).*
- [06] BENTON COUNTY MAP NO. 10-6-00006 BY BURT WILKES, D.C.S., DATED DECEMBER 5, 1917. *SET SANDSTONE 18" X 14" X 8". DEPOSIT GLASS AND CAST IRON. ASH 8" (24") DIA (GLO BT) BEARS N84°W, 0.64 CHAINS (42.24 FEET); OAK 4" DIA (CSBT) BEARS S34°W, 0.294 CHAINS (19.40 FEET); OAK 5" DIA (CSBT) BEARS S31-1/2°E, 0.730 CHAINS (48.20 FEET).*

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME

## CORNER RESTORATION BOOK NO 1

C.S. No. 235

The  $\frac{1}{4}$  Sec. Cor. between 16 & 17 - T. 10 S., R. 6 W.Set Stone 18" x 14" x 8" marked C.S. on W face corner top. From which  
Deposit broken Glass & Stone Castings underneath.

" Fir 8" in diam. bears N 84° W. 64" Chs. dist. Orig Tree?

Oak 5" " " " S. 31 1/2° E. 130 " "

" 4" " " " S. 34° W. 294 " "

Witnessed by Jas. Watson, W.H. Smith.

Nov. 26, 1917

The N. W. Corner of Richard Tatum D.L.C. No. 47 - T. 10 S., R. 6 W.

Set  $\frac{3}{8}$ " x 2 1/4" x 28" iron bar for cor. from which

" Fir 60" in diam. bears N. 70° W. 15" Chs. dist. Orig Tree. (dead)

Fir 24" " " " S. 18 1/2° E. 1.812 " "

Oak 3" " " " S. 9° W. 180 " "

Witnessed by W.S. Alcorn, Jas. Watson, J.R. Kibbey, &amp; W.H. Smith No 26, 1917

The S.W. Corner of The Richard Tatum D.L.C. No. 47 - T. 10 S., R. 6 W.

Set two plow shears bolted end to end for cor. from which

" W. Fir 10" in diam. bears N. 70° W. 43" Chs. dist. Orig Tree (down)

" Maple 10" " " " East .05 " " "

" Fir 10" " " " S. 9° W. 1325 " "

" W. " 28" " " " N. 56 1/2° W. 530 " "

" W. " 6" " " " N. 70° W. 578 " "

Witnessed by W.S. Alcorn, Jas. Watson, J.R. Kibbey, Low. Townsend

and P. Price Nov 23, 1917

C.S. No. 236

The Standard  $\frac{1}{4}$  Sec. Cor. to Section 5 - T. 10 S., R. 4 W.

Set Granite Stone 10" x 8" x 14" for Corner - from which

" Oak 9" in diam. - bears S. 53 1/2° W. 303 Chs. dist.

Tripple Oak 10" " " " S. 19° E. 385 " "

Oak 15" (24) " " " S. 59° W. 1.00 " " Orig. Tree

Witnessed by H. Densham &amp; J.H. Wilson Dec. 13, 1917

The <sup>Most</sup> S. W. Corner of The Anthony Roberts D.L.C. No. 41 - T. 10 S., R. 4 W.Set two bottles - quart underneath and pint on top for Cor. from <sup>which</sup>

" Oak in diam. bears N. 1° E. 200" Chs. Dist. Orig Tree

" Oak 22" " " " N. 50 3/4° E. 93 " " "

" Oak 6 3/4" " " " N. 8 1/2° E. 173 " "

" Oak 7" " " " N. 76 1/2° E. 173 " "

" Oak 4" " " " N. 37 1/2° E. 139 " "

Witnessed by H. Densham &amp; J.H. Wilson

Dec. 22, 1917

1/4-Section corner between 16 and 17, Twp. 10 S., R. 6 W.

592548

Reestablishment by Burt Wilkes

November 21, 1917

Set stone 18" x 14" x 8" marked C. S. on W. face and + on top  
Deposit broken glass and stove castings underneath.

Ash 8" in diam bears N 84° W

.64 chains

Oak 5" in diam bears S 31 1/2° E

.730 chains

Oak 4" in diam bears S 34° W

.294 chains

Witnessed by Jas. Watson and W. H. Smith