

DATE 01/15/2004

TOWNSHIP 10 SOUTH, RANGE 06 WEST, WILLAMETTE MERIDIAN; SECTION 32 CORNER N/A
DONATION LAND CLAIM JAMES WATSON NO. 40 CORNER SOUTH-SOUTHWEST

COMMON CORNER(S):

POINT ON NORTH LINE OF WASHINGTON PATTERSON DONATION LAND CLAIM NO. 37

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES OF THE JAMES WATSON DONATION LAND CLAIM (DLC) NO. 40 BY DENNIS HATHORN, D.S., DATED DECEMBER 8, 1854. **SET POST FROM WHICH AN OAK 6" DIA BEARS S72°W, 406 LINKS (267.96 FEET) AND AN OAK 18" DIA BEARS N42°W, 540 LINKS (356.40 FEET).**
- [02] BENTON COUNTY SURVEY NO. 203 FIELD NOTES (FIELD BOOK 7, PAGE 45) BY J. A. GANONG, D.C.S., DATED FEBRUARY 7, 1911. **CORNER NOT DESCRIBED.**
- [03] BENTON COUNTY OLD SURVEY NO. 177 OF ROAD NO. 351, FIELD NOTES (FIELDBOOK 18, PAGE 2) BY W. C. GALLOWAY, C.S., DATED SEPTEMBER 17, 1914. **SET 1-1/4" PIPE. OAK 6" DIA (GLO BT) BEARS S71°50'W, 4.06 CHAINS (267.96 FEET) STANDING; OAK 18" DIA (GLO BT) BEARS N44°40'W, 5.40 CHAINS (356.40 FEET) STANDING, TO BE STUMP. OAK 6" DIA BEARS N58°10'W, 4.329 CHAINS (285.71 FEET). THE NOTE "SET 1-1/4" IRON ROD WEST 3.395 CHAINS (224.07 FEET)" HAS BEEN CROSSED OUT.**
- [04] BENTON COUNTY CORNER RESTORATION BOOK 1, PAGE 83 BY W. C. GALLOWAY, C.S., DATED SEPTEMBER 19, 1914. **SET 1-1/4" PIPE. OAK 6" DIA (GLO BT) BEARS S71°50'W, 4.06 CHAINS (267.96 FEET) STANDING; OAK 18" DIA (GLO BT) BEARS N44°40'W, 5.40 CHAINS (356.40 FEET) STANDING, TO BE CUT. OAK 6" DIA BEARS N58°10'W, 4.329 CHAINS (285.71 FEET).**
- [05] BENTON COUNTY CORNER RESTORATION NO. 404. **TRANSCRIBED FROM RECORD [04] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.**
- [06] BENTON COUNTY SURVEY NO. 541 FIELD NOTES (FIELD BOOK 22, PAGE 49) BY W. C. GALLOWAY, C.S., DATED FEBRUARY 16, 1916. **CORNER NOT DESCRIBED.**
- [07] BENTON COUNTY RECORD OF ROADS BOOK NO. 2, PAGE 513, DATED AUGUST 20, 1920. **1-1/4" IRON ROD.**
- [08] BENTON COUNTY ROAD 16530 (OLD ROAD NO. 424) ROLL MAP BY WALTER W. LARSEN, D.C.S., DATED AUGUST 24, 1920. **1-1/4" ROD.**
- [09] BENTON COUNTY SURVEY NO. 721 (ROAD SURVEY NO. 424) FIELD NOTES (FIELDBOOK 25, PAGE 21) BY WALTER W. LARSEN, D.C.S., DATED SEPTEMBER 28, 1920. **IRON PIPE.**

NOTES:

THIS IS A MICROSOFT WORD 2000 DOCUMENT NAMED "06840030" CREATED FROM A BOILER PLATE DOCUMENT NAMED "HISTORY", WHICH HAS A STYLESHEET NAMED "CORNER" ATTACHED TO IT.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE

ADDRESS: 360 S.W. AVERY AVE. CORVALLIS OR 97333; PH. 766-6821

RESEARCH BY: BERNARD S. ALTENBACH, ENGINEER/SURVEY TECH.

DATA ENTRY BY: BSA

SEE CORNER FILE NO. 106039020

SCANNED

403

N. W. corner of Isaac King C1 39, Twp. 10 S. R. 6 W. W. M. ⁴⁵¹
Reestablishment by W. C. Galloway April 1947

Reeset original stone which had been dug out, Stone 4" x 8" x 18"
Set in exact place from a $\frac{5}{8}$ " iron rod S 30° and $\frac{3}{4}$ " pipe N. 30°
Witness Edson Damm

Sec. 28

404

Most south S. W. corner of James Watson DLC 40, Twp 10 S R 6 W

Reestablishment by W. C. Galloway

Set $1\frac{1}{4}$ " pipe

Oak 6" in diam bears S71° 50' W

Oak 18" in diam bears N 44° 40' W

Oak 6" in diam bears N 58° 10' W

Witnesses Richard Kingery Walter Norton

September 19, 1914

432
4.06 chains (standing)
5.40 chains (standing)
4.329 chains

Sec. 32

C.S. Road #345 S.W. corner of Andrew Foster, D.L.C. # 37 Tp. 13 S. R. 6 W.
Stone 12"x16"x16" set. A 1 1/4" pipe West 3.20 cks.

Witnesses D.B. Farley, A.H. Gray, Virgil Arney, P.J.A. Bink, L.J. Romo. June 26, 1914.

" " S.E. corner of Andrew Foster, Cl. # 37 Tp. 13 S. R. 6 W. All points gone.
Plains, Nebraska - set 3/4" pipe 30' south 3/4" pipe North 30', online set in Johnston
Set 1 1/4" pipe oak stake North 20 feet, oak stake South 20 feet Rock Bar
corner set on line proportional dist. from NE. of Cl. 37 E. S.E. of C. 38.
Witnesses above June 26, 1914.

" " N.W. corner of James Foster Cl. # 38 Tp. 13 - 6.
Set 1 1/4" pipe.

Stone 12"x16"x16" East. 3.20 cks.
Witnesses as above June 26, 1914.

C.S. # 18 cont. 1/4 sec. cor. between secs. 25 & 30 Tp. 14 S. Trs. 47 & 5 W.
Set a 1 1/4" pipe galv.
Set a 1 1/4" pipe in cen. of maple stump S. E. .065 cks.
Set a pipe 20 feet North
Witnesses G.H. Bath July 29, 1914.

914 Road #346 West S.E. cor. of Thomas P. Adams D.L.C. # 48 Tp. 12 S R 5 W.
Set 3/4" iron rod
1 1/4" pipe bears N 25' W. 40.075 cks.
Center of R.R. N. 89° 29' E. 15.006 cks.
Witness G.H. Bath. August 12, 1914.

Road # 357 North of Int. of James Watson Cl. # 40. Tp. 10 S. R. 6 W.
Set 1 1/4" pipe oak stump 12" S. 35° E. .32 cks.
Oak 15" in dia. bears N. 10° E. .24 cks. set.
Pin 32" " " N. 85° E. .955"
Witnesses Richard Kingery, S. A. Graves, J.M.R.A. Fowler Sept. 15, 1914

" " S.W. cor. of James Watson D.L.C. # 40. Tp. 10 S. R. 6 W.
Set 1 1/4" pipe
Oak 6" in dia. bears S 71° 50' W. 4.06 cks. set.
" 18" " " N. 44° 40' W. 5.40 cks. " 20 & cut.
" 6" " " N. 58° 10' W. 4.329" (285.71)
Witnesses Richard Kingery, Walter Notton, Sept. 19, 1914

" " Sec. cor. to sec. 5, 6, 7 & 8. Tp. 11 S. R. 6 W.
Set 1 1/4" shaft.
Oak 6" in dia. bears N. 6° 20' E. 1.077 cks.
Pin 18" " " S. 42° W. 1.72. " set.
" 12" " " N. 87° 30' W. .510 "
Witnesses Richard Kingery, Walter Notton, Sept. 24, 1914.