

107400140

DATE 09/07/2017TOWNSHIP 10 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 33 CORNER EAST 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**
WEST 1/4 CORNER SECTION 34**RECORDS (INFORMATION IN BOLD /ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY DENNIS HATHORN, D.S., DATED AUGUST 26, 1856. SET POST FROM WHICH A FIR 36" DIA BEARS S78°E, 165 LINKS (108.90 FEET); A FIR 40" DIA BEARS N0°30'W, 292 LINKS (192.72 FEET).
- [02] SURVEY NO. 38 FROM PAGE 47 OF THE RECORD BOOK OF SURVEYS BY ANDREW L. PORTER, C.S., DATED JULY 19, 1889. BEGINNING AT 1/4 SECTION CORNER BETWEEN SECTIONS 33 AND 34. CORNER NOT DESCRIBED.
- [03] REESTABLISHMENT NOTES FROM PAGE 49 OF THE RECORD BOOK OF SURVEYS BY ANDREW L. PORTER, C.S., DATED JULY 20, 1889. SET NEW POST. MARKED A FIR 14" DIA BEARS S47°W, 54 LINKS (35.64 FEET); A MAPLE 8" DIA BEARS S65°E, 52 LINKS (34.32 FEET). OLD TREES BADLY DEFACTED BY FIRE.
- [04] BENTON COUNTY SURVEY NO. 535 (OLD NO. 247) FIELD NOTES (FIELD BOOK 20, PAGE 56) BY W. C. GALLOWAY, C.S., DATED DECEMBER 14, 1915. SET QUART BOTTLE. MAPLE 10" DIA (CSBT) BEARS S66°E, 0.515 CHAINS (33.99 FEET); FIR 12" DIA (CSBT) BEARS S46°W, 0.542 CHAINS (35.77 FEET).
- [05] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 101, BY W. C. GALLOWAY, C.S., DATED DECEMBER 14, 1915. SET QUART BOTTLE IN PLACE OF OLD STAKE WITH LETTERS ON. GOVERNMENT FIELD NOTES DO NOT FIT AT ALL. ORIGINAL MAPLE 10" DIA (CSBT) BEARS S66°E, 0.515 CHAINS (33.99 FEET) TO FACE; ORIGINAL FIR 12" DIA (CSBT) BEARS S46°W, 0.542 CHAINS (35.77 FEET) TO FACE.
- [06] BENTON COUNTY CORNER RESTORATION NO. 588. TRANSCRIBED FROM RECORD [05] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.
- [07] BENTON COUNTY MAP NO. 10-7-00018 BY W. C. GALLOWAY, C.S., DATED DECEMBER 20, 1915. QUART BOTTLE. MAPLE 10" DIA (CSBT) BEARS S66°E, 0.515 CHAINS (33.99 FEET); FIR 12" DIA (CSBT) BEARS S46°W, 0.542 CHAINS (35.77 FEET).
- [08] BENTON COUNTY SURVEY NO. 6324 BY ARNOLD BRUBAKER, P.L.S., DATED MARCH 8, 1977. FOUND QUART BOTTLE ON EAST SIDE OF CORNER POST. REPLACED WITH 5/8" REBAR. MAPLE 10" DIA (CSBT) BEARS S66°E, 34 FEET, DOWN; FIR 12" DIA (CSBT) BEARS S46°W, 35.77 FEET, ROTTEN STUMP. D. FIR 12" DIA BEARS N34°W, 25.75 FEET, MARKED "E1/4 S33" AND "BT"; D. FIR 14" DIA BEARS N37°E, 17.1 FEET, MARKED "W1/4 S34" AND "BT".
- [09] BENTON COUNTY SURVEY NO. 9875 BY JIM S. PETERSON, P.L.S., DATED MARCH 2, 1995. FOUND 5/8" IRON ROD AT FENCE CORNER. FIR 16" DIA BEARS N34°W, 25.75 FEET, HEALED FACE; FIR SNAG 14" DIA BEARS N37°E, 17.1 FEET, SCRIBING VISIBLE. FIR 8" DIA BEARS S44°E, 49.7 FEET, MARKED "1/4 S34 BT".

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME

County Survey #416

S.E. cor. of James Wood Ct. # 65 T. 115. R. 6 W.
 Set 1 1/2" x 18" iron pin with glass orig. cor. orig. trees are now stumps
 W. Fir 7" in dia. bears N. 40° E. .058 chs.
 R. " 28" " " S. 25° 30' E. .275 "
 W. " 12" " " N. 55° 40' W. .446 "
 Witnesses A.J. Price, W.R. Read, R.E. Nelson & F.M. LaBear Dec. 7 1915.

Corner to 16, 17, 20 & 21 T. 115. R. 6 W.
 Set Qt. bottle 17" under surface S.E. oak gone.
 Oak 30" in dia. bears N. 72° 30' E. 4.76 chs. std.
 " 16" " " S. 47° W. 2.46 "
 Witnesses as above Dec. 3, 1915.

1/4 sec. corner between secs. 15 & 16 T. 115. R. 6 W.
 Set 3/8" x 1 1/2" x 35" iron bar N.W. tree down
 Orig. Oak 18" in dia. bears N. 17° E. 3.02 chs. std.
 Fir 5" " " N. 59° 30' E. .210 "
 Witnesses A.J. Price W.R. Read & B.M. LaBear Dec. 4, 1915.

Corner to secs. 15, 16, 21 & 22 T. 115. R. 6 W.
 Set 3/8" x 1 1/2" x 30" iron bar with glass
 Stone mound stone scattered a little
 Witnesses as lost corner Dec. 4, 1915.

1/4 sec. cor. between secs. 16 & 21 T. 115. R. 6 W.
 Set 3/8" x 2" x 32" iron bar
 Orig. Oak 18" in dia. bears N. 22° E. .48 chs. std.
 " 18" " " S. 52° W. .217 "
 Witnesses A.J. Price & W.R. Read Dec. 6, 1915.

CS # 246 is cont.
 listed on page 106
 5182
 CS # 247
 is delivery CS.

1/4 sec. cor. between secs. 33 & 34 T. 10 S. R. 7 W. golf field, holes do not fit at all.
 Set Qt. bottle in place of old stake with letters on
 Orig. Maple 10" in dia. bears S. 66° E. .515 chs. to face.
 Orig. Fir 12" " " S. 46° W. .542 "
 Witnesses James Stenback, A.E. Wetherford & Hiram Parker Dec. 14 1915

1/4 sec. cor. between secs. 32 & 33 T. 10 S. R. 7 W.
 Set Aug. for cor. orig. witness trees dead.
 Fir 22" in dia. bears S. 81° 30' W. .362 chs.
 " 15" " " N. 13° W. .413 "
 Witnesses as above Dec. 15, 1915.

1/4 sec. corner on the south of sec. 33, 2nd stn. parallel T. 10 S. R. 7 W.
 Set a cedar post 5" x 7" x 36"
 Fir 20" in dia. bears N. 30° 30' E. .095 chs.
 Orig. " 30" " " S. 61° E. .46 "
 " 24" " " S. 16° E. .137 "
 Witnesses as above Dec. 16, 1915.



¼-Section corner between sections 33 and 34, Twp. 10 S., R. 7 W.

Reestablishment by W. C. Galloway

December 14, 1915

Set Qt. bottle in place of old stake with letters.

Maple 10" in diam bears S 66° E

Fir 12" in diam bears S 46° W

.515 chains

.542 chains

Witnesses James Stenback, A. B. Whatherford, Hiram Parker, and Henry Oleman