

1 14846060

DATE 10/05/2021

TOWNSHIP 11 SOUTH, RANGE 4 WEST, WILLAMETTE MERIDIAN; SECTION 7 CORNER N/A
DONATION LAND CLAIM WILLIAM TAYLOR NO. 46 CORNER WEST-NORTHWEST

COMMON CORNER(S):

NORTHEAST CORNER OF THE WILLIAM H. ELLIOTT DONATION LAND CLAIM NO. 52
POINT ON THE SOUTH LINE OF THE JEREMIAH V. LEWIS DONATION LAND CLAIM NO. 45

RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES OF THE WILLIAM H. ELLIOTT DONATION LAND CLAIM (DLC) NO. 52 BY DENNIS HATHORN, D.S., DATED NOVEMBER 3, 1853. *SET POST, DEPOSITED BRICK AND DUG TRENCH.*
- [02] GENERAL LAND OFFICE (GLO) NOTES OF THE WILLIAM TAYLOR DONATION LAND CLAIM (DLC) NO. 46 BY DENNIS HATHORN, D.S., DATED NOVEMBER 4, 1853. *SET POST, DEPOSITED BRICK AND DUG TRENCH.*
- [03] BENTON COUNTY SURVEY NO. 179 (OLD NO. 76) FIELD NOTES (FIELD BOOK 5, PAGE 73) BY W. C. GALLOWAY, D.C.S., NO DATE GIVEN. *3/4" PIPE SET.*
- [04] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 118, BY W. C. GALLOWAY, D.C.S., NO DATE GIVEN. *3/4" PIPE SET ON LINE FROM SOUTHWEST CORNER OF CLAIM 45 TO SOUTHEAST CORNER OF CLAIM 45.*
- [05] BENTON COUNTY CORNER RESTORATION NO. 653. *TRANSCRIBED FROM RECORD [04] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.*
- [06] BENTON COUNTY SURVEY NO. 179 (OLD NO. 76) MAP BY UNKNOWN DRAFTSMAN, NO DATE GIVEN. *3/4" PIPE.*
- [07] BENTON COUNTY SURVEY NO. 351 (OLD NO. 133) FIELD NOTES (FIELD BOOK 11, PAGE 3) BY F. MARION WILKES, C.S., DATED NOVEMBER 14, 1912. *3/4" PIPE.*
- [08] BENTON COUNTY SURVEY NO. 629 (OLD NO. 271) FIELD NOTES (FIELD BOOK 23, PAGE 73) BY W. C. GALLOWAY, C.S., DATED APRIL 17, 1918. *3/4" PIPE.*
- [09] BENTON COUNTY SURVEY NO. 629 (OLD NO. 271) MAP BY W. C. GALLOWAY, C.S., DATED APRIL 26, 1918. *3/4" PIPE.*
- [10] BENTON COUNTY MAP NO. 11-4-00010 BY W. C. GALLOWAY, C.S., DATED APRIL 26, 1918. *3/4" PIPE.*
- [11] BENTON COUNTY SURVEY NO. 3709 BY VERLE C. MOORE, P.L.S., DATED DECEMBER 1, 1962. *FOUND 3/4" IRON PIPE.*
- [12] BENTON COUNTY SURVEY NO. 9754 BY TYLER B. PARSONS, P.L.S., DATED JANUARY 7, 2003. *FOUND 3/4" IRON PIPE BENT AT END OF FENCE.*

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME

C.S. #255
Continued

S.E. corner of Eli Summers D.L.C. # 67 T. 11 S. R. 6 W.

Set 1" X 24" I pin point of oak stake found in hole
 Oak 4" in dia. bears S. 16° 20' W. .141 chs.
 " 5" " " " N. 41° 40' W. .101 "
 " 30" " " " N. 72° 50' E. .84 " stump std.
 " 24" " " " S. 56° 50' W. .08 " " "
 " 14" " " " N. 41° 40' W. 1.00 " " "

Witnesses A.C. Johnson, C.E. Jackson & J.E. Mc Donough Nov. 17, 1916.

C.S. #128
continued.

Sec. Cor. bet. secs. 32 & 33 on 3rd. Std. parallel T. 13 S. R. 7 W.

Set Sand stone 6" X 8" X 9" . has 4 notches. Had turned over ^{position.} outgl.
 Cedar N. 75° E. 43 chs. lying down.
 Mkd. cedar 10" in dia. bears S. 75° E. .484 chs.
 Maple 12" " " " N. 40° W. .69 " std.

Witness Geo. T. Sebrell. Jan. 17, 1917.

"

1/4 sec. cor. on north of sec. 5 T. 14 S. R. 7 W.

Set 3/8" X 21" iron rod Fir stump 30" S. 18° E. 2.14 chs.
 Fir 30" in dia. bears S. 47° E. .475 chs.
 " 8" " " " S. 64° 10' W. .588 "

Witness Geo. T. Sebrell Jan 17, 1917.

"

1/4 sec. cor. bet. secs. 3 & 8 T. 14 S. R. 7 W.

Set 3/4" X 30" pipe
 Fir 12" in dia. bears N. 10° E. .21 chs. std.
 " 24" " " " S. 81° 30' E. .48 " "

Witnesses Geo. T. & Benj. Sebrell Jan 19, 1917.

"

1/4 sec. cor. bet. secs. 5 & 6 T. 14 S. R. 7 W.

Set 3/4" pipe 30" long Vine maple bunch N.E., Dogwood N. 80° W. 62
 W. fir 54" in dia. bears. S. 33° E. 1.122 chs. blazed trees
 R. " 44" " " S. 75° 30' W. .777 " N. & S.

Witness Geo. T. Sebrell Jan. 22, 1917.

S.W. corner of D.D. Stroud's Cl. # 44 T. 11 S. R. 4 W.

Granit stone set good position for both fences.

S.E. corner of J.V. Lewis D.L.C. # 45 T. 11 S. R. 4 W.

1" pipe already set

Most West N.W. cor. of W. Taylor D.L.C. # 46 T. 11 S. R. 4 W.

3/4" pipe set on line from S.W. cor. of Cl. # 45 to S.E. cor. of Cl. # 45.



C.S. #22

By Burt W.

C.S. #22

By Burt W.

C.S. #22

By Burt W.

1

11.

"

Most West N. W. corner of William Taylor DLC 46, Twp. 11 S., R. 4 W.

653

Reestablishment by W. C. Galloway

Date _____

895

$\frac{3}{4}$ " pipe. Set on line from S. W. corner of Cl 45 to S. E. corner of Cl 45.