

**115600200**

DATE 08/31/2021TOWNSHIP 11 SOUTH, RANGE 5 WEST, WILLAMETTE MERIDIAN; SECTION 25 CORNER SOUTHWEST  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHEAST CORNER SECTION 26  
NORTHEAST CORNER SECTION 35  
NORTHWEST CORNER SECTION 36**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY GEORGE W. HYDE, D.S., DATED JULY 3, 1852. *SET POST FROM WHICH AN ASH 18" DIA BEARS S22°W, 588 LINKS (388.08 FEET); ASH 8" DIA BEARS N51-1/2°W, 250 LINKS (165.00 FEET); ASH 18" DIA BEARS N10°E, 1043 LINKS (688.38 FEET); MADE TRENCH AS PER INSTRUCTIONS.*
- [02] BENTON COUNTY SURVEY NO. 536 (OLD NO. 129) FIELD NOTES (FIELD BOOK 20, PAGE 60) BY W. C. GALLOWAY, C.S., DATED JANUARY 6, 1916. *SET QUART BOTTLE 10" UNDER SURFACE. ASH 18" DIA (GLO BT) BEARS N10°E, 10.16 CHAINS (670.56 FEET) MEASURED TO FACE, STANDING, REMARKED; BRANCH OF ORIGINAL ASH 18" DIA (GLO BT) BEARS S22°W, 5.86 CHAINS (386.76 FEET) TO "NEW" FACE; REMARKED ASH 8" DIA (NOW 24" DIA) (GLO BT) BEARS N51°10'W, 2.614 CHAINS (172.52 FEET) TO FACE AT BOTTOM.*
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 102 BY W. C. GALLOWAY, C.S., DATED JANUARY 6, 1916. *SET QUART BOTTLE 10" UNDER SURFACE. ASH 18" DIA (GLO BT) BEARS N10°E, 10.16 CHAINS (670.56 FEET) MEASURED TO FACE, STANDING, REMARKED; BRANCH OF ORIGINAL ASH 18" DIA (GLO BT) BEARS S22°W, 5.86 CHAINS (386.76 FEET) TO NEW FACE REMARKED; ASH 8" DIA (NOW 24" DIA) (GLO BT) BEARS N51°10'W, 2.614 CHAINS (172.52 FEET) TO FACE AT BOTTOM, REMARKED.*
- [04] BENTON COUNTY CORNER RESTORATION NO. 729. *TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.*
- [05] BENTON COUNTY MAP NO. 11-5-00018 BY UNKNOWN DRAFTSMAN, NO DATE GIVEN. *SET QUART BOTTLE 10" UNDER SURFACE. FORKED ASH 18" DIA (GLO BT) BEARS N10°E, 10.16 CHAINS (670.56 FEET), STANDING, REMARKED; ASH 18" DIA (GLO BT) BEARS S22°W, 5.86 CHAINS (386.76 FEET) TO FACE OF BRANCH OF OLD TREE; ASH 24" DIA (GLO BT) BEARS N51°10'W, 2.614 CHAINS (172.52 FEET) TO FACE AT BOTTOM, REMARKED.*

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME

## BENTON COUNTY CORNER RESTORATION BOOK NO. 1

CS. 424

C.S. #247

 $\frac{1}{4}$  Sec. cor. between secs. 28 & 33 T. 10S. R. 7W.

Set Qt. bottle snag N 48° E 79 mds snag S. 18° E. 67 std.

Fir 34" in dia. bears S. 1° E. 540 chs.

" 5" " " " S 86° 0' W. 231 "

Witnesses James Stanback, Hiram Parker, Henry Olman &amp; A.B. Weatherford Dec. 18, 1915.

"

Corner to secs 27, 28, 33 & 34 T. 10S R 7W. <sup>found a stone not in place with</sup> <sub>marks on</sub>Set  $\frac{3}{4}$ " x 30" iron rod set corner with fences. orig. notes do not fit trees

Burnt fir 36" in dia. bears S. 83° E. 2.913 chs. to face.

orig. " " 40" " " " N. 14° 30' W. 1.25 " " "

" " " 48" " " " N. 15° E. .55 " " "

Stone 6" x 6" x 5" south 20 feet

Fir 36" in dia. bears S. 77° 25' W. 2.517 "

Witnesses as above also John Bottger Dec. 18 1915.

Continuation SS #124  
W.C. Galloway CS.

Corner to secs. 25, 26, 35 &amp; 36 T. 11S. R. 5W.

Set Qt bottle 10" under surface

Measured to face Ash 18" in dia. bears N. 10° E. 10.16 chs. std. ramkd.

Branch of original " 18" " " " S. 22° W. 5.86 " to new face "

" 8" " " " N. 51° 10' W. 2.614 " to face at bottom <sup>new 24</sup> <sub>in dia.</sub>

Witness M.W. Rosecrans

Jan. 6, 1916.

"

Corner to secs. 26, 27, 34 &amp; 35 T. 11S. R. 5W.

Set Qt. bottle 10" under surface set from ash stump

Prune tree 7" in dia. bears N. 10° 30' W. .311 chs. mtd. 1

" " 7" " " " N. 88° 50' E. .256 " " 1

" " 7" " " " S. 70° 10' W. .305 " " 1

Fir 18" " " " " S. 69° 30' W. 4.813 "

Comb on N. school bldg. bears S. 18° 31' W. Top of Court House S. 28° 06' E.

Witness M.W. Rosecrans.

Jan 7, 1916.

Cont. C.S. 181

 $\frac{1}{4}$  sec. cor. between secs. 1 & 12 T. 15S. R. 6W.

Set 1" x 24" iron rod &amp; stumps std. orig. trees.

Fir 8" in dia. bears S. 33° W. .224 chs.

W. " 10" " " " N. 61° W. .057 "

Witnesses L.A. Houck, Robert &amp; A.R. Kyle Jan. 12, 1916.

CS # 248  
W.C. Galloway CS.

Most w st N.W. cor. of E. Redmour Cl. # 40 T. 14S. R. 8W.

Set a wagon thimble orig. cor. N.W. tree down.

Wkd. Fir 8" in dia. bears S. 53° 30' E. .288 chs.

" 30" " " " S. 28° W. .55 " std.

Witnesses Carl Ogulsky &amp; Edward Taylor March 2, 1916.

"

Interior corner of E. Redmour Cl. # 40 T. 14 S. R. 8 W.

Set a 12 gauge double bbl shotgun bbl.

Oak 18" in dia. bears N. 27° W. 1.88 chs. std.

Witnesses Edd. Taylor, D. D. Loughbottom &amp; C.S. Seely

Feb. 22, 1916.

Corner to Sections 25, 26, 35 and 36, Twp. 11 S., R. 5 W.

729

851

Reestablishment by W. C. Galloway

January 6, 1916

Set Qt. bottle 10" under surface

Ash 18" in diam bears N 10° E

Ash 18" in diam bears S 22° W

Ash 8" in diam bears N 51° 10' W

10.16 chains (std.remkd

5.86 ch.to face(std.)

2.614 ch.to face

Witness M. W. Rosecrans