

116440300

DATE 05/24/2013TOWNSHIP 11 SOUTH, RANGE 6 WEST, WILLAMETTE MERIDIAN; SECTION 22 CORNER SOUTH 1/4
DONATION LAND CLAIM N/A CORNER N/ACOMMON CORNER(S):
NORTH 1/4 CORNER SECTION 27**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)****BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.**

[01] GENERAL LAND OFFICE (GLO) NOTES BY JOSIAH W. PRESTON AND HARVEY GORDON, D.S., DATED AUGUST 4, 1854. SET POST FROM WHICH A W. **OAK 40" DIA BEARS S72°E, 59 LINKS (38.94 FEET); AN ASH 12" DIA BEARS N37°E, 202 LINKS (133.32 FEET).**

[02] BENTON COUNTY SURVEY NO. 571 (OLD NO. 255) FIELD NOTES (FIELD BOOK 22, PAGE 25) BY W. C. GALLOWAY, C.S., DATED OCTOBER 31, 1916. SET **3/4" X 35" BOLT. ASH STANDING, OAK DOWN. ASH 12" DIA (GLO BT) BEARS N37°E, 2.02 CHAINS (133.32 FEET) STANDING. OAK 8" DIA BEARS N40°30'E, 0.303 CHAINS (20.00 FEET); OAK 14" DIA BEARS S13°30'E, 0.319 CHAINS (21.05 FEET).**

[03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 117, BY W. C. GALLOWAY, C.S., DATED NOVEMBER 18, 1916. SET **3/4" X 35" BOLT. ASH STANDING, OAK DOWN. CORNER SOUTH OF MARYS RIVER. ASH 12" DIA (GLO BT) BEARS N37°E, 2.02 CHAINS (133.32 FEET) STANDING HOLLOW. OAK 8" DIA (CSBT) BEARS N40°30'E, 0.303 CHAINS (20.00 FEET); OAK 14" DIA (CSBT) BEARS S13°30'E, 0.319 CHAINS (21.05 FEET).**

[04] BENTON COUNTY CORNER RESTORATION NO. 875. **TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.**

[05] BENTON COUNTY MAP NO. 11-6-00005 BY W. C. GALLOWAY, C.S., DATED NOVEMBER 27, 1916. **3/4" X 35" BOLT. ASH 12" DIA (GLO BT) BEARS N37°E, 2.02 CHAINS (133.32 FEET) STANDING. OAK 8" DIA (CSBT) BEARS N40°30'E, 0.303 CHAINS (20.00 FEET); OAK 14" DIA (CSBT) BEARS S13°30'E, 0.319 CHAINS (21.05 FEET).**

[06] BENTON COUNTY SURVEY NO. 4804 BY BERT W. UDELL, P.E., DATED SEPTEMBER, 1969. **FOUND 3/4" BOLT AND RECENT BEARING TREES. SET 5/8" ROD BEARS S89°39'-1/4'W, 206.58 FEET, EAST OF FENCE ABOUT 6 FEET.**

[07] BENTON COUNTY SURVEY NO. 4928 BY BERT W. UDELL, P.E., DATED MAY 30, 1970. **CORNER NOT TIED OR DESCRIBED.**

[08] BENTON COUNTY SURVEY NO. 5948 BYARNOLD BRUBAKER, P.L.S., DATED OCTOBER 2, 1975. **3/4" BOLT.**

[09] BENTON COUNTY SURVEY NO. 9264 BY THEODORE JAMES LANGTON, P.L.S., DATED NOVEMBER 19, 1996. **FOUND 3/4" IRON BOLT. CORNER LIES IN DENSE BRUSH ABOUT 150' SOUTH OF THE MARYS RIVER AND ABOUT 200' EAST OF A NORTH-SOUTH FENCE. OAK 14" DIA (CSBT) BEARS N40°30'E, 20 FEET, HEALED FACE; OAK SNAG 16" DIA (CSBT) BEARS S13°30'E, 21.05 FEET. OAK 25" DIA BEARS S6°W, 11.25 FEET, HEALED FACE, PREVIOUSLY UNRECORDED.**

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE. CORVALLIS OR 97333; PH. 766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME

CORNER RESTRICTION BOOK NO. 1

- C.S. 455
- 1/4 sec. cor. bet. secs. 13 & 14 T. 11 S. R. 6 W.
Set 3/4" X 22" galv. pipe. orig. cor.
Fir 12" in dia. bears N. 130° 30' E. 2.80 ehs.
" 5" " " S. 75° E. 2.50 " std.
Witnesses John Hallett & A.C. Johnson, Nov. 11, 1916.
- 1/4 sec. cor. between secs. 22 & 23 T. 11 S. R. 6 W.
Set a bot. bottle under stone 8" X 11" X 15"
Oak 2 1/4" in dia. bears N. 52° E. 2.97 ehs. std.
" 20" " " N. 78° W. 2.19 " "
Witness A.C. Johnson Nov. 17, 1916.
- 1/4 sec. cor. bet. secs. 15 & 22 T. 11 S. R. 6 W.
Stone 12" X 12" X 14" & 4" X 12" on top. No trees near.
- 1/4 sec. cor. between secs. 21 & 22 T. 11 S. R. 6 W.
Set bot. bottle 12" under surface
E. corner of house S. 8° 32' E.
Oak 1 1/2" in dia. bears S. 20° 45' W. 8.174 ehs.
Witness Dick Ballard, A.C. Johnson & J.E. McDonough Nov. 18, 1916.
- Corner 76 secs. 21, 22, 27 & 28 T. 11 S. R. 6 W.
Set a stone 4" X 11" X 15" stake hole 24" deep orig. cor.
Oak 4" in dia. bears N. 58° E. 1.683 ehs.
" 12" " " S. 33° 26' E. 3.689 "
" 12" " " S. 17° E. 4.00 " std.
Ash 6" " " S. 16° 23' W. 3.799 "
Oak 10" " " N. 28° 50' W. 5.845 "
Stone 7" X 10" X 15" N. 16° 30' W. 4.85 ehs.
Witnesses Dick Ballard & bro. A.C. Johnson, J.E. McDonough & other Nov. 3, 1916.
(Set by Geo. Mueser but fuller that it had been moved who other corners were, moved to make one nec. miss a corner. The line 3/4" dia. X 11" X 15")
- 1/4 sec. cor. between secs. 22 & 27 T. 11 S. R. 6 W.
Set a 3/4" X 35" bolt Ash std. oak dowel cor. s. of Morris River
Ash 1 1/2" in dia. bears N. 37° E. 2.02 ehs. std. hollow
Oak 8" " " N. 40° 30' E. 3.03 "
" 14" " " S. 13° 30' E. 3.19 "
Witnesses J.E. McDonough & C.E. Jackson, Nov. 18, 1916.
- 1/4 sec. cor. between secs. 10 & 15 T. 11 S. R. 6 W.
Set 3/4" pipe orig. cor. oak dowel
Fir 10" in dia. bears N. 20° E. .48 ehs. std.
" 32" " " N. 71° W. 1.82 "
Witnesses A.C. Johnson, J.E. McDonough & C.E. Jackson, Nov. 16, 1916.
- Most East N.E. cor. of Eli Summers, D.C. # 67 T. 11 S. R. 6 W.
Set Watkins' Limestone bottle 12" under surface also stone & brick bat.
Oak 2 1/4" in dia. bears S. 54° 40' W. 2.775 ehs. unadjusted. 2 stumps check almost exact.
" 14" " " " N. 65° W. 1.690 "
Witness James E. McDonough Nov. 1916.

1/2-Section corner between sections 22 and 27, Twp. 11 S. R. 6 W.

Reestablishment by W. C. Galley

Set a ~~35~~ x 35" bolt, Ash standing, Oak down, Corner S. of Mary's River.

Ash 12" in diam bears N 37° E

2.02 chains (standing)

Oak 8" in diam bears N 40° 30' E

.303 chains

Oak 14" in diam bears S 13° 30' E

.319 chains

Witnesses J. E. McDonough and C. E. Jackson

November 18, 1916

1034
875