

**116500540**

DATE 01/31/2018TOWNSHIP 11 SOUTH, RANGE 6 WEST, WILLAMETTE MERIDIAN; SECTION 10 CORNER EAST 1/4  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**  
WEST 1/4 CORNER SECTION 11**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)****BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.**

**[01]** GENERAL LAND OFFICE (GLO) NOTES BY JOSIAH W. PRESTON, D.S., AND HARVEY GORDON, D.S., DATED AUGUST 1854. SET POST FROM WHICH A **MAPLE 10" DIA BEARS N80°E, 20 LINKS (13.20 FEET); A FIR 14" DIA BEARS S65°W, 8 LINKS (5.28 FEET).**

**[02]** BENTON COUNTY SURVEY NO. 1322 (OLD NO. 339) FIELD NOTES (FIELD BOOK 55, PAGE 41) BY W. C. GALLOWAY, C.S., DATED APRIL 3, 1937. SET CHANNEL IRON. FIR 14" DIA (GLO BT) BEARS S65°W, 0.080 CHAINS (5.28 FEET), STANDING, NAIL ON NORTH SIDE; MAPLE 10" DIA (GLO BT) BEARS N80°E, 0.195 CHAINS (12.87 FEET), STANDING. MARKED FIR 37" DIA BEARS S55°W, 0.058 CHAINS (3.83 FEET), NAIL WEST SIDE.

**[03]** BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 213, BY W. C. GALLOWAY, C.S., DATED APRIL 3, 1937. SET A CHANNEL IRON. FIR 14" DIA (GLO BT) BEARS S65°W, 0.080 CHAINS (5.28 FEET), STANDING, NAIL ON NORTH SIDE; MAPLE 10" DIA (GLO BT) BEARS N80°E, 0.195 CHAINS (12.87 FEET), STANDING. MARKED FIR 37" DIA (CSBT) BEARS S55°W, 0.058 CHAINS (3.83 FEET), NAIL IN WEST SIDE.

**[04]** BENTON COUNTY CORNER RESTORATION NO. 835. TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.

**[05]** BENTON COUNTY SURVEY NO. 1322 (OLD NO. 339) MAP BY W. C. GALLOWAY, C.S., DATED APRIL, 1937. CHANNEL IRON. FIR 14" DIA (GLO BT) BEARS S65°W, 0.08 CHAINS (5.28 FEET), STANDING, NAIL NORTH; MAPLE 10" DIA (GLO BT) BEARS N80°E, 0.195 CHAINS (12.87 FEET), STANDING. FIR 37" DIA (CSBT) BEARS S55°W, 0.085 [SIC.] CHAINS (5.61 FEET), NAIL WEST.

**[06]** BENTON COUNTY MAP 11-6-00002 BY W. C. GALLOWAY, C.S., DATED APRIL, 1937. CHANNEL IRON. FIR 14" DIA (GLO BT) BEARS S65°W, 0.08 CHAINS (5.28 FEET), STANDING, NAIL NORTH; MAPLE 10" DIA (GLO BT) BEARS N80°E, 0.195 CHAINS (12.87 FEET), STANDING. FIR 37" DIA (CSBT) BEARS S55°W, 0.085 [SIC.] CHAINS (5.61 FEET), NAIL WEST.

**[07]** BENTON COUNTY SURVEY NO. 1352 (OLD NO. 220) FIELD NOTES (FIELD BOOK 55, PAGE 67) BY W. C. GALLOWAY, C.S., DATED OCTOBER 5, 1937. CORNER NOT DESCRIBED.

**[08]** BENTON COUNTY MAP NO. 11-6-00003 BY UNKNOWN DRAFTSMAN, DATED OCTOBER, 1937. CHANNEL IRON. FIR 14" DIA (GLO BT) BEARS S65°W, 0.08 CHAINS (5.28 FEET), STANDING, NAIL NORTH; MAPLE 10" DIA (GLO BT) BEARS N80°E, 0.195 CHAINS (12.87 FEET), STANDING. FIR 37" DIA (CSBT) BEARS S55°W, 0.085 [SIC.] CHAINS (5.61 FEET), NAIL WEST.

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME

C.S. 108

April 21, 1937  
by W.C.G.  
R. J. Stewart

Corner to Sections 29, 30, 31 & 32 T. 13 S. R. 7 W.  
Set a 5/8" bolt from an  
Oak 18" in dia. bears N. 88° E. .387 cks. std. (hollow) Mk'd. B.T. on bark  
Fir 40" " " S. 69° E. 2.80 " " Stab with letters on two sides  
Mkd. Fir 9" " N. 80° E. .140 "  
" " 11" " " S. 34° E. .120 "  
" " 10" " " S. 66° W. .180 "  
" " 19" " " N. 30° W. .257 "  
High  $\emptyset$  on Stone 10" x 18" x ? N. 47° 25' E. 1.249 "

C.S. 67

W.C.G. July 11, 1910  
M. H. Wight & J. A. Gentry

S. E. Corner of Luke Mulkey D.L.C. # 37 T. 12 S. R. 5 W. W.M.  
Set a round concrete post 18" long  
No trees.

"

S.W. corner of Luke Mulkey D.L.C. # 43 T. 12 - 6  
Stone 6" x 8" x ?  
Ash 10" N. 1° W. 250 links std.  
Oak 12" N. 15 1/4° W. 622 " "

C.S. 339

Witnesses  
Rudolph J. Stewart  
Harry Arbuckle  
Philip Auld  
July 23, 1937

1/4 Section Corner bet. Secs. 1 & 2 T. 11 - 6  
Set 3/4" x 24" iron rod  
Fir 6" in dia. bears East 1.50 lying down  
" 40" " " West 1.10 std. letters on bark  
Mkd. a fir 14" " " N. 85° 30' E. .448

Witnesses as  
above except  
Auld.

July 27, 1937

1/4 Sec. Corner bet. Secs. 2 & 3 T. 11 - 6  
Set 1" bolt 16" long under Stone 9" x 11" x 15"  
Fir 14" in dia. bears S. 71° E. .128, Orig. tree std.  
" 13" " " N. 56° 15' W. .414, " " "  
" 28" " " S. 48° E. .062 to hear of stump  
Mkd. " 50" " " S. 70° 40' W. .532  
" 24" " " N. 44° 45' E. .464

Witnesses

Rudolph J. Stewart  
Geo. Schroyer  
July 28, 1937

1/4 Sec. Corner on the North line of Sec. 2 T. 11 - 6. Std. cor.  
Set a 3/4" x 26" bolt  
Fir 12" in dia. bears S. 27° W. .65 std. (Maple gone)  
Mkd. " 60" " " N. 35° W. .273 cks. Stake on S.W.

C.S. 339

W.C. Gentry  
Witnesses  
Judolph J. Stewart  
Roy F. Ferris

1/4 Sec. Corner between Sections 2 & 11 T. 11 - 6  
Set 1 1/4" x 19" Pipe From  
Maple 12" in dia. bears S. 20° E. .53 std. found S  
Mkd. fir 28" " " N. 47° E. .177 Arrow in bark N.W.  
" " 50" " " N. 75° E. .222 " " " on South

Witnesses as above  
and J. J. Johnson  
Apr. 3, 1937

1/4 Sec. Corner bet. Secs. 10 & 11 T. 11 - 6  
Set a channel iron  
Fir 14" in dia. bears S. 65° W. .080 std. Nail on N. side  
Maple 10" " " N. 80° E. .195 " "  
Mkd. fir 37" " " S. 55° W. .058 cks. Nail in W. side.



¼-Section corner between sections 10 and 11, Twp. 11-6

835  
721

Reestablishment by W. C. Galloway

April 3, 1937

Set a channel iron

Fir 14" in diam bears S 65° W

Maple 10" in diam bears N 80° E

Fir 37" in diam bears S 55° W

Witness J. J. Johnson

.080 chains

.195 chains

.058 chains