

116867040

DATE 07/05/2013

TOWNSHIP 11 SOUTH, RANGE 6 WEST, WILLAMETTE MERIDIAN; SECTION 15 CORNER N/A
DONATION LAND CLAIM ELI SUMMERS NO. 67 CORNER NORTHWEST

COMMON CORNER(S):

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES OF THE ELI SUMMERS DONATION LAND CLAIM NUMBER 67 BY DAVID STUMP, D.S., DATED MARCH 17, 1856. SET POST FROM WHICH A W. OAK 16" DIA BEARS S39°E, 265 LINKS (174.90 FEET); A W. OAK 20" DIA BEARS S37°W, 113 LINKS (74.58 FEET); A MAPLE 20" DIA BEARS S70°W, 131 LINKS (86.46 FEET).
- [02] BENTON COUNTY ROAD NO. 302 FIELD NOTES (FIELD BOOK 12, PAGE 51) BY W. C. GALLOWAY, D.C.S., DATED JUNE 25, 1912. SET STONE 8" X 8" X 12", TREES STANDING, SOUTHEAST STUMP.
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 38, BY W. C. GALLOWAY, D.C.S., DATED JUNE 26, 1912. SET A STONE 8" X 8" X 12". SOUTHEAST STUMP STANDING. OAK 16" DIA (GLO BT) BEARS S39°E, 2.65 CHAINS (174.90 FEET) STUMP STANDING. OAK 20" DIA (GLO BT) BEARS S37°W, 1.13 CHAINS (74.58 FEET) STANDING, NOT MARKED; MAPLE 20" DIA (GLO BT) BEARS S70°W, 1.31 CHAINS (86.46 FEET) STANDING, NOT MARKED.
- [04] BENTON COUNTY CORNER RESTORATION NO. 966. TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.
- [05] BENTON COUNTY ROAD 16501 (BLAKESLEY CREEK ROAD) HARDCOPY MAP OF ROUTE 50-01, ROAD NO. 457, BY W. C. GALLOWAY, C.S., DATED JUNE 1923. STONE.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS OR 97333; PH. 766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME

38

CORNER RESTORATION BOOK NO. 1

- C.S. 162 ✓ Sec. cor. to sec. 29, 30, 31 & 32 Tp. 12 S. R. 6 W.
 Set $1\frac{1}{2}$ " pipe orig. cor.
 Fir 10" in dia. bears N. 43° E. 219' obs. stump std.
 " 30" " " S. 35° E. 42 " " "
 " 20" " " S. 60° W. 71 " " "
 " 18" " " N. 18° W. 48 " " "
 Witness J.C. Pritchett, J. Gray June 5, 1912.
- Road 23 ✓ S.W. cor. of Mark Cahoon D.L.C. #58 Tp. 10 S. R. 4 W.
 Stone 8" x 12" (Oak 12" N. 25° E. 477' std.)
 Oak 10" N. 37° 30' E. 1955' obs.
 " 12" S. 80° E. 320 " std.
 Witness J.C. Johnson & B.W. Harris June 14, 1912.
- " ✓ N.E. cor. of T.M. Reed's D.L.C. #57 Tp. 10-4.
 Set $\frac{3}{4}$ " x $\frac{1}{2}$ " iron bar
 Witness J.C. Johnson B.W. Harris & C.A. Hays June 14, 1912.
- Road #501 ✓ S.W. cor. of Thos. Hayden's D.L.C. #38 Tp. 13-7
 Set a $\frac{1}{2}$ " x 13" bar of iron (cut down) orig. cor.
 Oak 16" in dia. bears N. 42° 30' E. 294' obs.
 Fir 36" " " N. 5° W. 414 "
 Witness F. & P. Fullerton, M. Hayden & John Steffen, June 18, 1912.
- Road #302 ✓ N.W. cor. of Amos B. Lakely D.L.C. #63 Tp. 11 S. R. 6 W.
 Set a bar of iron (large)
 Fir 9" in dia. bears N. 31° 45' E. 198' obs.
 " 9" " " S. 60° 45' E. 259 "
 Oak 6" " " N. 59° W. 158 "
 Witness W.H. Ellenburgh J.H. & R.C. Johnson & C.F. Jackson June 25, 1912.
- " ✓ N.E. cor. of Amos B. Lakely D.L.C. #63 Tp. 11 S. R. 6 W.
 Set $\frac{3}{4}$ " x $2\frac{1}{2}$ " bar of iron
 Oak 10" in dia. bears S. 14° E. 23' std.
 " 10" 5" " S. 76° W. 95 "
 " 10" 4" " N. 54° 30' W. 52 "
 Witness W.H. Ellenburgh J.H. & R.C. Johnson June 25, 1912.
- " ✓ N.W. cor. of E.L. Summers' D.L.C. #67 Tp. 11-6
 Set a stone 8" x 12" S.E. stump std.
 Oak 16" S. 39° E. 265" stump std.
 " 20" in dia. bears S. 37° W. 113' obs. not mtd.
 Maple, 20" " S. 70° W. 131 " " "
 Witness W.H. F. Ellenburgh J.H. & R.C. Johnson & C.F. Jackson June 26, 1912.

M.C.G.

April



Northwest corner of Eli Summers' D. L. C. 67, Twp. 11-6

966

Reestablishment by W. C. Galloway June 26, 1912

Set a stone 8" x 8" x 12"

Oak 16" in diam bears S 39° E S. E. stump standing

Oak 20" in diam bears S 37° W 2.65 chains (stump standing)

Maple 20" in diam bears S 70° W 1.13 chains (standing Not marked)

Maple 20" in diam bears S 70° W 1.31 chains (standing Not marked)

Witnesses W. H. Eilenburgh, J. H. and A. C. Johnson, and C. E. Jackson