

**117140600**

DATE 03/30/2021TOWNSHIP 11 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 6 CORNER SOUTH 1/4  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

NORTH 1/4 CORNER SECTION 7

**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY DENNIS HATHORN, D.S., DATED JULY 7, 1856. *SET POST FROM WHICH A BURNT FIR 40" DIA BEARS S6°W, 75 LINKS (49.50 FEET); GREEN FIR 30" DIA BEARS N85°E, 670 LINKS (442.20 FEET).*
- [02] BENTON COUNTY SURVEY NO. 154 (OLD NO. 56) FIELD NOTES (FIELD BOOK 4, PAGE 61) BY J. A. GANONG, D.C.S., DATED DECEMBER 27, 1909. *REESTABLISH 1/4 CORNER. ONE TREE STANDING, MARKS.*
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 57, BY J. A. GANONG, D.C.S., NO DATE GIVEN. *SET OAK STAKE 4" X 4" X 24" FOR CORNER. EAST TREE STANDING. OLD STAKE IMPRINT.*
- [04] BENTON COUNTY CORNER RESTORATION NO. 998. *TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.*
- [05] BENTON COUNTY SURVEY NO. 195 (OLD NO. 92) FIELD NOTES (FIELD BOOK 7, PAGE 31) BY J. A. GANONG, D.C.S., DATED DECEMBER 5, 1910. *CORNER NOT DESCRIBED.*
- [06] BENTON COUNTY SURVEY NO. 195 (OLD NO. 92) MAP BY UNKNOWN DRAFTSMAN, NO DATE GIVEN. *4" X 4" STAKE.*
- [07] BENTON COUNTY SURVEY NO. 441 (OLD NO. 207) FIELD NOTES (FIELD BOOK 17, PAGE 13) BY BURT WILKES, D.C.S., DATED APRIL 17, 1914. *3" X 5" FIR POST.*
- [08] BENTON COUNTY SURVEY NO. 441 (OLD NO. 207) MAP BY BURT WILKES, D.C.S., DATED APRIL 27, 1914. *POST.*
- [09] BENTON COUNTY MAP NO. 11-7-00004 BY BURT WILKES, D.C.S., DATED APRIL 27, 1914. *POST.*
- [10] BENTON COUNTY SURVEY NO. 706 (OLD NO. 286) FIELD NOTES (FIELD BOOK 27, PAGE 74) BY W. C. GALLOWAY, C.S., DATED MAY 26, 1920. *CORNER NOT DESCRIBED.*
- [11] BENTON COUNTY MAP NO. 11-7-00002 BY W. C. GALLOWAY, C.S., DATED MAY, 1920. *STAKE.*
- [12] OREGON STATE HIGHWAY DEPARTMENT CONSTRUCTED LINE DRG. NO. 5B-7-13, LINCOLN CO. LINE TO BLODGETT, EDDYVILLE-BLODGETT HIGHWAY, BENTON COUNTY, BY UNKNOWN DRAFTSMAN, DATED OCTOBER, 1936, REVISED FEBRUARY, 1975. *OAK STAKE FOUND.*
- [13] BENTON COUNTY BOOK OF ROAD HARDCOPIES PAGE 41, STATE HWY 180, ROUTE 49, ROAD NO. 552, BY UNKNOWN DRAFTSMAN, NO DATE GIVE. *STAKE.*

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME

Survey #55 1/4 Sec. Cor. bet. Secs. 3 & 4 in T.14S. R. 8W.  
Set 1 1/4" Galv. pipe under Sandstone 16X10X5 for Cor. at tree standing  
Marked, Fir 11" diam bears 5880 W. 592 Chs. dist.  
Witnesses, Henry Robinson + Henry Hammersley.

" #56 Cor. of Secs 5, 6, 7, 8 cont in T.11S. R. 7W.  
Set 1 1/4" pipe for Cor. one tree dead. other stumps standing, original stakes  
Witnessed by Joseph Petit, + Howard Bush.

" #56 1/4 Cor. bet Secs. 6 & 7 in T.11S R. 7W.  
Set Oak stake 4X4X24" for Cor. East tree standing, old stake in print  
Witnesses, Joseph Petit + Howard Bush.

" #57 S.W. Cor. Abner Shrum II.C. #39 in T.11S R. 5W.  
Original Gndstone, referenced  
S.E. Cor. Brooks house bears N 30° 47' E.  
W.E. Cor Mitchell " " S 58° 10' E  
East Gate Knotts " " S 31° 02' W.  
S.E. Cor. Lockes " " N 72° 42' W 1.609 chs. dist.

" #57 S.E. Cor. Abner Shrum II.C. #39, in T.11S R. 5W.  
Set 1 1/4 X 24" for Cor. Found original brick.  
Witnesses to above two Corners. F.S. Elliott, J.W. Mitchell.

" #59 S.W. Cor. Alexander Liggitt II.C. #40 in T.12S R. 6W. universal joint  
Set Stone for Cor. trees, 2, standing, Cor. in field. Set Crock jug and iron inside  
A 24" x 12" x 12" x 12" W. 6.943 chs., the S.E. cor. of Geo. Williams Cl. 53  
Oak 12" N. 15° 15' E. 4.59 chs. Std.  
" 36" N. 36° 30' W. 5.18 " to face

" #59 N.E. Cor. A. Liggitt #63 in T.12S R. 5W.  
Set Stone for Cor.

" #61 N.E. Cor. of Prior Scott II.C. #44 in T.12S R. 5W.  
Stone already set for Cor. Verified position of Cor by stumps of old B.T.G.  
Anchor post of fence bears 556° 10' W. 587 chs. dist.

" #61 S.E. Cor. Prior Scott II.C. #44 in T.12S R. 5W.  
Set 3/4" x 30" galvanized pipe for Cor, two trees std. in print of original stake.  
Remarked trees (original).

" #61 S. exterior Cor. Prior Scott II.C. #44 in T.12S R. 5W.  
Set oak stake 6x6x24" for Cor. in place of old stake, 2 trees standing.  
Witnessed by W.C. Galloway and John + Clyde Hayes.

" #61 S. interior Cor. Prior Scott II.C. #44 in T.12S R. 5W.  
Set 2x4x24" hard oak stake for Cor. stump standing no mark. of stake found. original in print  
Marked, Oak 10" diam bears 555° E. 778 chs. dist.  
" 12" " " N 20° 20' W. 715 " "  
Witnessed by W.C. Galloway, John + Clyde Hayes.

$\frac{1}{4}$ -Corner between sections 6 & 7 in Twp. 11 S R 7 W

998

Reestablishment by W. C. Galloway

Date 12-27-1909

Set Oak stake 4 x 4 x 24" for corner, East tree standing, old stake imprint.

Witnesses Jasper Petit and Howard Bush