

**117838010**

DATE 07/30/2013

TOWNSHIP 11 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 23 CORNER N/A  
DONATION LAND CLAIM WILLIAM WOOD NO. 38 CORNER EAST-NORTHEAST

**COMMON CORNER(S):**

SOUTH-SOUTHEAST CORNER OF THE WILLIAM BLODGET DONATION LAND CLAIM NO. 40

**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES OF THE WILLIAM BLODGET DONATION LAND CLAIM NO. 40 BY L. A. DAVIS, D.S., DATED JUNE 27, 1857. **SET POST FROM WHICH A FIR 40" DIA BEARS N55°W, 47 LINKS (31.02 FEET); A FIR 27" DIA BEARS S63°30'W, 59 LINKS (38.94 FEET).**
- [02] GENERAL LAND OFFICE NOTES OF THE WILLIAM WOOD DONATION LAND CLAIM NO. 38 BY L. A. DAVIS, D.S., DATED JUNE 27, 1857. **TO CORNER FROM WHICH A FIR 40" DIA (GLO BT) BEARS N55°W, 47 LINKS (31.02 FEET); A FIR 27" DIA (GLO BT) BEARS S63°30'W, 59 LINKS (38.94 FEET).**
- [03] BENTON COUNTY SURVEY NO. 216 (OLD NO. 88) FIELD NOTES (FIELD BOOK 6, PAGE 55) BY J. A. GANONG, D.C.S., DATED MARCH 28, 1911. **REESTABLISHED 3/4" X 24" IN ORIGINAL HOLE. NORTHWEST ONE TREE STANDING. REMARKED OLD TREE. FIR 9" DIA BEARS N54°30'E, 0.543 CHAINS (35.84 FEET); FIR 10" DIA BEARS S53°15'E, 0.354 CHAINS (23.36 FEET).**
- [04] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 62. BY J. A. GANONG, D.C.S., NO DATE GIVEN. **SET 3/4" X 24" PIPE FOR CORNER. NORTHWEST TREE STANDING. ORIGINAL STAKE HOLE. MARKED FIR 9" DIA (CSBT) BEARS N54°30'E, 0.543 CHAINS (35.84 FEET); FIR 10" DIA (CSBT) BEARS S53°15'E, 0.354 CHAINS (23.36 FEET).**
- [05] BENTON COUNTY CORNER RESTORATION NO. 1171. **TRANSCRIBED FROM RECORD [04] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.**
- [06] BENTON COUNTY MAP NO. 11-6&7-00007 BY W. C. GALLOWAY, C.S., DATED MAY 12, 1915. **3/4" PIPE.**
- [07] BENTON COUNTY SURVEY NO. 6437 BY DAVID K. BATEMAN, P.L.S., DATED JULY 5, 1977. **FOUND 3/4" PIPE 6" DOWN. D. FIR STUMP 50" DIA (GLO BT) BEARS N54°W, 33.0 FEET; D. FIR REMAINS (GLO BT) BEARS N63°W (SIC), 39 FEET. MARKED D. FIR 12" DIA BEARS S60°W, 24.6 FEET; D. FIR 8" DIA BEARS N40°W, 2.3 FEET.**
- [08] BENTON COUNTY SURVEY NO. 8081 BY THEODORE JAMES LANGTON, P.L.S., DATED DECEMBER 1, 1987. **FOUND 3/4" (INNER DIAMETER) PIPE. FOUND BTS PER C.S. 6437.**

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS OR 97333; PH. 766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME

Survey #87

## LOWOR RESERVATION BOOK NO. 1

1/4 Cor. bet. sec. 81 & 82 T 115. R 7 W.  
Set 1" x 30" blk pipe for Cor. W. tree standing. Original stake in pair  
Marked, W. 70m 26" diam. tree. S 65° 35' E. 68E Ch. dist.  
Witnesses, N. Pope, G. Wickhamsky, & Chas. Alderman.

#88.

N.E. Cor. of 20<sup>th</sup> Wood. Ill. # 38 in T 115. R 7 W. 1216 - p 55  
Set 3/4" x 24" pipe for Cor. NW tree standing. original stake in  
Marked: Fir 7" diam. tree. N 54° 30' E. 543 Ch. dist.



" 10" " " S 53° 15' E. 354 "  
Witnesses, E. L. Davis & Bert Read,

#88.

S.W. Cor. 20<sup>th</sup> Blagotta Ill. # 40 in T 115 R 6 W.  
Set 3/4" x 24" pipe for Cor. two gone, set by logs & dist.  
Witnesses same as above.

#88.

North Exterior Cor of 20<sup>th</sup> Wood. Ill. # 38 in T 115. R 7 W.  
Set 3/4" x 24" pipe for Cor. Set by logs & dist.  
Witnessed by E. L. Davis, & Bert Read.

#88.

N.W. Cor. of 20<sup>th</sup> Woods. Ill. # 38 in T 115. R 6 W.  
Set 3/4" x 24" pipe for Cor. Set by logs & distance.  
M. Gotsch Rindalls house by S 33° 38' E.  
Center of M. Widows frame, M. R. Shultz house by S 48° 58' W.  
Witnessed by E. L. Davis and Bert Read.

#88.

S.W. Cor of 20<sup>th</sup> Woods. Ill. # 38 in T 115, R 6 W.  
Set Stone 16 x 8 x 7 for Cor. tree down, nearby gone, original stake in pair  
Marked, Set 7" diam. tree. N 73° 30' E. 380 Ch. dist.  
Fir 6" " " N 27° 45' W. 547 "  
Witnesses, E. L. Davis, Bert Read & Tom. Mulkey.

#88.

S.E. Cor. of 20<sup>th</sup> Woods Ill. # 38 in T 115, R 6 W.  
Set Stone 13 x 8 x 5 for Cor. stump standing, NW tree down. original stake in pair  
Marked, Fir 17" diam tree. S 69° W. 119 Ch. dist.  
Fir 14" " " N 78° 30' W. 165 "  
Witnessed by E. L. Davis and Bert Read.

#80 (but)

1/4 Cor bet Secs 16 & 20 in T 105. R 4 W.  
Set 1 1/2 x 20" blk pipe for Cor. tree & stump standing see page 50  
Marked, Set 10" diam tree S 24° 45' E. 445 Ch. dist. 1 1/2" blk pipe  
Witnesses, C. M. & John Standenford & Chas. Shelton.

#130.

1/4 Cor bet. Secs. 81 & 82 in T 115. R 6 W.  
Set Stone 14 x 12 x 8 for Cor. W. tree standing other gone. Original stake in pair  
Marked, fir 15" diam tree N 6° E. 726 Ch. dist.  
Witnesses, Geo. Vestberg, H. Taylor and M. J. Reddick.

Sum

Sum

N. E. corner of William Wood DLC 38, Twp. 11 S R 7 W

1171

Reestablishment by W. C. Galloway

Date 3-28-1911

Set  $3/4"$  x  $24"$  pipe for corner, N. W. tree standing, original stake hole  
Fir 9" in diam bears N  $54^{\circ} 30'$  E .543 chains dist.

Fir 10" in diam bears S  $53^{\circ} 15'$  E .354 chains dist.

Witnesses E. L. Davis and Birt Read