

S. R. 6 W.

C.S. Road 635 S.W. corner of S.K. Brown D.L.C. 54 T. 12-5
 By W.C. Galloway C.S. Found orig sandstone, placed other rock by same
 Witness, V.M. Patterson The orig. N.W. cor. of Nicholas Owenby D.L.C. #62 is 1072.27 feet N. 87° 45½' W.
 Top of Marys Peak Lookout is. S 89° 59½' W.

As above
 Jan. 28, 1946

S.E. corner of Solomank. Brown Cl. 54 T. 12-5
 Set a 1½" shaft. Found pieces of orig. sandstone with letters.
 Oak stump 24" in dia. N. 40° E. 2.31 chs.
 " 30" in dia. bears S. 80° 40' W. 1.75 " std.
 " 6" (N. 40° 19") " N. 12° W. .75 " "
 Blazed Oak 12" in dia. " S. 31° W. .156 chs.

from orig. place

11-C
12-6

C.S. No. 254
 C.C. Hanson Dra C.S.
 Witness - F. Vetter
 L.A. Wells

Sec Cor. between Secs 13, 18, 24 (19 Twp 14 S., R. 4 & 5 W.)
 Set a ¾" pipe 4' long in river bed. Nothing but Willow brush
 near. 30 no trees. Corner set from Linn Co Survey #1929

¼ Sec Cor bet Secs 13 & 18 Twp 14 S., R. 4 & 5 W.
 Set a ¾" pipe $\frac{\text{Surf}}{8}$
 W. Oak 18" N 56° 20' W. 0.485
 " " 14" N 5° W 0.970

Cor to Secs 22, 23, 26 & 27 Twp. 12 S. R. 5 W.
 Set ¾" rod $\frac{\text{Surf}}{10}$
 Oak 46" S 5° 23' E 4.440
 " 12" N 87° 50' E 4.150

W.

C.S. No 86
 C.C. Hanson Dra C.S.
 Witness - A.L. Bergstrom
 L.A. Wells

for measure

Cor to Secs. 26, 27, 34, & 35 Twp. 12 S., R. 5 W.
 Set ¾" rod $\frac{\text{Surf}}{10}$
 ¾" pipe S. 3° 04' E. 2.752 (on West line of Hwy)
 Maple 60" S. 15° 56' W. 4.210.

Lookout

¼ Sec Cor between Secs 25 & 36 Twp 12 S., R. 5 W.
 Set 5/8" rod
 Ash 20" S 32° 49' E 1.005
 " " N 22° 33' W 0.625

std.

Cor to Secs. 25, 26, 35, & 36 Twp 12 S., R. 5 W.
 Set 1" Rod $\frac{\text{Surf}}{12}$
 Ash 20" N. 72° 05' E. 3.020
 " 14" S. 61° 25' E. 2.770
 Mull. Balm 60" S. 81° 29' W. 6.060

M.C. bet Secs. 25 & 36 Twp. 12 S., R. 5 W.
 Set 5/8" rod
 Maple 40" N. 59° E. 6.11 std.
 " 48" S 13° W. 0.465

Corner to sections 25, 26, 35 and 36, Twp. 12 S., R. 5 W.

Reestablishment by W. C. Galloway

1946

1226

Set 1" rod 12" below surface

Ash 20" in diam bears N 72° 05' E

Ash 14" in diam bears S 61° 25' E

Balm 60" in diam bears S 81° 29' W

3.020 chains

2.770 chains

6.060 chains

Witnesses C. C. Hanson , M. L. Beyerlein and L. A. Wells

BENTON COUNTY SURVEYORS OFFICE - CORNER RESTORATION

03029

T 12 S, R 5 W, W. B. & M., BENTON COUNTY, OREGON


REPORTED BY Verle Moore

SECTION 25

The information shown hereon was taken from the referenced county survey. Date: 7/31/90

TITLE L.S. 501

DATE 6-14-1982



- OFFICIAL CORNER FOUND
- CORNER SET

Sec. CORNER COMMON TO SEC. 25, 26, 35 & 36
is 1" I. rod about 1' below surface

DESCRIBE

ADDITIONAL INFORMATION

See. C.S. 7421

OVER

LEGIBLE MARKS ON BEARING OBJECTS

KIND	Ash		
SIZE	18"		
BEARING	S. 60° 25' E		
DISTANCE	182.82		
BT TAG POSTED			

BENTON COUNTY SURVEYORS OFFICE - CORNER RESTORATION

03155

T 12 S, R 5 W, W. B. & M., BENTON COUNTY, OREGON


REPORTED BY VERLE MOORE

SECTION 25

The information shown hereon was taken from the referenced county survey. Date: 7/31/90

TITLE L.S. 501

DATE 5-11-1983



- OFFICIAL CORNER FOUND
- CORNER SET

SEC. CORNER COMMON TO SEC. 25, 26, 35 & 36
is 1" Rod ABOUT 1' BELOW SURFACE

DESCRIBE

ADDITIONAL INFORMATION

SEE C.S. 7519

OVER

LEGIBLE MARKS ON BEARING OBJECTS

KIND	ASH		
SIZE	18"		
BEARING	S. 60° 25' E.		
DISTANCE	182.82'		
BT TAG POSTED			

26 | 25
35 | 36

CORNER HISTORY		T 12 S, R 5 W		SECTION 25 D.L.C.		CORNER SW CORNER		# 00200
NO.	DATE	SOURCE	SURVEYOR	MONUMENTS AND ACCESSORIES			COMMENTS	
1	5/5/1853	GLO	G.W. HYDE	SET Post 1 MAPLE 3 ASH BT'S				1
								2
2	7/3/46	CS 1794	CURTIS C. HANSON	SET 1" x 40" shaft 2 ASH 1 BALM			FBIOS PAGE 28	3
3	NO DATE	CS 7527	BENTON CO SUR OFF	" " " " " "				4
4	NO DATE	OLD COR BOOK 1 PAGE 24	CURTIS C. HANSON	SET 1" ROD 12" BELOW SURFACE 2 ASH 1 BALM				5
								6
5	1946	CR 1226	CURTIS C. HANSON	SET 1" ROD " " " "			" TRANS COPY OF (4)	7
①	NONE GIVEN	CS # 2740	"	1" ROD @ 2 ASH + 1 BALM FOR B.T.'S				8
⑦	1/11/72	CS 5306	VERIE MOORE	FD 1" IRON ROD 15" BELOW SURFACE 18" ASH			T	9
⑩	6/14/82	CR 3029	" "	" " " " " "			TRANS OF [09]	10
⑨	6/14/82	CS 7421	" "	FD 1" IRON ROD 18" ASH				11
								12
⑪	5/11/83	CS 7519	VERIE MOORE	" " " " " "				13
⑫	5/11/83	CR 3155	" "	" " " " " "			TRANS OF [11]	14
								15
⑬	8/14/95	CS # 5944	" "	FIND 1" I. ROD				16
								17
								18
								19
								20
								21
							CR	22
							1741	23
							1226 ✓	24
							3029 ✓	25
							3155 ✓	26
							CS 7421 - VM	27
							1794 - CCH	28
							7327 - CCH	29
							* 2740 -	30
							5306 -	31
							7519 - VM	

BENTON COUNTY CORNER HISTORY FORM, PAGE 1 OF 1,**125600200H**DATE 1/31/1995TOWNSHIP 12 SOUTH, RANGE 5 WEST, WILLAMETTE MERIDIAN; SECTION 25 CORNER SW
DONATION LAND CLAIM _____ CORNER _____**COMMON CORNER(S):**

THE SOUTHEAST CORNER OF SECTION 26.
THE NORTHEAST CORNER OF SECTION 35.
THE NORTHWEST CORNER OF SECTION 36.

UPDATES AND REVISIONS:**CORNER RECORDS (PREVIOUS RENEWALS, SURVEYS, ETC.)**

- [01] ORIGINAL GLO SURVEY BY G.W. HYDE DATED MAY 5, 1853.
- [02] COUNTY SURVEY NO. 1794 BY CURTIS C. HANSON DATED JULY 31, 1946 (FIELD BOOK NO. 103, PAGE 28).
- [03] COUNTY SURVEY NO. 7327 BY BENTON COUNTY SURVEYOR'S OFFICE (NO DATE GIVEN).
- [04] OLD CORNER BOOK NO. 1 PAGE 241 BY CURTIS C. HANSON (NO DATE GIVEN).
- [05] CORNER RESTORATION NO. 1226 BY CURTIS C. HANSON DATED IN 1946.
- [06] COUNTY SURVEY NO. 2740 BY CURTIS C. HANSON (NO DATE GIVEN).
- [07] COUNTY SURVEY NO. 5306 BY VERLE MOORE DATED JANUARY 11, 1972.
- [08] COUNTY SURVEY NO. 5944 BY VERLE MOORE DATED AUGUST 14, 1975.
- [09] COUNTY SURVEY NO. 7421 BY VERLE MOORE DATED JUNE 14, 1982.
- [10] CORNER RESTORATION NO. 3029 BY VERLE MOORE DATED JUNE 14, 1982.
- [11] COUNTY SURVEY NO. 7519 BY VERLE MOORE DATED MAY 11, 1983.
- [12] CORNER RESTORATION NO. 3155 BY VERLE MOORE DATED MAY 11, 1983.

COMMENTS/LOCATION/ETC:

RECORD [05] IS A TRANSCRIBED COPY OF RECORD [04] AND MAY CONTAIN ERRORS AND OMISSIONS.
RECORD [10] WAS TRANSCRIBED FROM RECORD [09] AND MAY CONTAIN ERRORS AND OMISSIONS.
RECORD [12] WAS TRANSCRIBED FROM RECORD [11] AND MAY CONTAIN ERRORS AND OMISSIONS.

NOTES:

THIS IS A MICROSOFT WORD (VERSION 5.0) DOCUMENT NAMED "25600200" CREATED FROM A BOILER PLATE DOCUMENT NAMED "HISTORY", WHICH HAS A STYLESHEET NAMED "CORNER" ATTACHED TO IT.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE. CORVALLIS OR 97333; PH. 757-6821
RESEARCH BY: CURTIS J. LIESENFELT/MARK E. ANDERSON
DATA ENTRY BY: COLETTE MONACO