

C.S. #117 Sec. cor. to sec. 4, 6, 8 & 9 1p. 13-5.
 Set $1\frac{1}{2}$ " pipe. orig. cor.
 Oak 30" in dia. bears S. $73^{\circ}30'$ E. 7.17' std.
 " 7" " " " S. $3^{\circ}15'$ W. 1.759'
 Witnesses J. G. Buchanan & Herald Whitley Sept. 21, 1911.

Roads #293 Sec. cor. to sec. 26, 27, 34 & 35 Tp. 12-6.
 Set a stone 8" X 10" X 12" 3 stumps std.
 Oak 6" in dia. bears N. $84^{\circ}30'$ E. 6.95'
 Fir 9" " " " S. 60° E. 1.183'
 Oak 4" " " " S. $37^{\circ}20'$ W. 1.358'
 " 5" " " " N. $12^{\circ}20'$ W. 4.72'
 Witnesses Chs. Johnson, A. T. Erwin, J. B. Ellis & Henry Gorkard Sept 26, 1911.

C.S. #118 N.E. cor. of Hiram Allen's D.L.C. #55 Tp. 12-5.
 Set a 1" pipe
 Oak 12" in dia. bears N. $37^{\circ}00'$ E. 4.745 std.
 " 14" " " " S. $18^{\circ}35'$ W. 4.660'
 Witnesses R. D. Cause & P. F. Thomas Oct. 5, 1911.

" S.E. cor. of Hiram Allen's D.L.C. #55 Tp. 12-5.
 Set $1\frac{1}{2}$ " pipe
 Oak 12" in dia. bears S. 15° E. 3.26' std.
 Oak happle 6" " " N. $87^{\circ}30'$ W. .584'
 Witnesses R. D. Cause & P. F. Thomas Oct. 6, 1911.

" S.W. cor. of Geo. Bethel's D.L.C. #49 Tp. 12-5.
 Set 1" pipe galvanized orig. cor.
 Ash 18" in dia. bears N. 23° E. 5.46' std.
 Oaks 20" " " " S. $89^{\circ}30'$ E. .539'
 Witnesses P. F. Thomas Lloyd Schram Oct. 7, 1911.

C.S. #119 S.W. cor. of Richard Irwin's D.L.C. #51 Tp. 13-5.
 Set a stone 7" X 8" X 12" orig. cor.
 Oak 30" in dia. bears N. 69° W. 10.16' std.
 " 24" " " " N. $48^{\circ}45'$ W. 8.58' "
 Witnesses R. D. Cause & P. F. Thomas Oct. 19, 1911.

" Sec. cor. to sec. 14, 15, 22 & 23 Tp. 13-5.
 Set 1" galvanized pipe 12" under surface. cor. set from ^{1 hole} ~~stone~~
 Oak 10" in dia. bears N. $85^{\circ}27'$ E. 11.134'
 " 14" " " " S. $62^{\circ}40'$ E. 7.799'
 Witnesses R. D. Cause & P. F. Thomas Oct. 29, 1911.

" $\frac{1}{4}$ cor. between sec. 14 & 23 Tp. 13-5.
 Set a $1\frac{1}{2}$ " pipe
 Oak 19" in dia. bears S. $2^{\circ}50'$ E. 2.896'
 " 10" " " " S. 55° W. 3.05' std.
 " 5" " " " S. $77^{\circ}43'$ W. 2.848'
 Witnesses R. D. Cause & P. F. Thomas Oct. 24 1911.

Northeast corner of Hiram Allen's DLC 55, Twp. 12-5

Reestablishment by W. C. Galloway

October 5, 1911

1292

Set a 1" pipe

Oak 12" in diam bears N. 37° 00' E

4.745 chains (standing)

Oak 14" in diam bears S. 18° 35' W

4.660 chains

Witnesses R. O. Caves, and P. F. Thomas

125855010

BENTON COUNTY SURVEYORS OFFICE - CORNER RESTORATION

1295


T 12 S, R 5 W, W. B. & M., BENTON COUNTY, OREGON

REPORTED BY Mike Lemke

SECTION 55

TITLE Crew Chief for Fred Lemke RLS 443

DATE January 10, 1979



● OFFICIAL CORNER FOUND

○ CORNER SET

NE

DLC CORNER COMMON TO SEC. DLC 55 & S. Line 49
IS 2 3/4" Brass Disc on 2 1/2" Iron Pipe

DESCRIBE

ADDITIONAL INFORMATION

2 1/2" Iron Pipe is 36" long, set over
1"X36" iron pipe also found portions of
Orig. stone

Cor was recovered and shown to me by

Crew of O. Shaw

OVER

(Oct. 5, 1911)

LEGIBLE MARKS ON BEARING OBJECTS

	Face Showing		
	Marked		
	Not		
	Legible		
KIND	Oak	Oak	
SIZE	(12") 40"	(14") 40"	
BEARING	N37°E	S18°35'W	
DISTANCE	4.745 Ch.	4.660CH.	
BT TAG POSTED	<u>No</u>	<u>No</u>	
	<u>to e BT</u>	<u>to e BT</u>	