

127140400

DATE 03/04/2020TOWNSHIP 12 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 18 CORNER SOUTH 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

NORTH 1/4 CORNER SECTION 19

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY CLARK SMITH, D.S., DATED DECEMBER 10, 1878. SET POST FROM WHICH A FIR 5" DIA BEARS N40°E, 230 LINKS (151.80 FEET); FIR 6" DIA BEARS S10°W, 302 LINKS (199.32 FEET).
- [02] BENTON COUNTY SURVEY NO. 1603 (OLD NO. 156) FIELD NOTES (FIELD BOOK 69, PAGE 51) BY W. C. GALLOWAY, C.S., DATED DECEMBER 11, 1942. SET 3/4" PIPE 0.40 CHAINS (26.40 FEET) WEST OF CREEK 4 FEET WIDE. FIR 6" DIA BEARS N56°E, 0.568 CHAINS (37.49 FEET); CEDAR 26" DIA BEARS S15°E, 0.379 CHAINS (25.01 FEET); HEMLOCK 17" DIA BEARS N51-1/2°W, 0.410 CHAINS (27.06 FEET).
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 239, BY W. C. GALLOWAY, C.S., DATED APRIL, 1944. SET 3/4" PIPE 40 LINKS (26.40 FEET) WEST OF CREEK 6 LINKS (3.96 FEET) WIDE, DEEP CANYON. MARKED FIR 6" DIA (CSBT) BEARS N56°E, 0.568 CHAINS (37.49 FEET); MARKED CEDAR 26" DIA (CSBT) BEARS S15°E, 0.379 CHAINS (25.01 FEET), SPIKE FOR MEASURE ON EAST; MARKED HEMLOCK 17" DIA (CSBT) BEARS N51-1/2°W, 0.410 CHAINS (27.06 FEET).
- [04] BENTON COUNTY CORNER RESTORATION NO. 1668. TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.
- [05] BENTON COUNTY MAP NO. 12-7-00008 BY W. C. GALLOWAY, C.S., DATED JULY 1, 1944. 3/4" PIPE. FIR 6" DIA (CSBT) BEARS N56°E, 0.568 CHAINS (37.49 FEET); CEDAR 26" DIA (CSBT) BEARS S15°E, 0.379 CHAINS (25.01 FEET), SPIKE EAST; HEMLOCK 17" DIA (CSBT) BEARS N51-1/2°W, 0.410 CHAINS (27.06 FEET).
- [06] BENTON COUNTY SURVEY NO. 7688 BY KENNETH M. WIGHTMAN, II, P.L.S., AND JAMES M. GRIFFIS, P.L.S., DATED NOVEMBER 1, 1983. FOUND 3/4" IRON PIPE. SET 3-1/2" ALUMINUM CAP WITH MAGNET IN PLACE OF PIPE MARKED "T12S R7W 1/4 S18/S19 1983 RPLS 1637" FROM WHICH CEDAR STUMP 40" DIA (CSBT) BEARS S15°E, 25.2 FEET, NO MARKS OR FACE VISIBLE; HEMLOCK STUMP 24" DIA (CSBT) BEARS N54°W, 28.1 FEET, BADLY ROTTED. MARKED ALDER 14" DIA BEARS N28°W, 36.6 FEET TO ALUMINUM NAIL AT SIDE CENTER, BARK SCRIBED "1/4 S18" "BT" WITH BRASS WASHER NAILED TO LOWER BLAZE; HEMLOCK 13" DIA BEARS S23°W, 48.2 FEET TO ALUMINUM NAIL AT SIDE CENTER, SCRIBED "1/4 S19" "BT" WITH BRASS WASHER NAILED TO LOWER BLAZE.
- [07] BENTON COUNTY SURVEY NO. 9027 BY CHRIS J. HUMCKE, P.L.S., DATED JULY 31, 1995. FOUND 3-1/2" ALUMINUM CAP SET ON 2-1/2" OUTSIDE DIAMETER ALUMINUM PIPE SET OVER 3/4" IRON PIPE. FOUR BEARING TREES.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME

C.S. #82
Set by F.M.W.
July 1910 reset by
W.C.G. 1945

Most E. S.E. corner of John T. Fortson D.L.C. #57. T. 14-6
Set 1" pipe in stake hole, 1 ft. E. of post. in 1945
Oak 16" in dia. bears N.71° E. .919 of a chain
" 14" " " " S.40° W. .626 " " "

C.S. #311
For Dale Cramer
by W.C. Galloway
June 14, 1944
Paul Finley Witness
Dale Cramer Witness

1/4 sec. Cor. bet. Sections 34 and 3 Tps. 14 and 15 S. R. 8 W.
Set a 3/4" pipe, Qt. bottle east of pipe
Maple 10" in dia. bears S. 8 1/2° W. .62 chn. std.
" 10" " " " N. 76° E. .09 " " measure at bottom.

1/4 Sec. Cor. bet. Sections 2 and 3 T. 14-6
Set a 3/4" Galv. pipe 48" long
Oak 16" in dia. bears N. 50° 30' W. 2.60 chs. std. Dead
Mkd. " 14" " " " S. 72° 16' E. .373 "
" fir 18" " " " " S. 63° 20' W. .420 "

C.S. #156
by W.C. Galloway
Witnesses
John R. Thompson
Norman Thompson
Mch. 31, 1944

1/4 Sec. Cor. bet. Sections 17 & 18 T. 12 S. R. 7 W.
Set 3/4" pipe, in N. edge of a Cr. 2' wide, about 100' E. of Shot Punch Cr.
Fir 25" in dia. bears N. 78° 27' E. .258 chn. to square spike on S. side.
Hemlock 14" " " East .262 chain to mark on N. side.
Fir 34" " " " S. 26° 06' W. .316 " to square spike on N.W. side.
" 108" " " " S. 72° 30' W. 1.510 " to " " " N.E. "

"
April 1944

Corner to Sections 17, 18, 19 and 20 T. 12-7
Set 3/4" pipe, (Measurements from section corners N. and W.)
Mkd. Fir 7" in dia. bears N. 44° 25' E. .614 chains to center of bottom.
" " 8" " " " S. 69° 45' E. .589 " " center of bottom
Alder 16" " " " " S. 68° E. .368 " mark on N. for measure
Mkd. Fir 19" " " " " S. 38° W. .652 " " " E. " "
Hemlock 6" " " " " N. 87 1/2° W. .221 "



April 1944

1/4 Section Corner bet. Secs. 18 and 19 T. 12-7
Set a 3/4" pipe, 40 lks. W. of creek & 1ks. wide, deep canyon.
Mkd. Fir 6" in dia. bears N. 56° E. .568 chain
" Cedar 26" " " " S. 15° E. .379 " spike for measure on E.
" Hemlock 17" " " " N. 51 1/2° W. .410 "

mark on S
E. 94.85 lks.
13-7
14-7W.
head of pipe
center
10) 247

Corner to Sections 18 and 19 T. 12 S. R. 7 W. and 13 and 24 T. 12-8.
Set a 3/4" galvanized pipe, Rock and stake by pipe
Set from B. fir 60" in dia. bears S. 80° W. 23 lks. one letter.
B. " 60" " " " N. 52° E. 895 " found letters
" 6" " now 36" " " S. 25° E. 25 " standing.
Mkd. " 36" " " N. 15° E. 91.6 " center of tree.
" " 38" " " S. 68° E. 44.8 " mark on north

$\frac{1}{4}$ -Section corner between sections 18 and 19 Twp. 12-7

2005

1668

Reestablishment by W. C. Galloway

April 1944

Set a $\frac{5}{4}$ " pipe, 40 links W. of creek 6 links wide, deep canyon

Fir 6" in diam bears N 56° E .568 chains

Cedar 26" in diam bears S 15° E .379 chains

Hemlock 17" in diam bears N 51 $\frac{1}{2}$ ° W .410 chains