

127200540

DATE 03/17/2015

TOWNSHIP 12 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 7 CORNER EAST 1/4
DONATION LAND CLAIM N/A CORNER N/A

COMMON CORNER(S):
WEST 1/4 CORNER SECTION 8

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

[01] GENERAL LAND OFFICE (GLO) NOTES BY E. P. HENDERSON, D.S., DATED MAY 26, 1875. SET POST FROM WHICH A FIR 8" DIA BEARS EAST, **64 LINKS (42.24 FEET)**; FIR 10" DIA BEARS N5°W, **39 LINKS (25.74 FEET)**.

[02] BENTON COUNTY SURVEY NO. 1603 (OLD NO. 156) FIELD NOTES (FIELD BOOK 69, PAGE 43) BY W. C. GALLOWAY, C.S., DATED JANUARY 15, 1943. SET 60 SPIKE. SET 1/2" PIPE NORTH OF CEDAR LOG. FIR 8" DIA (NOW 34" DIA) (GLO BT) BEARS S86-1/2°E, **0.64 CHAINS (42.24 FEET) STANDING**; FIR 10" DIA (NOW 36" DIA) (GLO BT) BEARS N5°W, **0.39 CHAINS (25.74 FEET) STANDING**.

[03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 233, BY W. C. GALLOWAY, C.S., DATED JANUARY 15, 1943. SET 1/2" PIPE NORTH OF CEDAR LOG. FIR 8" DIA (NOW 34" DIA) (GLO BT) BEARS S86-1/2°E, **0.64 CHAINS (42.24 FEET) STANDING**; FIR 10" DIA (NOW 36" DIA) (GLO BT) BEARS N5°W, **0.39 CHAINS (25.74 FEET) STANDING**.

[04] BENTON COUNTY CORNER RESTORATION NO. 1623. TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.

[05] BENTON COUNTY MAP NO. 12-7-00003 BY UNKNOWN DRAFTSMAN, NO DATE GIVEN. 1/2" PIPE. FIR 8" DIA (NOW 34" DIA) (GLO BT) BEARS S86-1/2°E, **0.64 CHAINS (42.24 FEET) STANDING**; FIR 10" DIA (NOW 36" DIA) (GLO BT) BEARS N5°W, **0.39 CHAINS (25.74 FEET) STANDING**.

[06] BENTON COUNTY MAP NO. 12-7-00008 BY W. C. GALLOWAY, C.S., DATED JULY 1, 1944. 1/2" PIPE. FIR (8" DIA) 34" DIA (GLO BT) BEARS S80-1/2°E (SIC), **0.64 CHAINS (42.24 FEET)**; FIR (10" DIA) 36" DIA (GLO BT) BEARS N5°W, **0.39 CHAINS (25.74 FEET)**.

[07] BENTON COUNTY SURVEY NO. 6627 BY BERT W. UDELL, P.L.S., DATED APRIL 18, 1978. CORNER FOUND PER C.S. 156.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME

County Survey 207
July 15, 1942 by W.C.G.
Witness Victor Plunkert

Corner to Sections 8, 9, 16 and 17 T. 11 S. R. 7 W. of the Will. Mer.
Set $\frac{1}{2}$ " galv. pipe from fir 40' S. 30° E., 58' stump
Marys River North 1.10
" " West 0.75
" " South .75
" " S bank 1.608

Marked ash 10" in dia. bears N. 15° 20' W. 1.074
" " " " " " 9. 46° 28' E. 1.876
" Vine maple 5 $\frac{1}{2}$ " " " " S. 14° 23' E. .798
" Ash 10" " " " " N. 36° 40' W. 1.077

C.S. #265
Dec. 1939 by W.C.G.
Witness Warren Norton and
Walter Norton.

$\frac{1}{4}$ Sec. Cor. bet. Secs. 14 and 15 T. 11-7
Set $\frac{3}{4}$ " pipe
Fir 40" in dia. bears S. 25° E. 2.12 stump
Mtd. " 3" " " " N. 44 $\frac{1}{2}$ ° E. 1.154
" 4 " " " " S. 63 $\frac{3}{4}$ ° E. 1.297
" Digwood 10" " " " S. 25° E. 1.352

C.S. 231
Dec. 22, 1941
by W.C. Galloway
Adrian Seits
Walter Fauerso

S.E. corner of Jesse Wood C. 1.75 T. 12-6
38" x 36" iron rod
Fir 60" in dia. bears N. 10° W (3.87) 3.854 to spike
" 15" " " " S. 1° W. 1.71 Stump. (Letters on bark)
Mtd. " 16" " " " S. 35° W. .176 chs.
" " 14" " " " N. 35° W. .134 "

C.S. #231
Sept. 25, 1943 by
W.C. Galloway C.S.
F.M. Beardsley

Corner to Sections 6, 7, 1 and 12 T. 12 S. Rs. 6 and 7 W.
Set a $\frac{3}{4}$ " pipe and mound of stone Set from creek S. 7 W. and stump.
39.939 chains S. 0° 26' E. to $\frac{1}{4}$ sec. cor.
Marked an oak 4" in dia. bears S. 44° 08' E. 6.08 of a chain
" Fir 11" " " " S. 20° E. .270
" " 18" " " " S. 79° W. .190
" Apple 4" " " " N. 55 $\frac{1}{4}$ ° W. .374

C.S. 156
by W.C.G.

Corner to Secs. 7, 8, 17 and 18 T. 12-7
Set a $\frac{3}{4}$ " pipe in hole
Fir 6" in dia. (now 32") bears S. 17 $\frac{1}{2}$ ° E. 1.01 chs. std.
" 8" " " (" 32") " S. 65° W. .98 " " old face.
" 16" " " (" 48") " N. 18 $\frac{1}{2}$ ° W. 2.10 " " "
" 8" " " (" 32") " N. 5° 20' E. 1.73 " " center

C.S. #156
Jan. 15, 1943
by W.C.G.
John R. Thompson
Davis

$\frac{1}{4}$ Sec. Cor. bet. Secs. 7 and 8 T. 12-7
Set $\frac{1}{2}$ " pipe, N. of center lg.
Fir 8" in dia. (now 54") bears S. 86 $\frac{1}{2}$ ° E. .64 std.
" 10" " " (" 36") " N. 5° W. .39 "



$\frac{1}{4}$ -Section corner between sections 7 and 8, Twp. 12-7

1623 | 1463

Reestablishment by W. C. Galloway

January 15, 1943

Set $\frac{1}{2}$ " pipe, N. of Cedar log.

Fir 8" in diam bears S $86\frac{1}{2}^{\circ}$ E

Fir 10" in diam bears N 5° W

Witnesses John R. Thompson and Mr. Davis

.64 chains

.39 chains