

127200640

DATE 03/12/2015

TOWNSHIP 12 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 5 CORNER WEST 1/4
DONATION LAND CLAIM N/A CORNER N/A

COMMON CORNER(S):
EAST 1/4 CORNER SECTION 6

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)
BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY E. P. HENDERSON, D.S., DATED MAY 26, 1875. SET POST FROM WHICH A BURNT CEDAR 16" DIA BEARS **S20°W, 20 LINKS (13.20 FEET)**; A BURNT FIR 20" DIA BEARS **S60°E, 22 LINKS (14.52 FEET)**.
- [02] BENTON COUNTY SURVEY NO. 176 (OLD NO. 74) FIELD NOTES (FIELD BOOK 5, PAGE 60) BY W. C. GALLOWAY, D.C.S., DATED 1910. SET **3/4" PIPE. ORIGINAL CORNER. ALDER 20" DIA BEARS N15°45'E, 0.412 CHAINS (27.19 FEET) SLOPE; ALDER 12" DIA BEARS S46°10'W, 0.362 CHAINS (23.89 FEET) SLOPE.**
- [03] BENTON COUNTY SURVEY NO. 176 (OLD NO. 74) MAP (RECORD OF PLATS BOOK 3, PAGE 67) BY UNKNOWN DRAFTSMAN, NO DATE GIVEN. **3/4" PIPE.**
- [04] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 11, BY W. C. GALLOWAY, D.C.S., DATED SEPTEMBER 1, 1910. SET **3/4" PIPE. ORIGINAL CORNER. BOTH CEDARS STANDING. ALDER 20" DIA (CSBT) BEARS N15°45'E, 0.412 CHAINS (27.19 FEET) SLOPE MEASURE; ALDER 12" DIA (CSBT) BEARS S46°10'W, 0.362 CHAINS (23.89 FEET) SLOPE MEASURE.**
- [05] BENTON COUNTY CORNER RESTORATION NO. 3220. **TRANSCRIBED FROM RECORD [04] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.**
- [06] BENTON COUNTY SURVEY NO. 8574 BY MARK E. STEELE, P.L.S., DATED OCTOBER 25, 1991. **FOUND 1/2" INSIDE DIAMETER IRON PIPE AND 2 BEARING TREES.**

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME

CORNER RESTORATION BOOK NO. 1

Survey # 74
W. C. Galtman

1/4 sec. cor. between sec. 31 & 6 Tps. 11 & 12 - 7.
Set a 3/4" pipe orig. cor. both stumps stbd.
Fir 14" in dia. bears N. 89° 26' E. 1.811' slope measure.
" 16" " " S. 50° 35' E. 1.246' "

Witness W.C. Sigforth, Robert Schepfer, Sam Taylor & Gilbert Mason
Aug. 31, 1910.

Sec. cor. to sec. 31, 32, 5 & 6. Tps. 11 & 12 - 7.
Set 1" pipe orig. cor. 4 stumps stbd. on 1/4 sec & 3 stumps
Alder 12" in dia. bears N. 3° 47' E. .751'
Fir 17" " " S. 25° 14' E. 2.338'
" 14" " " S. 21° 15' W. 1.753' slope measure.
" 12" " " N. 11° 27' W. 1.052'

Witness W.C. Sigforth, Gilbert Mason, Sam Taylor & Robert Schepfer Aug. 31, 1910.

1/4 sec. between sec. 5 & 6 Tps. 12 - 7.
Set 3/4" pipe orig. cor. both corners stbd.

Alder 20" in dia. bears N. 15° 45' E. 412' slope measure.
" 12" " " S. 46° 10' W. 362' "

Witness W.C. Sigforth, Gilbert Mason, Sam Taylor & Robert Schepfer Sept. 1, 1910.

1/4 sec. cor. between sec. 6 & 7 Tps. 12 - 7.

Set Mason eating
Fir 9" in dia. bears N. 70° E. .066'
" 8" " " S. 19° 45' E. .400'

Witness W.C. Sigforth, Gilbert Mason, Sam Taylor & Robert Schepfer Sept. 6, 1910.

Sec. cor. to sec. 6, 7, 1 & 5 Tps. 12 - 7 & 8.

Set post 6" x 6"
Fir 24" in dia. bears N. 60° 6' E. 3.757' slope measure.
Alder 7" " " S. 40° E. 3.00' stbd.
Fir 34" " " S. 30° 14' E. .303'
" 18" " " S. 60° 6' W. 6.142'
" 20" " " N. 77° 50' W. 3.814' slope measure.

Witness W.C. Sigforth, Gilbert Mason, Sam Taylor & Robert Schepfer Sept. 5, 1910.

1/4 cor. between sec. 1 & 6 Tps. 12 - 7 & 8.
Set 4" x 4" stake orig. cor. sang stbd.
Fir 20" in dia. bears N. 98° 25' E. .916'
" 24" " " S. 87° 45' W. .612'

Witness W.C. Sigforth, Gilbert Mason, Sam Taylor & Robert Schepfer Sept. 6, 1910.

75
W.C.G. N.W. cor. David Butterfield D.L.C. # 47 Tps. 12 - 5.

Set 1" pipe
Chitem 8" in dia. bears N. 75° 45' E. .644'
" 3" " " N. 55° W. .268'

Witness Ford & W.B. Cate. Sept. 27, 1910.

76
W.C.G. S.W. cor. Jeremiah Lewis D.L.C. # 45 Tps. 11 - 4.

Set 3/4" pipe
Cppl 8" in dia. bears N. 68° 50' E. .353'
Oak 10" " " S. 16° 15' W. .957'

Witness G. Logsdon & J.W. Dodge. Oct. 6, 1910.

1/4-Section between Sections 5 and 6, Twp. 12-7

Reestablished by W. C. Galloway

September 1, 1910

3220

Set 3/4" pipe original corner

both cedars standing

Alder 20" in diam bears N. 15° 45' E

.412 chains (slope measure)

Alder 12" in diam bears S. 46° 10' W

.362 chains (slope measure)

Witnesses W. C. Siefert, Gilbert Mason, Ivan Taylor and Robert Shafer