

134875020

DATE 04/09/2013TOWNSHIP 13 SOUTH, RANGE 4 WEST, WILLAMETTE MERIDIAN; SECTION 6 CORNER N/A
DONATION LAND CLAIM GEORGE FOGLE NO. 75 CORNER SOUTHEASTCOMMON CORNER(S):RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

[01] GENERAL LAND OFFICE (GLO) NOTES OF THE GEORGE FOGLE DONATION LAND CLAIM NO. 75 BY DENNIS HATHORN, D.S., DATED FEBRUARY 14, 1854. ***PLANTED A SANDSTONE 6" X 10" X 24" FROM WHICH AN OAK 20" DIA BEARS N3-1/2°W, 628 LINKS (414.48 FEET); AN OAK 12" DIA BEARS N23-1/2°W, 504 LINKS (332.64 FEET).***

[02] BENTON COUNTY SURVEY NO. 4478 BY HOWARD E. TAYLOR, P.E., DATED NOVEMBER 6, 1967. ***PLOWED, BT'S GONE. SET 1-1/4" PIPE 15" UNDER WITH SCRAP METAL, 5/8" ROD ON SURFACE. SOUTHEAST CORNER OUTDOOR BRICK FIREPLACE BEARS N23°W, 121.5 FEET. THE SOUTHEAST CORNER OF THE FOGLE CLAIM WAS SET BY TURNING 90°00' EASTERLY FROM THE LINE BETWEEN THE SOUTHWEST AND NORTHWEST CORNERS OF THE FOGLE CLAIM AND RUNNING GLO RECORD 40 CHAINS FROM THE SOUTHWEST CORNER. THE SOUTHWEST CORNER OF THE FOGLE CLAIM MAY HAVE BEEN REESTABLISHED INCORRECTLY THOUGH. A 5/8" ROD WAS SET ON THE LINE BETWEEN THE SOUTHEAST AND THE SOUTHWEST CORNERS OF THE FOGLE CLAIM 252.9 FEET FROM THE SOUTHEAST CORNER AND 4.0 FEET NORTH OF ANCHOR POST. AN ANGLE WAS TURNED FROM THE LINE BETWEEN THE SOUTHEAST AND THE SOUTHWEST CORNERS 90°00' NORTHERLY AND A 5/8" ROD WAS SET 93.72 FEET FROM THE SOUTHEAST CORNER AND 3.5 FEET NORTHEAST OF ANCHOR POST.***

[03] BENTON COUNTY SURVEY NO. 10117 BY THEODORE JAMES LANGTON, P.L.S., DATED NOVEMBER 10, 2005. ***CORNER NOT TIED OR DESCRIBED.***

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE. CORVALLIS OR 97333; PH. 766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME