

135240100

DATE 01/25/2008TOWNSHIP 13 SOUTH, RANGE 05 WEST, WILLAMETTE MERIDIAN; SECTION 32 CORNER SOUTH 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

POINT ON NORTH LINE OF SECTION 5, TOWNSHIP 14 SOUTH, RANGE 5 WEST

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) FIELD NOTES BY JAMES E. FREEMAN, D.S., DATED FEBRUARY 2, 1853. *SET POST. DEPOSIT CHARRED STAKE AND RAISED MOUND WITH TRENCH.*
- [02] BENTON COUNTY SURVEY NO. 729 (OLD NO. 306) FIELD NOTES (BOOK 25, PAGE 39) BY W. C. GALLOWAY, C.S., DATED OCTOBER 22, 1920. *SET 3/4" PIPE. ASH 8" DIA BEARS S65°20'E, 1.150 CHAINS (75.90 FEET); ASH 9" DIA BEARS S18°40'W, 0.674 CHAINS (44.48 FEET).*
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 145 BY W. C. GALLOWAY, C.S., DATED OCTOBER 23, 1920. *SET 3/4" PIPE AT 8.11 CHAINS (535.26 FEET), N89°49'W OF STANDARD 1/4 CORNER. ASH 8" DIA BEARS S65°20'E, 1.150 CHAINS (75.90 FEET); ASH 9" DIA BEARS S18°40'W, 0.674 CHAINS (44.48 FEET).*
- [04] BENTON COUNTY CORNER RESTORATION NO. 1779. *TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.*

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: BERNARD S. ALTENBACH, ENGINEER/SURVEY TECH.
DATA ENTRY BY: SAME

Q.S. 306)

 $\frac{1}{4}$ sec cor on S. line of sec. 84 T13-5WSet $\frac{1}{2}$ " galv. pipe + gravel 15" under surfaceSet cor at 8.11 chs. N89°49'W of standard $\frac{1}{4}$ sec. cor. on N of sec. 3.

11)

Cor betw sec. 374 on 3rd Standard Parallel S 3145Set a $\frac{1}{2}$ " galv iron pipe + gravel 14" under surface40.083 chs. N89°49'W of std. $\frac{1}{4}$ cor

Mile post (I.M. Richards) bears S57°30'W 2.208 chs

E. rail at N89°49'W. is 1.894 chs.

 $\frac{1}{2}$ " galv pipe bears S 0°23'E 20.607 chs.

11)

Sec. cor betw sec. 33 + 34 on 3rd Std. Parallel S. T13-5W

Set qt. bottle 14" under surface at 8.11 chs W. of std. cor.

E. rail at S89°49'E is 6.216 chs.

40 cor. is $\frac{1}{2}$ " pipe N89°49'W 11.931 chs. which has

U.S. G.S. B.M. bearing N20°20'W 1.407 chs.

11)

Std. $\frac{1}{4}$ sec. cor. on N of sec. 4 T. 14-5Set $\frac{3}{4}$ " galv pipe - proportional dist.

Ash 8" in dia bears S. 73°15'W .807 chs

Oak 11" " " " N48°35'W .1.928"

11)

 $\frac{1}{4}$ sec. cor. on S. line of sec. 33 T 13-5Set $\frac{1}{2}$ " galv pipe 8.11 chs. W. of Std. $\frac{1}{4}$ cor.~~Ash 15" in dia bears S 70° 5' 0.582 chs. Stump 1153~~~~" 5" " " " S 59° 25' E 5.45" out '53~~

11)

Cor. betw. sec. 4 + 5 on 3rd Std. Parallel S. T 14-5Set a $\frac{1}{2}$ " galv. pipe proportional dist. 40.083 chs. N of cor.N. cor. of octagon ^{concrete} water tank. bears N64°22'W 2.572 chs

Stk. S. 20 feet.

11)

Cor. betw. sec. 32 + 33 on 3rd Std parallel S T 13-5Set $\frac{1}{2}$ " pipe at 8.10 chs. N89°49'W of std. cor.A $\frac{3}{4}$ " pipe bears S. at 14.5 - 20 feet.

11)

Std. $\frac{1}{4}$ cor on N. of sec. 5 T 14-5Set $\frac{1}{2}$ " pipe proportional dist. 40.083 chs W. of sec cor.

Another post 14" in dia. bears. N25°E .124 chs.

Maple 14" " " " N87°15'W 1.788 chs.

11)

 $\frac{1}{4}$ Sec. cor on S. line of sec. 38 T 13-5Set $\frac{3}{4}$ " pipe at 8.11 chs N89°49'W. of Std. $\frac{1}{4}$ cor.

Ash 8" in dia. bears S 65°20'E 1.150 chs

" 9" " " " S. 18°40'W .674 "



11)

Sec. Cor betw. sec. 5 + 6 on 3rd Std parallel S. T 14-5Set $\frac{1}{2}$ " galv pipe. proportional dist 40.083 chs W

Oak 2" in dia. bears S. 35°10'W .752 chs

Apple 14" " " " N 41° W. .258 chs

$\frac{1}{4}$ -Section corner on S. line of section 32, Twp. 13-5

1779

Reestablishment by W. C. Galloway

October 23, 1920

Set a $\frac{3}{4}$ " pipe at 8.11 chains N $89^{\circ} 49'$ W of std. $\frac{1}{4}$ corner

Ash 8" in diam bears S $65^{\circ} 20'$ E

1.150 chains

Ash 9" in diam bears S $18^{\circ} 40'$ W

.674 chains

Witness W. W. Larsen