

DATE 08/04/2010

TOWNSHIP 13 SOUTH, RANGE 05 WEST, WILLAMETTE MERIDIAN; SECTION 06 CORNER N/A
DONATION LAND CLAIM JACOB M. CURRIER NO. 39 CORNER NORTHEAST

COMMON CORNER(S):

NONE

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS MEASURED TO THE FACE OF BEARING TREES.

[01] GENERAL LAND OFFICE (GLO) NOTES OF THE JACOB M. CURRIER DONATION LAND CLAIM (DLC) NO. 39 BY D. HATHORN, D.S., DATED JANUARY 11, 1854. SET A POST. MARKED A 30" W. OAK N121/2°E, 804 LKS. (530.64 FT.) AND AN 18" W. OAK N31°E, 837 LKS. (552.42 FT.).

[02] COUNTY SURVEY OLD NO. 30 (NO NEW NO.) FIELD NOTES (BOOK 28, PAGE 38) BY W. C. GALLOWAY, C.S., DATED MARCH 21, 1921. SET A 1 1/4" X 36" GALV. PIPE. FOUND A 30" OAK STUMP (GLO BT) N12°30'E, 8.04 CHS. (530.64 FT.) AND AN 18" OAK (GLO BT) N31°E, 8.37 CHS. (552.42 FT.), STANDING. MARKED A 6" OAK S68°15'E, 0.485 CHS. (32.01 FT.).

[03] CORNER RESTORATION BOOK NO. 1, PAGE 156 BY W. C. GALLOWAY, C.S., DATED MARCH 21, 1921. SET A 1 1/4" X 36" GALV. PIPE. FOUND A 30" OAK STUMP (GLO BT) N12°30'E, 8.04 CHS. (530.64 FT.) AND AN 18" OAK (GLO BT) N31°E, 8.37 CHS. (552.42 FT.), STANDING. MARKED A 6" OAK S681/4°E, 0.485 CHS. (32.01 FT.).

[04] CORNER RESTORATION NO. 1793. TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.

[05] LOOSE LEAF NOTES OF ROUTE 1, SECTION F (BELLFOUNTAIN RD.) BY W. C. GALLOWAY, C.S., DATED JULY 26, 1945. FOUND A 1 1/4" X 36" G. P. FOUND A 30" OAK STUMP (GLO BT) N12°30'E, 8.04 CHS. (530.64 FT.), AN 18" OAK STUMP (GLO BT) N31°E, 8.37 CHS. (552.42 FT.) AND A 6" OAK (CSBT) S68°15'E, 0.485 CHS. (32.01 FT.). SET A 1/2' GALV. BOLT 30.00' EAST AND A 5/8" BOLT WEST, AT 90° ANGLES TO THE CENTER LINE OF THE ROAD.

[06] BENTON COUNTY MAP NO. 13-5-00006, NO DATE OR DRAFTSMAN GIVEN. 1/2" GALV. BOLT TO EAST OF CORNER. 5/8" BOLT TO WEST OF CORNER.

COMMENTS/LOCATION/ETC:

NOTES:

THIS IS A MICROSOFT WORD 2003 DOCUMENT NAMED "35839010" CREATED FROM A BOILER PLATE DOCUMENT NAMED "HISTORY", WHICH HAS A STYLESHEET NAMED "CORNER" ATTACHED TO IT.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE

ADDRESS: 360 S.W. AVERY AVE. CORVALLIS OR 97333; PH. 766-6821

RESEARCH BY: BERNARD S. ALTENBACH, ENGINEER/SURVEY TECH.

DATA ENTRY BY: SAME

- C.S. 277
W.C. Gallaway C.S.
Floyd Willert
Mar. 14, 1921.
N.E. cor. of J. Q. Thornton D.L.C. 37 T. 10-3
Set a 1 1/4" square pipe
A Granite stone about 12"x16"x? No. in pavement
Bears N. 75° 45' W. 1.92 obs.
Fir 24" in dia. bears N. 63° 53' W. 2.456 obs.
S.W. corner of a House bears N. 6° 15' W. 1.530 obs.
Cherry tree 7" in dia. bears N 50° 20' E. 1.226 "
- C.S. 277
S.E. cor. of J. Q. Thornton D.L.C. 37 T. 11-3
Set a 3/4" iron pin under a stone 5"x10"x12". set 3000 10" under surface
Walnut tree 16" in dia. bears S. 88° 10' W. 7.430 obs.
Oak 20" " " N. 7° W. 4.22 " std.
- C.S. 277
Corner on East line of J. Q. Thornton D.L.C. 37 T. 11-3.
Stone 6"x8"x? with cross "T" on top. A looted stone.
A 1 1/4" pipe bears S. 89° 42' W. 1.747 obs.
- C.S. 30 cont.
N.E. corner of Jacob M. Currier D.L.C. # 39 T. 13-5
Set a 1 1/4"x36" galv. pipe
Oak 30" in dia. bears N. 12 1/2° E. 8.04 obs. stamp. 530.04
" 18" " " N. 31° E. 8.37 " std. 552.02
" 6" " " S. 68 1/4° E. 4.85 " 22.01
- "
S.W. corner of Jesse Ownby D.L.C. 57 T. 13-5.
Set a granite stone 6"x6"x11"
Double oak 18"x30" in measure bears N. 4° 30' E. 367 obs.
" 24" in dia. bears N. 88 1/2° E. 1.16 " std.
" 24 " " S. 30 1/2° E. 2.25 " STAMP.
- "
N.W. corner of Geo. H. Herbert D.L.C. 40, T. 13-5
Sand Stone 12"x12"x?
Set a 3/4" pipe East 30 feet
Oak 30" in dia. bears S. 77° E. 1.53 obs. std.
" 9" " " S. 39° E. .92 "
- "
Most West
N.W. corner of Jesse Ownby D.L.C. 69 T. 12-5.
Stone 24"x9"x7" set.
Oak 10" in dia. bears S. 30° E. .036 obs.
" 20" " " S. 83 1/2° W. 1.03 " std.
" 15" " " N. 81° W. 2.30 " "
- "
S.W. corner of Jacob Martin D.L.C. 42 T. 12-6
Set 1" pipe & bones, orig corner, oak stamp N. 64 1/2° E. 1.40 obs.
Oak 20" in dia. bears N. 47 1/2° E. .37 obs. std. Hole S. 6° W. .08
" 12" " " S. 73° E. .151 "
" 5" " " S. 2 3/4° E. .224 "

C.S.
W.C. Gallaway
Floyd Willert
Mar. 14, 1921.C.S.
W.C. Gallaway
Floyd Willert
Mar. 14, 1921.C.S.
W.C. Gallaway
Floyd Willert
Mar. 14, 1921.C.S.
W.C. Gallaway
Floyd Willert
Mar. 14, 1921.C.S.
W.C. Gallaway
Floyd Willert
Mar. 14, 1921.

N. E. corner of Jacob M. Currier DLC 39, Twp. 13-5

Reestablishment by W. C. Galloway

Set a $1\frac{1}{4}$ " x 36" galvanized pipe
Oak 30" in diam bears N $12\frac{1}{8}$ ° E
Oak 18" in diam bears N $31\frac{3}{8}$ ° E
Oak 6" in diam bears S $68\frac{1}{4}$ ° E

Witness George E. Linton

1793

March 21, 1921

8.04 chains (stump)
8.37 chains (std.)
.485 chains