

135844010

DATE 01/05/2015TOWNSHIP 13 SOUTH, RANGE 5 WEST, WILLAMETTE MERIDIAN; SECTION 2 CORNER N/A
DONATION LAND CLAIM LEWIS DENNIS NO. 44 CORNER NORTHEAST**COMMON CORNER(S):**

POINT ON THE SOUTH LINE OF THE JESSE GAGE DONATION LAND CLAIM NO. 45.

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES OF THE LEWIS DENNIS DONATION LAND CLAIM NO. 44 BY DENNIS HATHORN, D.S., DATED FEBRUARY 15, 1854. **SET A POST FROM WHICH AN OAK 10" DIA BEARS N7°W, 113 LINKS (74.58 FEET); AN OAK 36" DIA BEARS S62°W, 59 LINKS (38.94 FEET); AN OAK 12" DIA BEARS S57°E 394 LINKS (260.04 FEET).**
- [02] BENTON COUNTY SURVEY NO. 253 (OLD NO. 110) FIELD NOTES (FIELD BOOK 15, PAGE 2) BY W. C. GALLOWAY, D.C.S., DATED MAY 29, 1911. **3/4" PIPE. OAK 10" DIA (GLO BT) BEARS N7°E, 1.13 CHAINS (74.58 FEET) STANDING; OAK 12" DIA (GLO BT) BEARS S57°E, 3.94 CHAINS (260.04 FEET) STANDING; DOUBLE FIR 32" DIA BEARS S43°30'W, 0.147 CHAINS (9.70 FEET).**
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 46, BY W. C. GALLOWAY, D.C.S., DATED MAY 30, 1911. **SET A 3/4" PIPE. OAK 10" DIA (GLO BT) BEARS N7°00'E, 1.13 CHAINS (74.58 FEET) STANDING; OAK 12" DIA (GLO BT) BEARS S57°00'E, 3.94 CHAINS (260.04 FEET) STANDING; DOUBLE FIR 32" DIA (CSBT) BEARS S43°30'W, 0.147 CHAINS (9.70 FEET).**
- [04] BENTON COUNTY CORNER RESTORATION NO. 1810. **TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.**
- [05] BENTON COUNTY SURVEY NO. 1444 (OLD NO. 131) FIELD NOTES (FIELD BOOK 63, PAGE 81) BY W. C. GALLOWAY, C.S., DATED SEPTEMBER 9, 1939. **3/4" PIPE NORTHEAST CORNER OF LEWIS DENNIS.**
- [06] BENTON COUNTY MAP NO. 13-5-00002 BY WALTER W. LARSEN, D.C.S., NO DATE GIVEN. **3/4" PIPE.**
- [07] BENTON COUNTY MAP NO. 13-5-00003 BY WALTER W. LARSEN, D.C.S, DATED APRIL 16, 1924. **3/4" PIPE. 3/4" PIPE SOUTHERLY 1.753 CHAINS (115.70 FEET).**
- [08] BENTON COUNTY SURVEY NO. 4269 BY JOHN F. GANNON, P.L.S., DATED JUNE 13, 1966. **FOUND 3/4" PIPE. FOUND A DOUBLE FIR STUMP (CSBT) S43°30'W, 9.7 FEET. SET A 1/2" IRON ROD S89°24'W, 46.36 FEET.**
- [09] BENTON COUNTY SURVEY NO. 9685 BY W. C. GALLOWAY, C.S., NO DATE GIVEN. **3/4" PIPE. OAK 10" DIA (GLO BT) BEARS N7°E, 1.13 CHAINS (74.58 FEET) STANDING; OAK 12" DIA (GLO BT) BEARS S57°E, 3.94 CHAINS (260.04 FEET); 32" DIA "Y" FIR S43-1/2°W, 0.147 CHAINS (9.70 FEET).**

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: BERNARD S. ALTENBACH, L.S.I.
DATA ENTRY BY: SAME

CORNER RESTORATION BOOK NO. 1

- Sunny #10
 N. E. car. of Lewis Denis D.L.C. # 44 TP 13-5. Sum
 Set a $\frac{3}{4}$ " split.
 Oak 10" in dia. bears N. 7° 00' E. 113 ch. stal
 " 12" " " S. 57° 00' E. 394 " "
 Double fir 32' " S. 45° 30' W. 147 "
 Witnesses Wm Stevens & Walter Smith May 30, 1911.
- Sec. car. to sec. 31, 32, 51 & 6 Tps. 11 & 12 - 6.
 Set a quart bottle.
 Fir 24" in dia. bears N. 13° 00' E. 62 ch. down
 Oak 14" " " S. 68° 00' E. 33 " " stal
 " 12" " " S. 62° 00' W. 107 " "
 Fir 26" " " N. 24° 00' W. 86 " "
 Witnesses R. L. Glass, J. H. Goldman & W. P. McFarland May 31, 1911.
- 1/4 sec. car. set. sec. 32 & 5 Tps. 11 & 12 - 6.
 Set a qt. bottle.
 Maple 24" in dia. bears S. 18° W. 30 ch. stal.
 Fir 8" " " N. 12° W. 68 " (63)
 Witnesses R. L. Glass, J. H. Goldman & W. P. McFarland June 1, 1911.
- Sec. car. to sec. 32, 33, 40 & 5 Tps. 11 & 12 S. R. 6W.
 Stone 6" x 6" x 6" (No. 9 Car. 414)
 Oak 14" in dia. bears N. 20° E. 72 ch. stal
 " 14" " " S. 83° 30' E. 70 " "
 " 12" " " N. 9° 30' W. 59 " " (60)
 Witnesses R. L. Glass, J. H. Goldman & W. P. McFarland June 1, 1911.
- 1/4 car. set. 29 & 32 TP 11-6.
 Set qt. bottle. Cherry down
 Maple 16" in dia. bears N. 32° E. 44 ch. stal.
 Fir 15" " " S. 88° 30' W. 066 "
 Witnesses R. L. Glass, J. H. Goldman & W. P. McFarland June 2, 1911.
- 1/4 sec. car. set. sec. 32 & 33 TP. 11-6.
 Set a stone 6" x 6" x 10" orig. car. found stone Feb. 25, 1946
 Fir 14" in dia. bears S. 72° E. 65 ch. stal down
 Oak 10" " " N. 27° 50' W. 105.733 "
 Witnesses R. L. Glass, J. H. Goldman & W. P. McFarland June 2, 1911.
- 1/4 sec. car. set. sec. 31 & 32 TP. 11-6.
 Set a $\frac{3}{4}$ " split 26" long.
 Oak 10" in dia. bears N. 14° E. 38 ch. stal
 Fir 10" " " N. 88° W. 75 " "
 Witnesses Bert Reed, W. P. McFarland July 11, 1911.

N. E. corner of Lewis Denis DLC 44, Twp. 13--8

Reestablishment by W. C. Galloway

May 30, 1911

1810

Set a 3/4" pipe

Oak 10" in diam bears N. 7° 00' E -

Oak 12" in diam bears S. 57° 00' E

Double Fir 32" in diam bears S 43° 30' W

1.13 chains (standing)

3.94 chains (standing)

.147 chains

Witnesses William Stevens and Walter Smith