

135847020

DATE 05/22/2013

TOWNSHIP 13 SOUTH, RANGE 5 WEST, WILLAMETTE MERIDIAN; SECTION 23 CORNER N/A
DONATION LAND CLAIM ISAAC W. WINKLE NO. 47 CORNER SOUTHEAST

COMMON CORNER(S):

ON THE NORTH LINE OF THE WILEY WINKEL D.L.C. NO. 48

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES OF THE ISAAC W. WINKLE DONATION LAND CLAIM (DLC) NO. 47 BY DENNIS HATHORN, D.S., DATED JANUARY 4, 1854. **PLANTED SANDSTONE 6" X 15" X 20" FROM WHICH A W. OAK 18" DIA BEARS S13°E, 6.15 CHAINS (405.90 FEET); A W. OAK 20" DIA BEARS S22°E, 7.15 CHAINS (471.90 FEET).**
- [02] GENERAL LAND OFFICE NOTES OF THE WILEY WINKLE DLC NO. 48 BY DENNIS HATHORN, D.S., DATED JANUARY 4, 1854. **ISAAC W. WINKEL'S SOUTHEAST CORNER.**
- [03] BENTON COUNTY ROAD NO. 338 FIELD NOTES (FIELD BOOK 16, PAGE 21) BY W. C. GALLOWAY, C.S., DATED 1914. **FROM SOUTHEAST CORNER OF DLC 47 S1°37'E, 7.250 CHAINS (478.50 FEET) TO 1/4" PIPE. DLC CORNER BEARS N13°44'W, 12.080 CHAINS (797.28 FEET) OF 3/4" PIPE.**
- [04] BENTON COUNTY MAP NO. 13-5-00016 BY WALTER W. LARSEN, D.C.S., DATED 1920. **STONE 6" X 15" X 20". OAK 18" DIA (GLO BT) BEARS S13°E, 6.15 CHAINS (405.90 FEET); OAK 20" DIA (GLO BT) BEARS S22°E, 7.15 CHAINS (471.90 FEET). 1/4" PIPE BEARS S0°21'W, 7.25 CHAINS (478.50 FEET); 3/4" PIPE BEARS S13°44'E, 12.080 CHAINS (797.28 FEET); 5/8" IRON ROD BEARS S0°21'W, 11.56 CHAINS (762.96 FEET).**
- [05] BENTON COUNTY SURVEY NO. 919 FIELD NOTES (FIELD BOOK 34, PAGE 44) BY WALTER W. LARSEN, D.C.S., DATED SEPTEMBER 18, 1924. **1" SQUARE ROD IN A STONE.**
- [06] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 174, BY WALTER W. LARSEN, D.C.S., DATED SEPTEMBER 18, 1924. **SET 1/2" X 1-1/2" IRON BAR AND STONE. OAK 18" DIA (GLO BT) BEARS S13°E, 6.15 CHAINS (405.90 FEET) STANDING; OAK 20" DIA (GLO BT) BEARS S22°E, 7.15 CHAINS (471.90 FEET) STANDING; 3/8" PIPE BEARS SOUTH, 7.25 CHAINS (478.50 FEET).**
- [07] BENTON COUNTY CORNER RESTORATION NO. 1817. **TRANSCRIBED FROM RECORD [06] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.**
- [08] BENTON COUNTY SURVEY NO. 954 (OLD NO. 304) FIELD NOTES (FIELD BOOK 35, PAGE 10) BY WALTER W. LARSEN, D.C.S., DATED 1925. **SET ON SOUTHEAST CORNER OF ISAAC WINKLE DLC 47. 3/8" PIPE BEARS SOUTH, 7.25 CHAINS (478.50 FEET). OAK 18" DIA (GLO BT) BEARS S13°E, 6.15 CHAINS (405.90 FEET); OAK 20" DIA (GLO BT) BEARS S22°E, 7.15 CHAINS (471.90 FEET).**
- [09] BENTON COUNTY SURVEY NO. 1221 (OLD NO. 304) BY UNKNOWN DRAFTSMAN AND DATE. **STONE AND 1" ROD. OAK 18" DIA (GLO BT) BEARS S13°E, 6.15 CHAINS (405.90 FEET). 3/8" PIPE BEARS S0°21'W, 7.25 CHAINS (478.50 FEET). ROD BEARS S0°21'W, 11.56 CHAINS (762.96 FEET).**
- [10] BENTON COUNTY SURVEY NO. 2481 BY CURTIS C. HANSON, C.S., DATED JUNE 3, 1953. **STONE 6" X 15" X 20". OAK 18" DIA (GLO BT) BEARS S13°E, 6.15 CHAINS (405.90 FEET); OAK 20" DIA (GLO BT) BEARS S22°E, 7.15 CHAINS (471.90 FEET). 3/8" PIPE BEARS S0°21'W, 7.25 CHAINS (478.50 FEET).**
- [11] BENTON COUNTY SURVEY NO. 4741 BY NICKOLAS A. YINGER, P.L.S., DATED APRIL 21, 1969. **FOUND STONE. FOUND 1/4" PIPE BEARS S0°21'W, 478.50 FEET.**
- [12] BENTON COUNTY SURVEY NO. 4754 BY NICKOLAS A. YINGER, P.L.S., DATED MAY 13, 1969. **FOUND STONE.**

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE

ADDRESS: 360 S.W. AVERY AVE. CORVALLIS OR 97333; PH. 766-6821

RESEARCH BY: DAVID L. MALONE, P.L.S.

DATA ENTRY BY: SAME

Sept 15, 1924
M. W. L.
Harry Hubbard
Peter Whitaker

Oct. 22, 1924
Bork
Decker

CORNER RESTORATION SACK NO. (

S. E. Corner 15200 W. 14th St. El. 147 T 13 S R 6 W
Set $2\frac{1}{2} \times 1\frac{1}{2}$ " iron bar & stone
Oak 18" S 13° E 6.15' chs standing
" 20" S 22° E 7.12"
 $\frac{3}{4}$ " pipe south 7.21"

N. W. Cor. A. F. Ragsdale El. 46 T 13 S R 6 W.
Set $\frac{1}{2}$ " rod 14" under surface from which
Oak 12" in dia. bears S 61° 20' W . 8.91 chs
S. E. cor. house " N 73° 15' W. 1.76 "

N. E. Cor. sec. 4. T. 10 S. R. 6 W.

Set 1" iron rod from which a
Fir 50" in dia. bears N 25° W 1.18 chs stump
Lard 4" " " " N 12° E . 42" st. ch.
Oak 14" " " " S 34° W 1.09" ahead
" " " " S 20 $\frac{1}{2}$ ° E 1.19 "
Marked Fir 10" " " " S 75° W . 0.55 "

$\frac{1}{4}$ cor. between sees 3 & 4 T. 13 S. R 6 W.

Set $1\frac{1}{2}$ " rod (ford axle) set from fir stump

Fir 60" S $23\frac{1}{2}$ ° W ~~2.15~~ 2.15 chs -
" W. " 24" N ~~16~~ 16° E . 6.72 "

Apr.
M. C.
changed by
M. C. Hall 1924
By Shannon at base. W. C.

~~A~~ $\frac{1}{4}$ cor. betw sees. 4 & 5 T. 13 S R 6 W.

Set $1\frac{1}{2}$ " rod. from which a

Dbl. Fir 30" in dia. bears N 52° W . 80

Fir (10") 30" " " " N 85° W . 6.4 st.

" (15") 32" " " " S 50° E . 1.87 "

Jan 5 & 6

1924

M. W. L.

Jones &

boys

S. W. Corner Wm. Quiney El. 54 T 13 S R 6 W.

Set $1\frac{1}{2}$ " pipe

Fir 48" in dia. bears N 53 $\frac{1}{2}$ ° E . 8.70 chs face

Oak 30" S 84° E 1.02 "

Fir 18" N 60° E . 1.50 "

" 16" S 19° W . 2.82 "

S. E. Cor Wm. Quiney El. 54 T 13 S R 6 W

Set 1" pipe

Fir 60" in dia. bears N 44° W 1.19 st. chs

" 40" " " S 60° E . 1.82 "

" 16" " " S 54° W . 2.72 "

$\frac{1}{4}$ Cor. betw sees. 13 & 24 T. 13 S R 6 W

Set stake from which a

Fir 18" in dia. bears S 76° W . 3.9 chs.

" 50" " " N 37° W . 3.3 " st.

Oak 10" " " S 50° W . 7.8 " "

May 19
M. C.
25 Ms C

Feb.
M. C.
25 Ms C

Sept
M. C.
engineer

Apr.
M. C.
W. C.

Apr.
M. C.

Apr.
M.

1817

S. E. corner Isaac Winkle Cl. 47, Twp. 13 S., R. 5 W.
Reestablishment by W. C. Galloway

Set $\frac{1}{2}$ x $1\frac{1}{2}$ iron bar and stone

Oak 18" in diam bears S 13° E

Oak 20" in diam bears S 22° E

$\frac{3}{8}$ " pipe bears south

Witnesses W. L. Larson, Harry Hubbard and Pete Whitaker

September 18, 1924

6.15 chains(standing)

7.15 chains

7.25 chains