

F. TUCKER / R. AARSETH

1983

19

256

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 13 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

W. 0° 07' E., beginning new measurement.  
Ascend over SE. slope.

2.70 Spur, slopes S. 80° E.; desc. over NE. slope.

5.40 Creek, 1 lk. wide, course S. 50° E.; asc. over SW. slope changing to SE. slope.

19.92 The cor. of secs. 14, 15, 22, and 23, reestablished by proportionate measurement and recorded by W. C. Galloway, County Surveyor, in 1914, and is accepted as the best available evidence of the position of the original corner, monumented with an iron pipe, 1/2 in. diam., firmly set, projecting 3 ins. above ground, from which the remains of bearing trees mkd. by Galloway

A fir stump, 18 ins. diam., bears N. 47 1/2° E., 46 1/2 lks. dist., with scribe marks BT visible on opened blaze.

A fir stump, 24 ins. diam., bears S. 16° E., 46 lks. dist., with healed blaze.

A root hole, bears S. 25 1/2° W., 35 1/2 lks. dist.

A fir stump, 34 ins. diam., bears N. 16 1/2° W., 72 lks. dist., with healed blaze.

At the corner point  
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

T 13 S	R 6 W
S 15	S 14
S 22	S 23

1983

from which new bearing trees

A fir, 9 ins. diam., bears N. 33° E., 17 lks. dist., mkd. T13S R6W S14 BT.

A fir, 11 ins. diam., bears S. 55 1/2° E., 55 lks. dist., mkd. T13S R6W S23 BT.

A fir, 11 ins. diam., bears S. 29 1/2° W., 71 1/2 lks. dist., mkd. T13S R6W S22 BT.

A fir, 15 ins. diam., bears N. 30 1/2° W., 5 lks. dist., mkd. T13S R6W S15 BT.

Corner is located in down wire fence, extending N. and S.

From this point, the 1/4 sec. cor. of secs. 14 and 15, perpetuated and recorded by W. C. Galloway, County Surveyor, in 1914 and 1940, from original evidence no longer in existence, bears N. 0° 06' E., 40.14 chs. dist., monumented with an iron pipe, 3/4 in. diam., firmly set, with top, 12 ins. below the surface of ground.

At the corner point

136500440

257

Dependent Resurvey, Portion of the Subdivisional Lines,  
T. 13 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 40 ins. in the ground, with top 12 ins. below the surface of the ground, directly over iron pipe, with brass cap mkd.</p> <p style="text-align: center;">T 13 S    R 6 W           ¼ S 15   S 14 1983</p> <p>from which new bearing trees</p> <p>    A pine, 11 ins. diam., bears S. 3° E., 215 lks. dist., mkd. ¼ S14 BT.</p> <p>    A fir, 13 ins. diam., bears S. 24½° W., 186 lks. dist., mkd. ¼ S15 BT.</p> <p>From this same point, the ¼ sec. cor. of secs. 15 and 22, perpetuated and recorded by W. C. Galloway, County Surveyor, in 1914, bears N. 89° 51' W., 40.02 chs. dist., monumented with a yew post, 6 ins. diam., loosely set, projecting 3 ft. above ground, alongside of which is a fir post, 4 ins. square, firmly set, projecting 10 ins. above ground, with scribe marks CS 208 visible, from which the remains of an original bearing tree</p> <p>    A maple, 27 ins. diam., bears N. 23° W., 16 lks. dist., with reverse scribe marks BT visible on opened blaze. (Record, N. 34° W.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 13 S    R 6 W           ¼ - S 15               S 22 1983</p> <p>from which new bearing trees</p> <p>    A fir, 27 ins. diam., bears S. 61½° W., 53½ lks. dist., mkd. ¼ S22 BT.</p> <p>    A fir, 15 ins. diam., bears N. ¼° W., 69 lks. dist., mkd. ¼ S15 BT.</p> <p>Deposit wooden posts alongside iron post.</p> <p>Corner is located in a down wire fence, extending E. and W.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, oak, hemlock, maple, alder, and yew; undergrowth, vine maple, salal, poison oak, hazel, Scotch broom, blackberry, salmonberry, devil's club, fern, and grasses.</p> <hr/> <p>From the ¼ sec. cor. of secs. 14 and 23, perpetuated and recorded by W. C. Galloway, County Surveyor, in 1914, monumented with an iron pipe, 1½ ins. diam., firmly set, with top 4 ins. below the surface of the ground, from which the remains of an original bearing tree</p>
--------	---