

136520140

CORNER IN COUNTY SURVEY #190 450 + 566

2222

$\frac{1}{16}$ CORNER NORTH LINE OF SW $\frac{1}{4}$, SECTION 35, T 13 S, R 6 W, W, M.

REESTABLISHED BY R. WILSON HUTCHISON, P.E.

4/7/1971

FOUND SQUARED FIR STAKE

FIR N1° 00' E (STUMP DECAYED)	.160 CHS	10.56'
FIR N 56° 00' E (STUMP DECAYED)	.228 CHS	15.048'

SET 1" X 4' IRON ROD

FIR 18" N 15° 00' W	6.3'
FIR 14" S 38° 00' W	24.0'

WITNESSES: BILL ROBINSON, LARRY LAYLON



136520140

BENTON COUNTY SURVEYORS OFFICE · CORNER RESTORATION 1958


T 13 S, R 6 W, W. B. & M., BENTON COUNTY, OREGON

REPORTED BY LES ROBERTS

SECTION 35

TITLE P.L.S. 1039

DATE 1-6-81



● OFFICIAL CORNER FOUND
○ CORNER-SET

1/16 CORNER COMMON TO SEC. 35 & _____
1" IRON PIN
DESCRIBE

ADDITIONAL INFORMATION

DID NOT FIND FIR LIMB SET BY GALLOWAY IN SURVEY # 190 DATED 1916. FOUND 1" IRON PIN OF UNKNOWN ORIGIN. IRON PIN FITS 2 ROTTED STUMPS AND DISTANCES TO W 1/4 COR. AND TO CTR. 1/4 COR. COMPARE FAVORABLY TO GALLOWAY'S 1916 SURVEY; SO I USE 1" IRON PIN FOR C.W. 1/16 COR.

OVER

LEGIBLE MARKS ON BEARING OBJECTS

	FOUND 12" ROTTED FIR STUMP (NO MARKS)	FOUND 14" ROTTED FIR STUMP (NO MARKS)	FOUND 14" FIR WITH CLOSED FACE (UNKNOWN ORIGIN)	FOUND 21" FIR WITH CLOSED FACE (UNKNOWN ORIGIN)
	1916 B.T.	1916 B.T.		
KIND	FIR STUMP	FIR STUMP	FIR	FIR
SIZE	12"	14"	14"	21"
BEARING	N 3 E	N 59 E	S 39 W	N 14 W
DISTANCE	10 ²	14 ⁸	20 ⁸	7 ²
BT TAG POSTED	NO	NO	YES	YES