

**136540400**

DATE 09/21/2018TOWNSHIP 13 SOUTH, RANGE 6 WEST, WILLAMETTE MERIDIAN; SECTION 14 CORNER SOUTH 1/4  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

NORTH 1/4 CORNER SECTION 23

**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY HARVEY GORDON, D.S., AND JOSIAH W. PRESTON, D.S., DATED SEPTEMBER 7, 1854. **SET POST FROM WHICH A R. FIR 50" DIA BEARS S38°E, 19 LINKS (12.54 FEET); R. FIR 60" DIA BEARS N31°E, 98 LINKS (64.68 FEET).**
- [02] BENTON COUNTY SURVEY NO. 447 (OLD NO. 208) FIELD NOTES (FIELD BOOK 17, PAGE 24) BY BURT WILKES, D.C.S., DATED MAY 13, 1914. **REESTABLISHED FROM NORTHWEST [SIC.] TREE, CORNER UNDER LARGE LOG. SET 1-1/4" IRON PIPE. MARK FIR 10" DIA BEARS N38°40'W, 0.288 CHAINS (19.01 FEET).**
- [03] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 79, BY BURT WILKES, D.C.S., NO DATE GIVEN. **SET 1-1/4" IRON PIPE, NEARLY UNDER LARGE LOG. FIR 60" DIA (GLO BT) BEARS N31°E, 0.98 CHAINS (64.68 FEET), OTHER TREE GONE. MARK FIR 10" DIA (CSBT) BEARS N38°40'W, 0.288 CHAINS (19.01 FEET).**
- [04] BENTON COUNTY CORNER RESTORATION NO. 1881. **TRANSCRIBED FROM RECORD [03] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.**
- [05] BENTON COUNTY SURVEY NO. 1469 (OLD NO. 208) MAP BY BURT WILKES, D.C.S., DATED MAY 12-21, 1914. **1-1/4" IRON PIPE. FIR 10" DIA (CSBT) BEARS N38°40'W, 0.288 CHAINS (19.01 FEET).**
- [06] BENTON COUNTY MAP NO. 13-6-00011 BY BURT WILKES, D.C.S., DATED MAY 12-21, 1914. **1-1/4" IRON PIPE. FIR 10" DIA (CSBT) BEARS N38°40'W, 0.288 CHAINS (19.01 FEET).**
- [07] BENTON COUNTY SURVEY NO. 1417 (OLD NO. 208) FIELD NOTES (FIELD BOOK 73, PAGE 26) BY W. C. GALLOWAY, C.S., DATED FEBRUARY 13, 1939. **1-1/4" PIPE.**
- [08] BENTON COUNTY SURVEY NO. 4452 BY JOHN F. GANNON, P.L.S., DATED OCTOBER 12, 1967. **FOUND 1-1/4" PIPE.**
- [09] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY FRANK A. TUERS AND ROBERT L. AARSETH, CADASTRAL SURVEYORS, DATED SEPTEMBER 1, 1983. **THE 1/4 SECTION CORNER PERPETUATED AND RECORDED BY W. C. GALLOWAY, C.S., IN 1914, MONUMENTED WITH AN IRON PIPE, 1-1/4" DIA, FIRMLY SET, WITH TOP 4" BELOW THE SURFACE OF THE GROUND, FROM WHICH THE REMAINS OF A FIR STUMP 78" DIA (GLO BT) BEARS N31°E, 98 LINKS (64.68 FEET), WITH SCRIBE MARKS "4S" VISIBLE ON OPEN BLAZE; THE REMAINS OF A FIR STUMP 18" DIA (CSBT) BEARS N41°W, 29 LINKS (19.14 FEET), WITH SCRIBE MARKS "208 BT" VISIBLE ON OPEN BLAZE. AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 22" IN THE GROUND, DIRECTLY OVER IRON PIPE, WITH BRASS CAP MARKED "T13S R6W S14 1/4 S23 1983" FROM WHICH A FIR 8" DIA BEARS N37-1/2°E, 45 LINKS (29.70 FEET), MARKED "1/4 S14 BT"; FIR 24" DIA BEARS S61°W, 14 LINKS (9.24 FEET), MARKED "1/4 S23 BT". CORNER IS LOCATED AT INTERSECTION OF FENCES EXTENDING SOUTH, EAST AND WEST.**

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME

C.S. 208, Cont.

1 1/2" x 2 1/2" Iron rod May 1935.

1/4 sec. cor. bet. secs. 22+23. Set yew post. All evidence of original cor gone  
Set on true sec. line & equidistant from sec. cors.  
Mark yew 5" S. 7 1/2° W. 476 - fir 28" S. 53 1/2° E. 820

Cor. of secs. 22, 23+24 set fir limb, all original trees standing.  
FIR 20" N. 68° E. 2.36, FIR 59, S. 38° W. 17, FIR 60" N. 70° W. 21, FIR 50" S. 47° E. 75

1/4 sec. cor. bet. secs. 15+22 - Set yew post from which  
fir 8" S. 68° E. 41, Maple 10" N. 34° W. 16, std. fir chopped nearly down for marks.  
Mark fir 10" S. 17 1/2° W. 440 -

1/4 sec. cor. bet. secs. 11+14. Set landside of plow - 10" below surface  
Old Oak 24" - S. 41 1/2° E. <sup>Not 43° E.</sup> 7.54, other tree gone  
Mark. Oak 6" N. 64 1/2° W. 875



1/4 sec. cor. bet. secs. 14+23. Set 1 1/2" iron pipe, nearly under large log  
Orig. fir 60" N. 31° E. 98 - other tree gone  
Mark fir 10" N. 38 1/2° W. 288.

1/4 sec. cor. bet. secs. 13+14. Set 2 1/4" x 47" iron boiler tube from which  
Ash 20" S. 80° W. 23 nearly ready to cave into creek.  
Mark. fir 14" N. 89° 30' W. 488

Cor. of secs. 13, 14, 23+24, set 1" iron pipe, from which  
"fir. 40" N. 64 1/2° E. 2.28"  
"fir 4" N. 11° W. 88"  
fir 36. S. 27° W. 2.30" is 2.265  
fir 24. S. 14° E. 2.34 is 1.787 bearings O.K.

Witnesses to all cors. in survey #208 - Geo. W. Horner, W. A. Wilson,  
Wm Webster Jos. Best.

C.S. 209

Arthur Skagg's old  
11-7-1928  
May 28 to June 7  
T. 10-7

1/4 sec. cor. bet. secs. 17+18. Set stone, 16" x 10" x 8" all original trees &  
evidence obliterated. set on true sec. line & equidistant bet. sec. cors.  
Mark. fir 34" N. 4° 20' W. 302

Cor. of secs. 17, 18, 19+20. Set fir limb, in old hole, found by digging  
Mark Fir 24" N. 26 1/2° E. 3.146, Fir 20, N. 53° 50' W. 4.672, Fir 5. S. 8° E. 1.944

1/4 sec. cor. bet. secs. 19+20. Set cedar post from N.W. Ct.  
Mark. fir 24" S. 24 1/2° E. 1.158, fir 14" S. 65 1/2° W. 1.887

Cor. of secs. 7, 8, 17+18, set fir limb, <sup>from W.B.T.</sup> Mark  
Mark fir 30" N. 57° E. 1.33, fir 26" N. 89° E. 879, fir 24" S. 43° W. 864  
This cor was reestablished in C.S. #148 but was out of position & changed  
West 186 + S. 068, Notes on p. 90-33. This volume.

1/4 sec. cor. bet. secs. 17+20. Stone 6x6x12, Mark. set by F.M.W.C.S. 49  
Willow 12" S. 12° 55' W. 510, Apple 10" S. 8 1/2° E. 1.972 marked in C.S. #209  
It was to all reestablishments in C.S. #209 Arthur Skagg Austin Skagg

$\frac{1}{4}$ -Section corner between sections 14 and 23, Twp. 13-6

1881

2266

Reestablishment by W. C. Galloway

Date May 1914

Set  $1\frac{1}{2}$ " iron pipe, nearly under large log.

Fir 60" in diam bears N 31° E

.98 chains

Fir 10" in diam bears N 38° 40' W

.288 chains