

136600340

DATE 12/11/2018TOWNSHIP 13 SOUTH, RANGE 6 WEST, WILLAMETTE MERIDIAN; SECTION 23 CORNER EAST 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

WEST 1/4 CORNER SECTION 24

RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY HARVEY GORDON, D.S., AND JOSIAH W. PRESTON, D.S., DATED SEPTEMBER 7, 1854. ***SET POST FROM WHICH A R. FIR 24" DIA BEARS S15°W, 50 LINKS (33.00 FEET); A MAPLE 4" DIA BEARS S24°E, 32 LINKS (21.12 FEET).***
- [02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY FRANK A. TUERS AND ROBERT L. AARSETH, CADASTRAL SURVEYORS, DATED SEPTEMBER 1, 1983. ***THE 1/4 SECTION CORNER, MONUMENTED WITH A YEW POST, 6" DIA, FIRMLY SET, PROJECTING 4 FEET ABOVE GROUND, AT INTERSECTION OF WIRE FENCES EXTENDING NORTH AND WEST, FROM WHICH THE REMAINS OF A FIR STUMP 36" DIA (GLO BT) BEARS S15°W, 50 LINKS (33.00 FEET) NO MARKS VISIBLE. AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "T13S R6W 1/4 S23 S24 1983" FROM WHICH A FIR 9" DIA BEARS N37°E, 36-1/2 LINKS (24.09 FEET), MARKED "1/4 S24 BT"; FIR 10" DIA BEARS S59-1/2°W, 12-1/2 LINKS (8.25 FEET), MARKED "1/4 S23 BT".***
- [03] BENTON COUNTY SURVEY NO. 8848 BY NORMAN D. SPRINGER, P.L.S., DATED JUNE 16, 1994. ***FOUND 3-1/4" BLM BRASS CAP ON 2-1/2" DIA IRON PIPE, 0.2 ABOVE GROUND. CAP IS MARKED "T13S R6W 1/4 S23 S24 1983",***

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME