

136853010

DATE 04/10/2014

TOWNSHIP 13 SOUTH, RANGE 6 WEST, WILLAMETTE MERIDIAN; SECTION 13 CORNER N/A
DONATION LAND CLAIM WILLIAM W. WILKINSON NO. 53 CORNER NORTHEAST

COMMON CORNER(S):

NORTHWEST CORNER WILLIAM QUIVEY DONATION LAND CLAIM NO. 54
POINT ON SOUTH LINE OF JAMES FOSTER DONATION LAND CLAIM NO. 38

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES OF THE JAMES FOSTER DONATION LAND CLAIM NO. 38 BY DENNIS HATHORN, D.S., DATED FEBRUARY 24, 1855. **CORNER NOT DESCRIBED.**
- [02] GENERAL LAND OFFICE NOTES OF THE WILLIAM W. WILKINSON DONATION LAND CLAIM NO. 53 BY DENNIS HATHORN, D.S., DATED APRIL 4, 1855. **SET POST FROM WHICH AN ASH 12" DIA BEARS S22°E, 288 LINKS (190.08 FEET); AN ASH 10" DIA BEARS S2°W, 241 LINKS (159.06 FEET).**
- [03] BENTON COUNTY SURVEY FOR ROAD NO. 380 FIELD NOTES (FIELD BOOK 21, PAGE 70) BY W. C. GALLOWAY, C.S., NO DATE GIVEN. **STONE 10" X 12" X 24". FIR 12" DIA BEARS N65°30'W, 1.180 CHAINS (77.88 FEET); FIR 2" DIA BEARS N25°45'E, 0.176 CHAINS (11.62 FEET). STAKE BEARS NORTH, 0.12 CHAINS (7.92 FEET) AND SOUTH, 0.18 CHAINS (11.88 FEET).**
- [04] BENTON COUNTY CORNER RESTORATION BOOK NO. 1, PAGE 110 BY W. C. GALLOWAY, C.S., DATED AUGUST 11, 1916. **STONE 10" X 12" X 24" LYING NEARLY FLAT. SET IT UP ON END AND MARKED. MARKED FIR 12" DIA (CSBT) BEARS N65°30'W, 1.180 CHAINS (77.88 FEET); MARKED FIR 2" DIA (CSBT) BEARS N25°45'E, 0.176 CHAINS (11.62 FEET).**
- [05] BENTON COUNTY CORNER RESTORATION NO. 2005. **TRANSCRIBED FROM RECORD [04] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.**
- [06] BENTON COUNTY SURVEY NO. 561 (OLD NO. 208) FIELD NOTES (FIELD BOOK 19, PAGE 39) BY BURT WILKES, D.C.S., DATED AUGUST 16, 1916. **CORNER NOT DESCRIBED.**
- [07] BENTON COUNTY SURVEY NO. 951 (OLD NO. 208) MAP BY BURT WILKES, D.C.S., DATED AUGUST 18, 1916. **STONE.**
- [08] BENTON COUNTY MAP NO. 13-6-00009 BY BURT WILKES, D.C.S., DATED AUGUST 18, 1916. **STONE.**
- [09] BENTON COUNTY MAP NO. 13-6-00006 BY W. C. GALLOWAY, C.S., DATED MAY 26, 1917. **STONE 10" X 12" X 24". FIR 12" DIA (CSBT) BEARS N65°30'W, 1.180 CHAINS (77.88 FEET); FIR 2" DIA (CSBT) BEARS N25°45'E, 0.176 CHAINS (11.62 FEET).**
- [10] BENTON COUNTY SURVEY NO. 1490 (OLD NO. 256) FIELD NOTES (FIELD BOOK 73, PAGE 54) BY BURT WILKES, D.C.S., DATED AUGUST 24, 1940. **STONE.**
- [11] BENTON COUNTY MAP NO. 13-6-00008 BY BURT WILKES, D.C.S., DATED AUGUST 1940. **STONE. FIR 12" DIA (CSBT) BEARS N65-1/2°W, 1.18 CHAINS (77.88 FEET).**
- [12] BENTON COUNTY SURVEY NO. 6280 BY JIM S. PETERSON, P.L.S., DATED MARCH 1977. **FOUND STONE.**
- [13] BENTON COUNTY SURVEY NO. 7565 BY NICK A. YINGER, P.L.S., DATED APRIL 1977. **FOUND STONE.**
- [14] BENTON COUNTY SURVEY NO. 7433 BY JIM S. PETERSON, P.L.S., DATED AUGUST 5, 1982. **FOUND 10" X 12" X 24" STONE. FIR 30" DIA (CSBT) BEARS N65°30'W, 1.180 CHAINS (77.88 FEET), HEALED FACE.**
- [15] BENTON COUNTY CORNER RESTORATION NO. 3062. **TRANSCRIBED FROM RECORD [14] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.**
- [16] BENTON COUNTY SURVEY NO. 7583 BY GARY T. JOHNSTON, P.L.S., DATED NOVEMBER 15, 1983. **FOUND 9" X 9" STONE.**

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME

CORNER RESTORATION BOOK NO. 1

C.S. 93
Notes on "382
Road #

C.S.

S.E. corner of D.D. Strouds D.L.C. # 44 T. 11 S. R. 4 W. iron. nail splice set.
Oak 18" in dia. bears S. 88° W. .20 chs. std.
Walnut 3" " N. 10° 40' W. .515 " not marked
To near rail on main line .364 "
Witness Walter E. Wood July 25, 1916.

N.E. corner of W.M. Taylor D.L.C. # 46 T. 11 S. R. 4 W.

Gun bbl under a stone 12" x 10" x 6" lying flat with hole $\frac{1}{2}$ deep in center. Set.
West corner of concrete N. 9° 20' W. 1.159 chs.
Walnut 1" in dia. bears N. 51° 08' E. .835 chs. not marked.
Oak 18" " " S. 2° W. .205 "
Witness W. E. Wood. July 25 1916.

C.S. Road # 380
Connected with
C.S. # 208
Witnesses
R. L. Jones & Oliver
Rogers

S.E. corner of W.M. W. Wilkerson D.L.C. # 53 T. 13 S. R. 6 W.
Set a Qt. bottle orig. cap.
Fir 14" in dia. bears N. 43° E. .12 chs. std.
Oak " 22" " S. 24° E. .607 "

Aug. 10, 1916.

S.W. corner of W.M. W. Wilkerson D.L.C. # 53 T. 13 S. R. 6 W.

Set 1" pipe
Oak 20" in dia. bears N. 4° 30' E. .663 chs. std.
" 12" " " N. 24° 30' E. .618 "
" Fir 25" " " S. 82° E. .723 "

Aug. 11, 1916.

S.E. cor. of W.M. Bennett C. # 50 T. 13 S. R. 6 W.

Set a 1" pipe S.E. oak down yew stake found standing.
Fir 18" in dia. bears S. 89° E. .173 chs. std.
" 14" " " S. 35° 30' W. .305 "

Aug. 11, 1916.

N.W. of W.M. Quivey D.L.C. # 54 T. 13 S. R. 6 W.

Stone 10" x 12" x 24" lying nearly flat. Set it up on end & mld.
Marked fir 2" in dia. bears N. 25° 45' E. .176 chs.
" 12" " " N. 65° 30' W. .1180 "

Aug. 11, 1916.

C.S. # 253 Most West S.W. cor. of James Greer D.L.C. # 50 T. 10 S. R. 6 W.

Stone 10" x 10" x 24" Orig. stone with figures on
Oak 7" in dia. bears N. 84° 40' E. .848 chs.
" 10" " " S. 7° 20' E. .217 "

Witnesses H.T. Walters, Elmer Maxfield, C.E. Rice. Sept. 12, 1916.

" N.E. corner of Samuel Rice D.L.C. # 45 T. 10 S. R. 6 W.

Orig. Stone with figures on C. 40" x 15" x 6" oak down. stamp.
Marked Oak 10" in dia. bears S. 48° 15' E. 3.718 chs.
" 12" " " N. 89° 50' W. 3.293 "
Witnesses as above and Bruce Miller. Sept. 12, 1916.

C.S. # 253
Continued on
See Page 114



2005

N. W. of William Oulvey DLC 54, Twp. 13 S., R. 6 W.

Reestablishment by W. C. Galloway

August 11, 1916

Stone 10" x 12" x 24" lying nearly flat. Set it up on end and marked.

Fir 2" in diam bears N 25° 45' E .176 chains

Fir 12" in diam bears N 65° 30' W 1.180 chains

Witnesses R. L. Jones and Oliver Rogers

BENTON COUNTY SURVEYORS OFFICE - CORNER RESTORATION

03062

T. 13 S, R. 6 W, W. B. & M., BENTON COUNTY, OREGON


REPORTED BY JIM PETERSON

DLC
SECTION 53

TITLE L.S. 1084

The information shown hereon was taken from CPL
the referenced county survey. Date: 7/31/95

DATE 8-5-1982



● OFFICIAL CORNER FOUND

○ CORNER SET

ENE CORNER COMMON TO SEC. DLC 53, NW DLC 54
IS STONE 10" X 12" X 24"
DESCRIBE

ADDITIONAL INFORMATION

SEE C.S. 7433

LEGIBLE MARKS ON BEARING OBJECTS

HEALED FACE			
FOUND			
KIND FIR			
SIZE 30"			
BEARING (N65°30'W.)			
DISTANCE (1.180 ch.)			
BT TAG POSTED			

OVER