

137100700

DATE 11/18/2020TOWNSHIP 13 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 6 CORNER NORTHWEST
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

NORTHEAST CORNER SECTION 1, TOWNSHIP 13 SOUTH, RANGE 8 WEST

RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ROBERT O. COLLIER, D.S., DATED SEPTEMBER 25, 1891. SET A POST 4-1/2 FEET LONG, 4" SQUARE, 24" IN GROUND, MARKED "CC T13S" ON SOUTH FACE, "R7WS6" ON EAST FACE AND "R8WS1" ON WEST FACE, WITH 6 NOTCHES ON SOUTHEAST AND SOUTHWEST FACES, FROM WHICH A FIR 40" DIA BEARS S78°E, 109 LINKS (71.94 FEET), MARKED "T13SR7WS6BT"; FIR 40" DIA BEARS S65°W, 28 LINKS (18.48 FEET), MARKED "T13SR8WS1BT"; FIR 48" DIA BEARS N9°W, 240 LINKS (158.40 FEET), MARKED "T13SR7+8WCCBT".
- [02] GENERAL LAND OFFICE (GLO) NOTES BY EDWARD F. SHARP, D.S., DATED SEPTEMBER 25, 1897. A POST 2 FEET ABOVE GROUND, 4" SQUARE, MARKED AND WITNESSED AS DESCRIBED BY THE SURVEYOR GENERAL.
- [03] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY JOSEPH S. GAWRON, CADASTRAL SURVEYOR, DATED NOVEMBER 16, 1960. INTERSECT SOUTH BOUNDARY SECTION 36, TOWNSHIP 12 SOUTH, RANGE 8 WEST, AND POINT FOR THE CLOSING CORNER OF TOWNSHIPS 13 SOUTH, RANGES 7 AND 8 WEST. SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "T12S R8W S36 S1 S6 R8W R7W CC T13S 1960" FROM WHICH A FIR 27" DIA BEARS S64°E, 32 LINKS (21.12 FEET), MARKED "T13S R7W S6 CC BT"; FIR 16" DIA BEARS S77°W, 21 LINKS (13.86 FEET), MARKED "T13S R8W S1 CC BT". FROM THIS POINT THE ORIGINAL CLOSING CORNER OF TOWNSHIPS 13 SOUTH, RANGES 7 AND 8 WEST, BEARS N1°54'E, 0.37 CHAINS (24.42 FEET), PERPETUATED WITH A FIR POLE, 6 FEET LONG, 10" DIA, FIRMLY SET, AT RECORD BEARING AND DISTANCE FROM THE REMAINS OF A FIR STUMP 40" DIA (GLO BT) BEARS S65°W, 28 LINKS (18.48 FEET); FIR 60" DIA (GLO BT) BEARS N9°W, 240 LINKS (158.40 FEET), MARKED "T13S R7 AND 8W CC BT". MARK "AM" ON EACH ACCESSORY.
- [04] LINCOLN COUNTY SURVEY NO. 6366 BY GARY T. JOHNSTON, P.E., DATED SEPTEMBER, 1975. FOUND BRASS CAP.
- [05] BENTON COUNTY SURVEY NO. 7796 BY THEODORE JAMES LANGTON, P.L.S., DATED SEPTEMBER 10, 1985. FOUND 3" BLM BRASS CAP MARKED "T12S R8W S36 S1 S6 CC T13S R8W R7W 1960" ON 2-1/4" OUTSIDE DIAMETER PIPE. FOUND D. FIR 19" DIA (BLM BT) BEARS S78-1/2°W, 14.0 FEET, HEALED FACE; D. FIR 32" DIA (BLM BT) BEARS S64-1/2°E, 19.8 FEET, HEALED FACE.
- [06] BENTON COUNTY SURVEY NO. 9745 BY JIM S. PETERSON, P.L.S., DATED JULY 19, 2002. FOUND 3-1/4" BLM BRASS CAP (1960). FOUND FIR 24" DIA (BLM BT) BEARS S77°W, 21 LINKS (13.86 FEET), HEALED FACE; FIR 36" DIA (BLM BT) BEARS S64°E, 32 LINKS (21.12 FEET), HEALED FACE.
- [07] LINCOLN COUNTY CORNER REPORT FILED AS LINCOLN COUNTY SURVEY NO. 18303 BY THOMAS R. HAMILTON, C.S., DATED 2007. FOUND 2-1/2" GALVANIZED IRON PIPE 0.8 FEET ABOVE GRADE WITH 3-1/4" BLM BRASS CAP MARKED "T12S R8W S36 S1 S6 CC T13S R8W R7W 1960", FROM WHICH PARTLY ROTTEN REMAINS OF SOUTHWEST 1/2 OF 5 FOOT TALL BURNED FIR STUMP 30" DIA (GLO BT) BEARS N47°W, 21.7 FEET, NO MARKS; 7 FOOT TALL FIR STUMP 60" DIA (GLO BT) BEARS N7-1/2°W, 182.4 FEET, WITH PARTLY LEGIBLE SCRIBING "R8W" ON LOOSE PIECE OF WOOD AGAINST SOUTH SIDE, STUMP HAS CHOP MARKS AND OVERGROWTH SCAR ON SOUTH FACE; FIR 36" DIA (BLM BT) WITH HEALED BLAZE BEARS S67°E, 21.1 FEET; FIR 24" DIA (BLM BT) WITH HEALED BLAZE FACING S85°E, BEARS S80°W, 13.9 FEET. 80D SPIKE IN 3 FOOT TALL FIR STUMP 5' DIA BEARS N87°22'51"E, 160.91 FEET; 2-1/2" GALVANIZED IRON PIPE 0.5 FEET ABOVE GRADE WITH 3-1/4" BLM BRASS CAP MARKED "T12S R8W R7W S36 S31 1960" BEARS S89°41'15"E, 285.73 FEET; 5/8" X 30" IRON ROD WITH 2" LINCOLN COUNTY ALUMINUM CAP MARKED "47AZ 2007" BEARS N20°25'32"W, 1911.72 FEET; CARSONITE POST 2 FEET NORTH.
- [08] LINCOLN COUNTY GEODETIC CONTROL FILED AS LINCOLN COUNTY SURVEY NO. 18325 BY THOMAS R. HAMILTON, C.S., DATED DECEMBER 12, 2007. 3-1/2" BLM BRASS CAP STAMPED "T12S R8W S36 S1 S6 CC T13S R8W R7W 1960" ON 2-1/2" X 30" GALVANIZED IRON PIPE.
- [09] LINCOLN COUNTY GEODETIC CONTROL FILED AS LINCOLN COUNTY SURVEY NO. 19436 BY EATHAN D. NICLEY, D.C.S., DATED OCTOBER 24, 2007. 3-1/2" BLM BRASS CAP STAMPED "T12S R8W S36 S1 S6 CC T13S R8W R7W 1960" ON 2-1/2" X 30" GALVANIZED IRON PIPE.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME