

137200240

DATE 04/08/2004TOWNSHIP 13 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 29 CORNER WEST 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

EAST 1/4 CORNER OF SECTION 30

RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY DENNIS HATHORN, D.S., DATED SEPTEMBER 5, 1856. *SET POST FROM WHICH A FIR 40" DIA BEARS N60°E, 60 LINKS (39.60 FEET); FIR 6" DIA BEARS N75°W, 23 LINKS (15.18 FEET).*
- [02] BENTON COUNTY SURVEY NO. 6123 BY FRED I. LEMKE, P.L.S., DATED JUNE 1, 1976. *FOUND 1" AXLE.*
- [03] BENTON COUNTY SURVEY NO. 6123A BY FRED I. LEMKE, P.L.S., DATED AUGUST 23, 1976. *FOUND 1" AXLE FROM WHICH A FIR STUMP 45" DIA (GLO BT) BEARS N60°E, 39.6 FEET; FIR BLOWDOWN 20" DIA (GLO BT) BEARS N75°W, 15.2 FEET. SCRIBED FIR 13" DIA BEARS N18°01'E, 7.2 FEET; FIR 7" DIA BEARS S42°11'W, 34.6 FEET.*
- [04] BENTON COUNTY SURVEY NO. 7044 BY RAYMOND C. MCWHINNEY, P.L.S., DATED FEBRUARY 9, 1980. *FOUND 1" AXLE. FOUND A FIR STUMP 45" DIA (GLO BT) BEARS N60°E, 39.6 FEET; FIR BLOWDOWN 20" DIA (GLO BT) BEARS N75°W, 15.2 FEET; FIR 13" DIA BEARS N18°01'E, 7.2 FEET; FIR 7" DIA BEARS S42°11'W, 34.6 FEET.*
- [05] BENTON COUNTY SURVEY NO. 7284 BY JACK R. BURRELL, P.L.S., DATED JUNE 16, 1981. *FOUND 1" AXLE. FIR STUMP 45" DIA (GLO BT) BEARS N60°E, 39.6 FEET; FIR (BLOWN OVER) 20" DIA (GLO BT) BEARS N75°W, 15.2 FEET; FIR 13" DIA BEARS N18°01'E, 7.2 FEET; FIR 7" DIA BEARS S42°11'W, 34.6 FEET.*
- [06] BENTON COUNTY CORNER RESTORATION NO. 2084 BY JACK R. BURRELL, P.L.S., DATED JUNE 23, 1981. *FOUND 1" AXLE. FIR STUMP 45" DIA (GLO BT) BEARS N60°E, 39.6 FEET; FIR (BLOWN OVER) 20" DIA (GLO BT) BEARS N75°W, 15.2 FEET; FIR 13" DIA BEARS N18°01'E, 7.2 FEET; FIR 7" DIA BEARS S42°11'W, 34.6 FEET.*
- [07] BENTON COUNTY SURVEY NO. 7310 BY JACK R. BURRELL, P.L.S., DATED JULY 23, 1981. *FOUND 1" AXLE. FIR STUMP 45" DIA (GLO BT) BEARS N60°E, 39.6 FEET; FIR (BLOWN OVER) 20" DIA (GLO BT) BEARS N75°W, 15.2 FEET; FIR 13" DIA BEARS N18°01'E, 7.2 FEET; FIR 7" DIA BEARS S42°11'W, 34.6 FEET.*
- [08] BENTON COUNTY SURVEY NO. 8722 BY RONALD H. SCHULSON, P.L.S., DATED MAY 28, 1993. *FOUND 1" IRON SHAFT. FIR 13" DIA BEARS N18°01'E, 7.2 FEET, CLOSED FACE; FIR 7" DIA BEARS S42°11'W, 34.6 FEET, CLOSED FACE.*
- [09] BENTON COUNTY SURVEY NO. 9878 BY JIM S. PETERSON, P.L.S., DATED JUNE 10, 1996. *FOUND 1" AXLE. FOUND FIR 20" DIA BEARS N18°E, 7.2 FEET, HEALED FACE; FIR DOWN 30" DIA (GLO BT) BEARS N75°W, 15.2 FEET, NO MARKS; FIR STUMP 44" DIA (GLO BT) BEARS N60°E, 39.6 FEET, SCRIBING VISIBLE; FIR DOWN 8" DIA BEARS S42°W, 34.6 FEET, HEALED FACE. CORNER LIES ON NORTHWEST SIDE OF OLD ROAD, ON SOUTHEAST SLOPE, 100 FEET NORTH OF CREEK.*
- [10] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY ROBERT L. AARSETH, CADASTRAL SURVEYOR, AND JANET R. MYERS, CADASTRAL SURVEYOR, DATED APRIL 4, 2005. *CORNER MONUMENTED WITH AN AXLE, 1" DIA, FIRMLY SET, PROJECTING 6" ABOVE GROUND, FROM WHICH A FIR STUMP 40" DIA (GLO BT) BEARS N60°E, 39.6 FEET, WITH SCRIBE MARKS "1/ S BT" VISIBLE ON OPENED DOUBLE BLAZE; FIR STUMP UPROOT 20" DIA (GLO BT) BEARS N75°W, 15.2 FEET, WITH NO MARKS VISIBLE; FIR 19" DIA BEARS N17-1/2°E, 7.4 FEET, WITH A HEALED DOUBLE BLAZE; FIR STUMP 12" DIA BEARS S42°W, 34.6 FEET, WITH NO MARKS VISIBLE. AT THE CORNER POINT SET A STAINLESS STEEL POST, 28" LONG, 2-1/2" DIA, 22" IN THE GROUND, DIRECTLY OVER AXLE, WITH BRASS CAP MARKED "T13S R7W 1/4 S30 S29 2000" FROM WHICH A FIR 15" DIA BEARS S16°W, 10.4 FEET TO A 2-1/2" X 1/4" MAGNETIC NAIL (MAG NAIL) DRIVEN AT THE BASE ON RIGHT SIDE CENTER, MARKED "1/4 S30 BT".*

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: BERNARD S. ALTENBACH, ENGINEER/SURVEY TECH.
DATA ENTRY BY: BSA

13-7-29

BENTON COUNTY SURVEYORS OFFICE - CORNER RESTORATION

2084


T 13 S, R 7 W, W. B. & M., BENTON COUNTY, OREGON

SECTION 29

REPORTED BY Jack Burrell

TITLE ORS 1630

DATE June 23, 1981



- OFFICIAL CORNER FOUND
- CORNER SET

W¹/₄ CORNER COMMON TO SEC. 29, 30, X & X
 IS 1" Axle
 DESCRIBE

ADDITIONAL INFORMATION

Refer to C.S. 7284

OVER

LEGIBLE MARKS ON BEARING OBJECTS

KIND	<u>Fir (Stump)</u>	<u>Fir (Blown over)</u>	<u>Fir</u>
SIZE	<u>45"</u>	<u>20"</u>	<u>13"</u>
BEARING	<u>N 60° E</u>	<u>N 75° W</u>	<u>N 18° 01' E</u>
DISTANCE	<u>39.6</u>	<u>15.2</u>	<u>7.2</u>
BT TAG POSTED	<u>No</u>	<u>?</u>	<u>No.</u>
			<u>542° 11' W</u>
			<u>34.6</u>
			<u>No.</u>
			<u>No.</u>