

**137200540**

DATE 08/03/2020TOWNSHIP 13 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 7 CORNER EAST 1/4  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

WEST 1/4 CORNER SECTION 8

**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ROBERT O. COLLIER, D.S., DATED FEBRUARY 9, 1892. *SET A POST 3 FEET LONG, 3" SQUARE, 24" IN THE GROUND, MARKED "1/4S" ON WEST FACE, FROM WHICH A FIR 40" DIA BEARS S75°W, 44 LINKS (29.04 FEET), MARKED "1/4S BT"; HEMLOCK 20" DIA BEARS S54°E, 42 LINKS (27.72 FEET), MARKED "1/4S BT". A FIR LINE TREE 40" DIA BEARS S0°04'E, 4.25 CHAINS (280.50 FEET), WITH 2 NOTCHES ON NORTH AND SOUTH SIDES.*
- [02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY ROBERT L. AARSETH AND JANET R. MYERS, CADASTRAL SURVEYORS, DATED APRIL 4, 2005. *THE 1/4 SECTION CORNER DETERMINED AT RECORD BEARING AND DISTANCE FROM THE REMAINS OF AN ORIGINAL BEARING TREE, A FIR SNAG 44" DIA (GLO BT) BEARS S75°W, 29.0 FEET, WITH SCRIBE MARKS "1/4 BT" VISIBLE ON OPENED BLAZE. AT THE CORNER POINT SET A STAINLESS STEEL POST, 28" LONG, 2-1/2" DIA, 20" IN THE GROUND, AND IN A COLLAR OF STONE, WITH BRASS CAP MARKED "T13S R7W 1/4 S7 S8 2000" FROM WHICH A FIR 18" DIA BEARS N19°E, 23.9 FEET TO A 2-1/2" X 1/4" MAGNETIC NAIL (MAG NAIL) DRIVEN AT THE BASE ON RIGHT SIDE CENTER, MARKED "1/4 S8 BT"; FIR 22" DIA BEARS S64°W, 26.8 FEET TO A MAG NAIL DRIVEN AT THE BASE ON RIGHT SIDE CENTER, MARKED "1/4 S7 BT". DEPOSIT A MAGNET IN A WHITE PLASTIC CASE AT THE BASE OF THE STAINLESS STEEL POST.*

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME