

137300500

DATE 08/06/2020TOWNSHIP 13 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 8 CORNER SOUTHEAST
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHWEST CORNER SECTION 9
NORTHWEST CORNER SECTION 16
NORTHEAST CORNER SECTION 17**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ROBERT O. COLLIER, D.S., DATED FEBRUARY 9, 1892. SET A POST 4 FEET LONG, 4" SQUARE, 24" IN GROUND, MARKED "T13SS9" ON NORTHEAST FACE, "R7WS16" ON SOUTHEAST FACE, "S17" ON SOUTHWEST FACE, AND "S8" ON NORTHWEST FACE WITH 4 NOTCHES ON SOUTH AND EAST EDGE, FROM WHICH A FIR 18" DIA BEARS N16°E, 106 LINKS (69.96 FEET), MARKED "T13SR7WS9BT"; FIR 30" DIA BEARS S34°E, 47 LINKS (31.02 FEET), MARKED "T13SR7WS16BT"; YEW 15" DIA BEARS S76°W, 28 LINKS (18.48 FEET), MARKED "T13SR7WS17BT"; YEW 15" DIA BEARS N4-1/4°W, 70 LINKS (46.20 FEET), MARKED "T13SR7WS8BT".
- [02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY DANNY J. NEVIN, CADASTRAL SURVEYOR, DATED SEPTEMBER 30, 1998. THE SECTION CORNER DETERMINED AT RECORD BEARING AND DISTANCE FROM A FIR 42" DIA (GLO BT) BEARS S34°E, 47 LINKS (31.02 FEET), WITH SCRIBE MARKS "T S 7W S" AND OTHER ILLEGIBLE SCRIBE MARKS VISIBLE ON OPENED BLAZE. AT THE CORNER POINT SET A STAINLESS STEEL POST, 28" LONG, 2-1/2" DIA, 22" IN THE GROUND, WITH BRASS CAP MARKED "T13S R7W S8 S9 S17 S16 1998" FROM WHICH A FIR 8" DIA BEARS N5-3/4°E, 16 LINKS (10.56 FEET), MARKED "T13S R7W S9 BT"; FIR 13" DIA BEARS S61-3/4°W, 34 LINKS (22.44 FEET), MARKED "T13S R7W S17 BT"; FIR 8" DIA BEARS N48-3/4°W, 45-1/2 LINKS (30.03 FEET), MARKED "T13S R7W S8 BT". DEPOSIT A MAGNET IN A WHITE PLASTIC CASE AT THE BASE OF THE STAINLESS STEEL POST.
- [03] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY ROBERT L. AARSETH AND JANET R. MYERS, CADASTRAL SURVEYORS, DATED APRIL 4, 2005. SECTION CORNER MONUMENTED WITH A STAINLESS STEEL POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 6" ABOVE GROUND, WITH BRASS CAP MARKED "T13S R7W S8 S9 S17 S16 1998" FROM WHICH A FIR 49" DIA (GLO BT) BEARS S34°E, 31.0 FEET, WITH SCRIBE MARKS "T S 7W S" AND OTHER ILLEGIBLE SCRIBE MARKS VISIBLE ON OPEN BLAZE; FIR 10" DIA (BLM BT) BEARS N5-3/4°E, 10.6 FEET, WITH SCRIBE MARKS "T13S R7W S9 BT" VISIBLE ON OPEN BLAZE; FIR 13" DIA BEARS S61-3/4°W, 22.4 FEET, WITH SCRIBE MARKS "T13S R7W S17 BT" VISIBLE ON OPEN BLAZE; FIR 8" DIA BEARS N48-3/4°W, 30.0 FEET, WITH SCRIBE MARKS "T13S R7W S8 BT" VISIBLE ON OPEN BLAZE.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME