

137400600

DATE 08/04/2020TOWNSHIP 13 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 3 CORNER SOUTHWEST
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHEAST CORNER SECTION 4
NORTHEAST CORNER SECTION 9
NORTHWEST CORNER SECTION 10**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ROBERT O. COLLIER, D.S., DATED FEBRUARY 9, 1892. *SET A STONE 18" X 12" X 8", 12" IN THE GROUND, MARKED WITH 5 NOTCHES ON SOUTH EDGE AND 3 NOTCHES ON EAST EDGE, FROM WHICH A CEDAR 12" DIA BEARS N30°E, 245 LINKS (161.70 FEET), MARKED "T13SR7WS3BT"; CEDAR 35" DIA BEARS S44°E, 129 LINKS (85.14 FEET), MARKED "T13SR7WS10BT"; FIR 48" DIA BEARS N75°W, 109 LINKS (71.94 FEET), MARKED "T13SR7WS4BT"; NO TREE IN LIMITS IN SECTION 9 SO DUG A PIT 18" X 18" X 12", 5-1/2 FEET DISTANCE.*
- [02] BENTON COUNTY SURVEY NO. 6923 BY GARY T. JOHNSTON, P.L.S., DATED JUNE, 1979. *FOUND FIR SNAG (GLO BT). CHOPPED OPEN, NO SCRIBES VISIBLE. FOUND 8" X 10" X 15" STONE, CORRECT BEARING AND DISTANCE FROM SNAG. FOUND DOWNED CEDAR (GLO BT) SOUTHEAST, NO SCRIBES VISIBLE. NORTHEAST CEDAR NOT FOUND, GROUND SLID AWAY INTO CREEK. ORIGINAL AND MEASURED TOPOGRAPHIC CALLS FROM CORNER: CREEK 3.5 CHAINS (231.0 FEET) EAST, RECORD - 230.0 MEASURED; YEW CREEK 24.9 CHAINS (1643.4 FEET) SOUTH, RECORD - 1650.0 MEASURED; NW/SE RIDGE 9.5 CHAINS (627.0 FEET) WEST, RECORD - 555.0 MEASURED; CREEK 18.45 CHAINS (1217.0 FEET) NORTH, RECORD - 650.0 MEASURED. REMONUMENTED WITH 5/8" X 30" IRON ROD. D. FIR 28" DIA BEARS S19°W, 75.7 FEET, MARKED "T13SR7WS9BT"; D. FIR 26" DIA BEARS S82°E, 30.5 FEET, MARKED "T13SR7WS10BT"; D. FIR 26" DIA BEARS N43°E, 15.9 FEET, MARKED "T13SR7WS3BT"; CEDAR 10" DIA BEARS N30°W, 40.0 FEET, MARKED "T13SR7WS4BT".*
- [03] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY ROBERT L. AARSETH AND JANET R. MYERS, CADASTRAL SURVEYORS, DATED APRIL 4, 2005. *THE CORNER MONUMENTED WITH AN IRON ROD, 5/8" DIA, FIRMLY SET, PROJECTING 4" ABOVE GROUND, (ALONGSIDE OF WHICH IS A BASALT STONE, 18" X 12" X 8", WITH NO VISIBLE MARKS), FROM WHICH A DOWN CEDAR (GLO BT), SIZE INDETERMINATE, BEARS S53-1/2°E, 85.1 FEET, WITH NO MARKS VISIBLE ON OPEN BLAZE; FIR SNAG (GLO BT), SIZE INDETERMINATE, BEARS N75°W, 71.9 FEET, WITH AXE MARKS VISIBLE; FIR 30" DIA BEARS N48-1/2°E, 15.9 FEET, WITH A HEALED BLAZE; FIR 34" DIA BEARS S79°E, 30.5 FEET, WITH A HEALED BLAZE; FIR 35" DIA BEARS S17-1/2°W, 75.7 FEET, WITH A HEALED BLAZE; CEDAR STUMP 10" DIA BEARS N28°W, 40.0 FEET, WITH SCRIBE MARKS "T13" AND OTHER ILLEGIBLE MARKS VISIBLE ON OPEN BLAZE. AT THE CORNER POINT SET A STAINLESS STEEL POST, 28" LONG, 2-1/2" DIA, 22" IN THE GROUND, DIRECTLY OVER IRON ROD, WITH BRASS CAP MARKED "T13S R7W S4 S3 S9 S10 2000" FROM WHICH A CEDAR 7" DIA BEARS N46°W, 46.8 FEET TO A 2-1/2" X 1/4" MAGNETIC NAIL (MAG NAIL) DRIVEN AT THE BASE ON RIGHT SIDE CENTER, MARKED "T13S R7W S4 BT". DEPOSIT THE BASALT STONE ALONGSIDE THE STAINLESS STEEL POST.*

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME