

137540500

DATE 09/09/2016TOWNSHIP 13 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 11 CORNER SOUTH 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

NORTH 1/4 CORNER SECTION 14

RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ROBERT O. COLLIER, D.S., DATED FEBRUARY 9, 1892. *SET A POST 4 FEET LONG, 3 INCHES SQUARE, 24 INCHES IN GROUND MARKED "1/4S" ON NORTH FACE FROM WHICH A HEMLOCK 8" DIA BEARS S27°E, 52 LINKS (34.32 FEET) MARKED "1/4S BT"; A HEMLOCK 6" DIA BEARS N74°W, 15 LINKS (9.90 FEET) MARKED "1/4S BT".*
- [02] BENTON COUNTY SURVEY NO. 6038 BY ARNOLD BRUBAKER, P.L.S., DATED FEBRUARY 27, 1976. *FOUND NO EVIDENCE OF ORIGINAL BEARING TREES IN LOGGED OFF WINDFALL PATCH. SET 5/8" ROD FOR 1/4 CORNER BY PROPORTION. FOUND SQUARED STAKE/TAG AND TWO HEMLOCK TREES BLAZED, BUT NOT SCRIBED, ABOUT 20 YEARS AGO. SAID STAKE BEARS S57°W, 107 FEET. MARKED HEMLOCK 10" DIA BEARS N82°E, 28.75 FEET; HEMLOCK 12" DIA BEARS S2°E, 36.95 FEET.*
- [03] BENTON COUNTY CORNER RESTORATION NO. 2035. *TRANSCRIBED FROM RECORD [02] AND MAY CONTAIN ERRORS AND/OR OMISSIONS.*
- [04] BENTON COUNTY SURVEY NO. 8602 BY JIM S. PETERSON, P.L.S., DATED NOVEMBER, 1991. *FOUND 5/8" IRON ROD.*
- [05] BENTON COUNTY SURVEY NO. 9867 BY JIM S. PETERSON, P.L.S., DATED NOVEMBER, 1991. *FOUND 5/8" IRON ROD.*
- [06] BENTON COUNTY SURVEY NO. 9884 BY JIM S. PETERSON, P.L.S., DATED JUNE 9, 1997. *FOUND 5/8" IRON ROD. FOUND HEMLOCK 18" DIA BEARS N82°E, 28.75 FEET, SCRIBING VISIBLE; HEMLOCK 18" DIA BEARS S2°E, 36.95 FEET, HEALED FACE.*
- [07] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY RICHARD S. KAISER, CADASTRAL SURVEYOR, DATED JULY 16, 2009. *THE 1/4 SECTION CORNER REESTABLISHED BY PROPORTIONATE MEASUREMENT BY BRUBAKER IN 1976. THERE IS NO REMAINING EVIDENCE OF THE ORIGINAL CORNER, THEREFORE THIS POINT IS ACCEPTED AS THE CORNER, MONUMENTED WITH AN IRON ROD, 5/8" DIA, FIRMLY SET, PROJECTING 2" ABOVE GROUND, FROM WHICH A DOWNED HEMLOCK 19" DIA BEARS N80°E, 29.8 FEET, WITH HEALED BLAZE; A DOWNED HEMLOCK 18" DIA BEARS S2°E, 35.2 FEET, WITH HEALED BLAZE. AT THE CORNER POINT SET A STAINLESS STEEL POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, DIRECTLY OVER IRON ROD, WITH BRASS CAP MARKED "T13S R7W S11 1/4 S14 2009" FROM WHICH A HEMLOCK 16" DIA BEARS N50-3/4°E, 25.2 FEET TO A 2-1/2" X 1/4" MAGNETIC NAIL (MAG NAIL) DRIVEN AT THE BASE ON RIGHT SIDE CENTER, MARKED "1/4 S11 BT"; A HEMLOCK 7" DIA BEARS S7-1/2°W, 17.9 FEET TO A MAG NAIL DRIVEN AT THE BASE ON RIGHT SIDE CENTER, MARKED "X" AT BREAST HEIGHT AND "BT" AT BASE. SET A FIBERGLASS FENCEPOST ALONGSIDE THE STAINLESS STEEL POST.*

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME

BENTON COUNTY SURVEYORS OFFICE - CORNER RESTORATION

2035

T 13 S, R 7 W, W. B. & M., BENTON COUNTY, OREGON


REPORTED BY Arnold Brubaker

SECTION 11

The information shown hereon was taken from
the referenced county survey. Date: 7/26/90
No. 6038

TITLE Surveyor 992

DATE Feb. 27 - 1976



● OFFICIAL CORNER FOUND

○ CORNER SET

1/4 CORNER COMMON TO SEC. 14 & 11
IS 5/8" iron rod
DESCRIBE

ADDITIONAL INFORMATION

Ed. sqd stake/Tag and two
Hemlock Trees Blazed but not
scribed, about 20 years ago.
Said stake bears S57°W 907ft.

LEGIBLE MARKS ON BEARING OBJECTS

KIND	<u>Hem</u>	<u>Hem</u>	
SIZE	<u>10"</u>	<u>12"</u>	
BEARING	<u>N82°E</u>	<u>S2°E</u>	
DISTANCE	<u>28.75'</u>	<u>36.95'</u>	
BT TAG POSTED			

OVER