

R. AARSETH / J. MYERS

2000

s 117

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 S., R. 7 W., Willamette Meridian, Oregon

FEET	
	Ascend over SE. slope, through heavy timber and dense undergrowth.
725	Top of ascent, slopes W.; desc. over NW. slope.
965	Bottom of descent, slopes W.; asc. over SE. slope.
1010	Dirt trail, 4 ft. wide, bears N. 80° E. and S. 80° W.
1085	Top of ascent, slopes N. 30° E.; desc. over NW. slope.
1089.11	The remains of an original line tree, a fir stump, 35 ins. diam., with 1 opened notch and 1 healed notch visible on N. side. Drive an iron rod, 24 ins. long, 5/8 in. diam., 19 ins. into the center of the stump, with aluminum cap mkd.
137600257	AP T 13 S R 7 W S 26 S 25 2000
	from which
	A fir, 26 ins. diam., bears S. 38° E., 25.1 ft. dist., mkd. AP S25 BT.
	A fir, 19 ins. diam., bears N. 70½° W., 8.8 ft. dist., mkd. AP S26 BT.
	This now becomes an angle point.

	N. 1° 12' 00" W., beginning new measurement.
	Descend over broken NW. slope.
140	Dirt trail, 2 ft. wide, bears N. 40° E. and S. 55° W.
980	Creek, 3 ft. wide, course N. 55° W.; asc. over broken SW. slope.
1410	Top of ascent, slopes NW.; desc. over NW. slope.
1527.34	The cor. of secs. 23, 24, 25, and 26, monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.
	T 13 S R 7 W S 23 S 24 S 26 S 25 1993
	from which the remains of the original bearing trees
	A fir, 68 ins. diam., bears S. 57° E., 27.7 ft. dist., with a healed blaze.