

R. AARSETH / D. NEVIN 1993

6 348

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 13 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	From this point, the National Geodetic Survey triangulation station "MARY RM 5," bears N. 24° 56' 03" W. (mean bearing), 523.732 chs. dist. (sea level distance), monumented with a standard brass tablet, firmly seated in a concrete post, 12 ins. diam., flush with the surface of the ground, mkd. MARY 1903 NO 5 1972.
	N. 0 09' 30" E., bet. secs. 23 and 24.
	Descend over NW. slope, through moderate timber and undergrowth.
2.25	Creek, 2 lks. wide, course W., also SE. cor. of logged area, edge bears N. and S. 70° W.; asc. over SW. slope, along E. edge of logged area.
9.55	Spur, slopes W.; desc. over W. slope.
22.30	Creek, 3 lks. wide, course N. 80° W.; asc. over SW. slope.
24.450	The remains of an original line tree, a fir stump, 66 ins. diam., with 2 notches on N. and S. sides. This now becomes an angle point. Drive an iron rod, 24 ins. long, 5/8 in. diam., 20 ins. into center of stump, with aluminum cap mkd.
	A P S 23 S 24 1993
	from which
	A fir, 18 ins. diam., bears N. 77½° E., 51 lks. dist., mkd. AP S24 BT.
	A hemlock, 8 ins. diam., bears S. 75° W., 34 lks. dist., mkd. AP S23 BT.
	The corner is located at top of ascent, slopes W.
	N. 0° 26' 00" W., beginning new measurement.
	Descend over NW. slope.
3.50	Creek, 5 lks. wide, course S. 40° W.; asc. over SW. slope.
13.80	Top of ascent, slopes W.; desc. over NW. slope.
15.050	Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate distance. There is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 13 S R 7 W S 23 S 24 1993
	from which

137600324

