

137640100

DATE 05/05/2016TOWNSHIP 13 SOUTH, RANGE 7 WEST, WILLAMETTE MERIDIAN; SECTION 36 CORNER SOUTH 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

POINT ON NORTH LINE OF SECTION 1, TOWNSHIP 14 SOUTH, RANGE 7 WEST

RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY ROBERT O. COLLIER, D.S., DATED SEPTEMBER 23, 1891. SET A POST 3 FEET LONG, 3" SQUARE, 24" IN GROUND MARKED "*1/4S SC*" ON NORTH FACE FROM WHICH A HEMLOCK 6" DIA BEARS S43°W, 14 LINKS (9.24 FEET) MARKED "*SC 1/4S BT*"; A CEDAR 24" DIA BEARS N66°W, 28 LINKS (18.48 FEET) MARKED "*SC 1/4S BT*".
- [02] BENTON COUNTY SURVEY NO. 8564 BY JIM S. PETERSON, P.L.S., DATED SEPTEMBER 20, 1991. SET 3/4" X 30" IRON PIPE WITH PLASTIC CAP MARKED "*LS1084*". FOUND CEDAR 48" DIA (GLO BT) BEARS N66°W, 18.5 FEET, CHOPPED FACE; HEMLOCK SNAG 28" DIA (GLO BT) BEARS S43°W, 9.2 FEET, CHOPPED FACE WITH VISIBLE SCRIBING. SET HEMLOCK 14" DIA BEARS N1°W, 22.1 FEET SCRIBED "*1/4 S36 BT*"; HEMLOCK 28" DIA BEARS N74°W, 43.7 FEET SCRIBED "*1/4 S36 BT*".
- [03] BENTON COUNTY SURVEY NO. 9866 BY JIM S. PETERSON, P.L.S., DATED APRIL 11, 2000. FOUND 3/4" IRON PIPE WITH PLASTIC CAP MARKED "*LS1084*". FOUND CEDAR 48" DIA (GLO BT) BEARS N66°W, 28 LINKS (18.48 FEET), CHOPPED FACE; HEMLOCK SNAG 28" DIA (GLO BT) BEARS S43°W, 14 LINKS (9.24 FEET), CHOPPED FACE; HEMLOCK 16" DIA BEARS N1°W, 22.1 FEET, SCRIBING VISIBLE; HEMLOCK 30" DIA BEARS N74°W, 43.7 FEET, SCRIBING VISIBLE. CORNER LIES ON SOUTH SLOPE, 100 FEET WEST OF CREEK.
- [04] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY RICHARD S. KAISER, CADASTRAL SURVEYOR, DATED MARCH 17, 2008. IRON PIPE, 3/4" DIA, FIRMLY SET, PROJECTING 1" ABOVE THE GROUND, WITH A YELLOW PLASTIC CAP MARKED "*PLS 1084*" FROM WHICH A HEMLOCK SNAG 24" DIA (GLO BT) BEARS S43°W, 9.3 FEET, WITH ILLEGIBLE SCRIBE MARKS VISIBLE ON OPENED BLAZE; A CEDAR STUMP 52" DIA (GLO BT) BEARS N66°W, 19.9 FEET, WITH NO SCRIBE MARKS VISIBLE ON OPENED BLAZE; A HEMLOCK 18" DIA BEARS N0-1/2°E, 22.2 FEET, WITH A HEALED BLAZE; A HEMLOCK STUMP 32" DIA BEARS N73-1/4°W, 44.1 FEET, WITH NO SCRIBE MARKS VISIBLE. AT THE CORNER POINT SET A STAINLESS STEEL POST, 28" LONG, 2-1/2" DIA, 20" IN THE GROUND, DIRECTLY OVER THE IRON PIPE AND IN A COLLAR OF STONE, WITH BRASS CAP MARKED "*T13S R7W S36 1/4 2008*" FROM WHICH A HEMLOCK 12" DIA BEARS N45-1/4°E, 19.4 FEET TO A 2-1/2" X 1/4" MAGNETIC NAIL (MAG NAIL) DRIVEN AT THE BASE ON RIGHT SIDE CENTER, MARKED "*X*" AT BREST HEIGHT AND "*BT*" AT THE BASE.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME