

138140300

DATE 01/06/2021TOWNSHIP 13 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 19 CORNER SOUTH 1/4
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

NORTH 1/4 CORNER SECTION 30

RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY EDWARD F. SHARP, D.S., DATED SEPTEMBER 25, 1897. SET A FIR POST 3 FEET LONG, 3" SQUARE, 14" IN THE GROUND ON BEDROCK, MARKED "*1/4S*" ON NORTH FACE, FROM WHICH A FIR 8" DIA BEARS N4°E, 6 LINKS (3.96 FEET), MARKED "*1/4SBT*"; FIR 7" DIA BEARS S63°W, 70 LINKS (46.20 FEET), MARKED "*1/4SBT*".
- [02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY JOSEPH S. GAWRON, D.S., DATED NOVEMBER 16, 1960. THE 1/4 SECTION CORNER DETERMINED AT RECORD BEARING AND DISTANCE FROM A FIR 24" DIA (GLO BT) BEARS N4°E, 6 LINKS (3.96 FEET), MARKED "*1/4S*" ON EXPOSED FACE OF OPENED BLAZE; FIR 22" DIA (GLO BT) BEARS S63°W, 70 LINKS (46.20 FEET), WITH A HEALED BLAZE. AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "S19 1/4 S30 T13S R8W 1960" FROM WHICH A FIR 18" DIA BEARS N37°E, 17 LINKS (11.22 FEET), MARKED "*1/4 S19 BT*"; FIR 16" DIA BEARS S42°W, 23 LINKS (15.18 FEET), MARKED "*1/4 S30 BT*".
- [03] BENTON COUNTY SURVEY NO. 5768 BY ARTHUR E. MOSHER, P.L.S., DATED MARCH, 1974. FOUND BRASS CAP.
- [04] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY LARRY D. EVANS, CADASTRAL SURVEYOR, DATED NOVEMBER 2, 1976. THE 1/4 SECTION CORNER MONUMENTED WITH AN IRON POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 12" ABOVE GROUND, AND IN A MOUND OF STONE, 2 FOOT BASE, TO TOP, WITH BRASS CAP MARKED "S19 1/4 S30 T13S R8W 1960" FROM WHICH A FIR STUMP 18" DIA (BLM BT) BEARS N37°E, 17 LINKS (11.22 FEET), WITH SCRIBE MARKS "*1/4 S19 BT*" VISIBLE ON PARTIALLY HEALED BLAZE; FIR STUMP 16" DIA (BLM BT) BEARS S34-1/2°W, 23 LINKS (15.18 FEET), WITH SCRIBE MARKS "*1/4 S30 BT*" VISIBLE ON PARTIALLY HEALED BLAZE; FIR 18" DIA BEARS S19°E, 124 LINKS (81.84 FEET), MARKED "*1/4 S30 BT*". ADD MARKS "1976" TO BRASS CAP. SET A 5 FOOT STEEL FENCE POST ALONGSIDE IRON POST.
- [05] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY ROBERT L. AARSETH, CADASTRAL SURVEYOR, DATED OCTOBER 15, 1998. THE 1/4 SECTION CORNER MONUMENTED WITH AN IRON POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 12" ABOVE GROUND, AND IN A MOUND OF STONE, 3-1/2 FOOT BASE, 10" HIGH, WITH BRASS CAP MARKED "S19 1/4 S30 T13S R8W 1960 1976" FROM WHICH A FIR STUMP 18" DIA (BLM BT) BEARS N37°E, 17 LINKS (11.22 FEET), WITH SCRIBE MARKS "*1/4 S19 BT*" VISIBLE ON OPEN BLAZE; DECAYED FIR STUMP 16" DIA (BLM BT) BEARS S34-1/2°W, 23 LINKS (15.18 FEET), NO MARKS VISIBLE; FIR STUMP 18" DIA (BLM BT) BEARS S19°E, 124 LINKS (81.84 FEET), WITH HEALED BLAZE; FIR SNAG 6" DIA BEARS N22°E, 24 LINKS (15.84 FEET), WITH SCRIBE MARKS "*1/4 S19*" VISIBLE ON PARTIALLY HEALED BLAZE.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME