

138200300

DATE 03/10/2021TOWNSHIP 13 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 19 CORNER SOUTHEAST
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHWEST CORNER SECTION 20
NORTHWEST CORNER SECTION 29
NORTHEAST CORNER SECTION 30**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY EDWARD F. SHARP, D.S., DATED SEPTEMBER 25, 1897. SET A FIR POST 3 FEET LONG, 4" SQUARE, 24" IN THE GROUND, MARKED "T13SS20" ON NORTHEAST FACE, "R7WS29" ON SOUTHEAST FACE, "S30" ON SOUTHWEST FACE, AND "S19" ON NORTHWEST FACE, WITH 2 NOTCHES ON SOUTH EDGE AND 5 NOTCHES ON EAST EDGE, FROM WHICH A FIR 24" DIA BEARS N65°E, 37 LINKS (24.42 FEET), MARKED "T13S R8W S20 BT"; FIR 24" DIA BEARS S3°E, 29 LINKS (19.14 FEET), MARKED "T13S R8W S29 BT"; FIR 30" DIA BEARS S10°W, 18 LINKS (11.88 FEET), MARKED "T13S R8W S30 BT"; FIR 24" DIA BEARS N20°W, 49 LINKS (32.34 FEET), MARKED "T13S R8W S19 BT".
- [02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY JOSEPH S. GAWRON, CADASTRAL SURVEYOR, DATED NOVEMBER 16, 1960. THE SECTION CORNER DETERMINED FROM A FIR STUMP 36" DIA (GLO BT) BEARS N65°E, 37 LINKS (24.42 FEET), MARKED "T13S R8W S17 BT"; FIR SNAG 30" DIA (GLO BT) BEARS S9°E, 23 LINKS (15.18 FEET), MARKED "T13S R8W S29 BT"; FIR SNAG 40" DIA (GLO BT) BEARS N80°W, 18 LINKS (11.88 FEET), MARKED "T13S R8W S30 BT"; FIR STUMP 36" DIA (GLO BT) BEARS N20°W, 49 LINKS (32.34 FEET), MARKED "BT" ON EXPOSED FACE OF ROTTED OPEN BLAZE. AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 26" IN THE GROUND, WITH BRASS CAP MARKED "T13S R8W S19 S20 S30 S29 1960" FROM WHICH A HEMLOCK 12" DIA BEARS N33°E, 34 LINKS (22.44 FEET), MARKED "T13S R8W S20 BT"; HEMLOCK 8" DIA BEARS S80°E, 16 LINKS (10.56 FEET), MARKED "T13S R8W S29 BT"; HEMLOCK 20" DIA BEARS S12°W, 15 LINKS (9.90 FEET), MARKED "T13S R8W S30 BT"; HEMLOCK 10" DIA BEARS N34°W, 19 LINKS (12.54 FEET), MARKED "T13S R8W S19 BT".
- [03] BENTON COUNTY SURVEY NO. 5767 BY ARTHUR E. MOSHER, P.L.S., DATED MARCH, 1974. FOUND BRASS CAP.
- [04] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY ROBERT L. AARSETH, CADASTRAL SURVEYOR, DATED OCTOBER 15, 1998. THE SECTION CORNER MONUMENTED WITH AN IRON POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 12" ABOVE GROUND, WITH BRASS CAP MARKED "T13S R8W S19 S20 S30 S29 1960" FROM WHICH A FIR STUMP 36" DIA (GLO BT) BEARS N65°E, 37 LINKS (24.42 FEET), WITH DECAYED BLAZE; FIR STUB 30" DIA (GLO BT) BEARS S9°E, 23 LINKS (15.18 FEET), WITH SCRIBE MARKS "S29 BT" VISIBLE ON DECAYED BLAZE; FIR STUB 40" DIA (GLO BT) BEARS N80°W, 18 LINKS (11.88 FEET), NO MARKS VISIBLE; DECAYED HEMLOCK SNAG 12" DIA (BLM BT) BEARS N33°E, 34 LINKS (22.44 FEET), NO MARKS VISIBLE; DECAYED HEMLOCK SNAG 9" DIA (BLM BT) BEARS S80°E, 16 LINKS (10.56 FEET), NO MARKS VISIBLE; DECAYED HEMLOCK SNAG 24" DIA (BLM BT) BEARS S12°W, 15 LINKS (9.90 FEET), WITH SCRIBE MARKS "R8W S" VISIBLE ON DECAYED OPEN BLAZE; DECAYED HEMLOCK SNAG 9" DIA (BLM BT) BEARS N34°W, 19 LINKS (12.54 FEET), WITH SCRIBE MARKS "T13S R8W S19 BT" VISIBLE ON PARTIALLY HEALED BLAZE; FIR 7" DIA BEARS N31°E, 15-1/2 LINKS (10.23 FEET), MARKED "T13S R8W S20 BT"; FIR 10" DIA BEARS S58°E, 25 LINKS (16.50 FEET), MARKED "T13S R8W S29 BT"; HEMLOCK 6" DIA BEARS S21°W, 13 LINKS (8.58 FEET), MARKED "T13S R8W S30 BT"; FIR 6" DIA BEARS N39-1/2°W, 19 LINKS (12.54 FEET), MARKED "T13S R8W S19 BT".
- [05] BENTON COUNTY SURVEY NO. 10863 BY ROBERT ALAN COOK, P.L.S., DATED DECEMBER 19, 2017. FOUND 1960 BLM BRASS CAP UP 9". D. FIR STUMP 30" DIA (GLO BT) BEARS S9°E, 15.2 FEET. HEMLOCK 10" DIA (BLM BT) BEARS S21°W, 8.6 FEET. D. FIR 12" DIA (BLM BT) BEARS N39°W, 12.5 FEET. D. FIR 16" DIA BEARS S13°E, 30.9 FEET, SCRIBED "T13SR8WS29" ABOVE "BT".

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME