

**138400140**

DATE 03/09/2021TOWNSHIP 13 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 33 CORNER EAST 1/4  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

WEST 1/4 CORNER SECTION 34

**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY EDWARD F. SHARP, D.S., DATED SEPTEMBER 25, 1897. *SET A FIR POST 3 FEET LONG, 3" SQUARE, 24" IN THE GROUND, MARKED "1/4S" ON WEST FACE, FROM WHICH A FIR 20" DIA BEARS N80°E, 32 LINKS (21.12 FEET), MARKED "1/4SBT"; FIR 24" DIA BEARS S85°W, 38 LINKS (25.08 FEET), MARKED "1/4SBT".*
- [02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY JOSEPH S. GAWRON, CADASTRAL SURVEYOR, DATED NOVEMBER 16, 1960. *THE 1/4 SECTION CORNER DETERMINED AT RECORD BEARING AND DISTANCE FROM A FIR 32" DIA (GLO BT) BEARS N80°E, 32 LINKS (21.12 FEET), MARKED WITH A HEALED BLAZE; FIR 36" DIA (GLO BT) BEARS S85°W, 38 LINKS (25.08 FEET), MARKED WITH A HEALED BLAZE. AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "1/4 S33 S34 T13S R8W 1960" FROM WHICH A FIR 6" DIA BEARS S66°E, 49 LINKS (32.34 FEET), MARKED "1/4 S34 BT"; FIR 8" DIA BEARS S34°W, 29 LINKS (19.14 FEET), MARKED "1/4 S33 BT".*
- [03] BENTON COUNTY SURVEY NO. 6508 BY GARY T. JOHNSTON, P.L.S., DATED OCTOBER, 1977. *FOUND BRASS CAP.*
- [04] BENTON COUNTY SURVEY NO. 6618 BY GARY T. JOHNSTON, P.L.S., DATED APRIL, 1978. *FOUND BRASS CAP.*

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME