

**138400200**

DATE 03/09/2021TOWNSHIP 13 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 27 CORNER SOUTHWEST  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHEAST CORNER SECTION 28  
NORTHEAST CORNER SECTION 33  
NORTHWEST CORNER SECTION 34**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY EDWARD F. SHARP, D.S., DATED SEPTEMBER 25, 1897. SET A HEMLOCK POST 3 FEET LONG, 4" SQUARE, 24" IN THE GROUND, MARKED "T13SS27" ON NORTHEAST FACE, "R8WS34" ON SOUTHEAST FACE, "S33" ON SOUTHWEST FACE, AND "S28" ON NORTHWEST FACE, WITH 1 NOTCH ON SOUTH EDGE AND 3 NOTCHES ON EAST EDGE, FROM WHICH A HEMLOCK 12" DIA BEARS N32°E, 27 LINKS (17.82 FEET), MARKED "T13S R8W S27 BT"; HEMLOCK 24" DIA BEARS S67°E, 34 LINKS (22.44 FEET), MARKED "T13S R8W S34 BT"; HEMLOCK 24" DIA BEARS S59°W, 31 LINKS (20.46 FEET), MARKED "T13S R8W S33 BT"; HEMLOCK 16" DIA BEARS N31°W, 35 LINKS (23.10 FEET), MARKED "T13S R8W S28 BT".
- [02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY JOSEPH S. GAWRON, CADASTRAL SURVEYOR, DATED NOVEMBER 16, 1960. THE SECTION CORNER DETERMINED AT RECORD BEARING AND DISTANCE FROM A HEMLOCK, DEAD AND DOWN, 15" DIA (GLO BT) BEARS N32°E, 27 LINKS (17.82 FEET); HEMLOCK 30" DIA (GLO BT) BEARS S67°E, 34 LINKS (22.44 FEET), MARKED "34" ON EXPOSED FACE OF OPENED BLAZE; ROTTED HEMLOCK STUMP (GLO BT) BEARS S59°W, 31 LINKS (20.46 FEET); HEMLOCK 30" DIA (GLO BT) BEARS N31°W, 35 LINKS (23.10 FEET), MARKED WITH A HEALED BLAZE. AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "T13S R8W S28 S27 S33 S34 1960" FROM WHICH A HEMLOCK 10" DIA BEARS N45°E, 74 LINKS (48.84 FEET), MARKED "T13S R8W S27 BT"; HEMLOCK 9" DIA BEARS S70°E, 28 LINKS (18.48 FEET), MARKED "T13S R8W S34 BT"; HEMLOCK 10" DIA BEARS S66°W, 28 LINKS (18.48 FEET), MARKED "T13S R8W S33 BT"; HEMLOCK 30" DIA BEARS N65°W, 25 LINKS (16.50 FEET), MARKED "T13S R8W S28 BT".
- [03] BENTON COUNTY SURVEY NO. 6508 BY GARY T. JOHNSTON, P.L.S., DATED OCTOBER, 1977. FOUND BRASS CAP.
- [04] BENTON COUNTY SURVEY NO. 6618 BY GARY T. JOHNSTON, P.L.S., DATED APRIL, 1978. FOUND BRASS CAP.
- [05] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY ROBERT L. AARSETH, CADASTRAL SURVEYOR, DATED OCTOBER 15, 1998. THE SECTION CORNER MONUMENTED WITH AN IRON POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 4" ABOVE GROUND, WITH BRASS CAP MARKED "T13S R8W S28 S27 S33 S34 1960" FROM WHICH A HEMLOCK 30" DIA (GLO BT) BEARS S67°E, 35-1/2 LINKS (23.43 FEET), WITH HEALED BLAZE; DECAYED HEMLOCK STUMP, SIZE INDETERMINATE, (GLO BT) BEARS S50°W, 31 LINKS (20.46 FEET); HEMLOCK 30" DIA (GLO BT) BEARS N22°W, 35 LINKS (23.10 FEET), WITH HEALED BLAZE; HEMLOCK 26" DIA (BLM BT) BEARS N45°E, 74 LINKS (48.84 FEET), WITH HEALED BLAZE; HEMLOCK 17" DIA (BLM BT) BEARS S70°E, 28 LINKS (18.48 FEET), WITH HEALED BLAZE; HEMLOCK STUMP 26" DIA (BLM BT) BEARS N65°W, 25 LINKS (16.50 FEET), WITH SCRIBE MARKS "T13S R8W S28 BT" VISIBLE ON OPEN BLAZE; HEMLOCK 9" DIA BEARS S32°W, 20-1/2 LINKS (13.53 FEET), MARKED "T13S R8W S33 BT".
- [06] BENTON COUNTY SURVEY NO. 10799 BY ROBERT ALAN COOK, P.L.S., DATED NOVEMBER 30, 2016. FOUND 1960 BLM BRASS CAP UP 8", SET STEEL POST RISER. HEMLOCK 12" DIA (BLM BT) BEARS N32°E, 13.6 FEET; HEMLOCK REMAINS 10" DIA (BLM BT) BEARS S66°W, 28 LINKS (18.48 FEET), CAN SEE MARKED FACE; HEMLOCK 36" DIA (GLO BT) BEARS S67°E, 34 LINKS (22.44 FEET).

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME