

**138400340**

DATE 04/12/2021TOWNSHIP 13 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 21 CORNER EAST 1/4  
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**

WEST 1/4 CORNER SECTION 22

**RECORDS (INFORMATION IN BOLD ITALICS IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY EDWARD F. SHARP, D.S., DATED SEPTEMBER 25, 1897. *SET A YEW POST 3 FEET LONG, 3" SQUARE, 18" IN THE GROUND ON "BEDROCK", MARKED "1/4S" ON WEST FACE, FROM WHICH A FIR 36" DIA BEARS S70°E, 58 LINKS (38.28 FEET), MARKED "1/4SBT"; HEMLOCK 8" DIA BEARS S79°W, 29 LINKS (19.14 FEET), MARKED "1/4SBT".*
- [02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY JOSEPH S. GAWRON, CADASTRAL SURVEYOR, DATED NOVEMBER 16, 1960. *THE 1/4 SECTION CORNER DETERMINED AT RECORD BEARING AND DISTANCE FROM A FIR SNAG 48" DIA (GLO BT) BEARS S70°E, 58 LINKS (38.28 FEET), MARKED "1/4S BT". AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "T13S R8W 1/4 S21 S22 1960" FROM WHICH A FIR 12" DIA BEARS N62°E, 15 LINKS (9.90 FEET), MARKED "1/4 S22 BT"; HEMLOCK 9" DIA BEARS S66°W, 13 LINKS (8.58 FEET), MARKED "1/4 S21 BT".*
- [03] BENTON COUNTY SURVEY NO. 5767 BY ARTHUR E. MOSHER, P.L.S., DATED MARCH, 1974. *FOUND BRASS CAP.*
- [04] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY ROBERT L. AARSETH, CADASTRAL SURVEYOR, DATED OCTOBER 15, 1998. *THE 1/4 SECTION CORNER MONUMENTED WITH AN IRON POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 8" ABOVE GROUND, AND IN A MOUND OF STONE, 3 FEET BASE, TO TOP, WITH BRASS CAP MARKED "T13S R8W 1/4 S21 S22 1960" FROM WHICH A FIR SNAG 48" DIA (GLO BT) BEARS S70°E, 58 LINKS (38.28 FEET), NO MARKS VISIBLE; FIR 17" DIA (BLM BT) BEARS N62°E, 15 LINKS (9.90 FEET), WITH HEALED BLAZE; HEMLOCK 16" DIA (BLM BT) BEARS S66°W, 13 LINKS (8.58 FEET), WITH HEALED BLAZE.*
- [05] BENTON COUNTY SURVEY NO. 10974 BY ROBERT ALAN COOK, P.L.S., DATED JUNE 28, 2019, ALSO FILED AS LINCOLN COUNTY SURVEY NO. 20916. *SET 5/8" ROD WITH 2" ALUMINUM CAP IN MOUND OF STONES UP 10" IN STEEP SLIDE AREA AMONG UPROOTED TREES. BLM PIPE AND CAP ARE GONE. D. FIR STUMP 48" DIA (GLO BT) BEARS S73°E, 39.6 FEET TO CENTER, NO MARKS; D. FIR WINDFALL 18" DIA (BLM BT) BEARS N61°E, 9.9 FEET TO CENTER OF ROTHOLE; D. FIR WINDFALL 18" DIA (BLM BT) BEARS S68°W, 8.6 FEET TO CENTER OF ROTHOLE; HEMLOCK 22" DIA BEARS N82°W, 31.6 FEET, SCRIBED "1/4S21" ABOVE "BT"; HEMLOCK 30" DIA BEARS S53°W, 25.5 FEET, SCRIBED "1/4S21" ABOVE "BT"; D. FIR STUMP 36" DIA WITH MAG NAIL IN CENTER TOP BEARS S89°45'41"E, 39.95 FEET; 1/2" ROD WITH YELLOW CAP MARKED "N.STAR" BEARS S63°24'40"E, 39.07 FEET.*

**FIRM/AGENCY:** BENTON COUNTY SURVEYOR'S OFFICE  
**ADDRESS:** 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821  
**RESEARCH BY:** DAVID L. MALONE, P.L.S.  
**DATA ENTRY BY:** SAME