

138400400

DATE 04/14/2021TOWNSHIP 13 SOUTH, RANGE 8 WEST, WILLAMETTE MERIDIAN; SECTION 15 CORNER SOUTHWEST
DONATION LAND CLAIM N/A CORNER N/A**COMMON CORNER(S):**SOUTHEAST CORNER SECTION 16
NORTHEAST CORNER SECTION 21
NORTHWEST CORNER SECTION 22**RECORDS (INFORMATION IN *BOLD ITALICS* IS COUNTY STAFFS' INTERPRETATION OF THE RECORD)**

BASED ON EXTENSIVE RESEARCH AND RECOVERY OF EVIDENCE, THIS OFFICE HAS DETERMINED THAT MOST GENERAL LAND OFFICE SURVEYORS IN BENTON COUNTY BEFORE 1890 MEASURED TO THE FACE OF BEARING TREES.

- [01] GENERAL LAND OFFICE (GLO) NOTES BY EDWARD F. SHARP, D.S., DATED SEPTEMBER 25, 1897. SET A YEW POST 3 FEET LONG, 4" SQUARE, 24" IN THE GROUND, MARKED "T13SS15" ON NORTHEAST FACE, "R8WS22" ON SOUTHEAST FACE, "S21" ON SOUTHWEST FACE, AND "S16" ON NORTHWEST FACE, WITH 3 NOTCHES ON SOUTH AND EAST EDGES, FROM WHICH A FIR 24" DIA BEARS N66°E, 68 LINKS (44.88 FEET), MARKED "T13SR8WS15BT"; FIR 20" DIA BEARS S72°E, 19 LINKS (12.54 FEET), MARKED "T13SR8WS22BT"; YEW 14" DIA BEARS S13°W, 18 LINKS (11.88 FEET), MARKED "T13SR8WS21BT"; HEMLOCK 20" DIA BEARS N28°W, 25 LINKS (16.50 FEET), MARKED "T13SR8WS16BT".
- [02] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY JOSEPH S. GAWRON, CADASTRAL SURVEYOR, DATED NOVEMBER 16, 1960. THE SECTION CORNER DETERMINED AT RECORD BEARING AND DISTANCE FROM A FIR 50" DIA (GLO BT) BEARS N66°E, 68 LINKS (44.88 FEET), MARKED WITH A HEALED BLAZE; FIR SNAG 20" DIA (GLO BT) BEARS S72°E, 19 LINKS (12.54 FEET), MARKED "T13S R8W S2"; YEW 14" DIA (GLO BT) BEARS S13°W, 18 LINKS (11.88 FEET), NO MARKS VISIBLE; HEMLOCK 36" DIA (GLO BT) BEARS N28°W, 25 LINKS (16.50 FEET), MARKED WITH A HEALED BLAZE. AT THE CORNER POINT SET AN IRON POST, 28" LONG, 2-1/2" DIA, 24" IN THE GROUND, WITH BRASS CAP MARKED "T13S R8W S16 S15 S21 S22 1960" FROM WHICH A FIR 35" DIA BEARS N23°E, 64 LINKS (42.24 FEET), MARKED "T13S R8W S15 BT"; HEMLOCK 30" DIA BEARS S85°E, 33 LINKS (21.78 FEET), MARKED "T13S R8W S22 BT"; HEMLOCK 18" DIA BEARS S63°W, 93 LINKS (61.38 FEET), MARKED "T13S R8W S21 BT"; HEMLOCK 30" DIA BEARS N29°W, 64 LINKS (42.24 FEET), MARKED "T13S R8W S16 BT".
- [03] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY FRANK A. TUERS AND ROBERT L. AARSETH, CADASTRAL SURVEYORS, DATED AUGUST 9, 1979. THE SECTION CORNER MONUMENTED WITH AN IRON POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 10" ABOVE GROUND, WITH BRASS CAP MARKED "T13S R8W S16 S15 S21 S22 1960" FROM WHICH A SAWED FIR STUMP 48" DIA (GLO BT) BEARS N66°E, 75-1/2 LINKS (49.83 FEET), NO MARKS VISIBLE; FIR SNAG 20" DIA (GLO BT) BEARS S72°E, 19 LINKS (12.54 FEET), NO MARKS VISIBLE; YEW SNAG 13" DIA (GLO BT) BEARS S13°W, 13 LINKS (8.58 FEET), WITH OPEN BLAZE, NO MARKS VISIBLE; SAWED HEMLOCK STUMP 38" DIA (GLO BT) BEARS N28°W, 25 LINKS (16.50 FEET), WITH HEALED BLAZE; SAWED FIR STUMP 36" DIA (BLM BT) BEARS N23°E, 64 LINKS (42.24 FEET), WITH SCRIBE MARKS "T13S R8W S15 BT" VISIBLE ON BURNED BLAZE; SAWED HEMLOCK STUMP 30" DIA (BLM BT) BEARS S85°E, 33 LINKS (21.78 FEET), WITH SCRIBE MARKS "T13S R8W S22 BT" VISIBLE ON BURNED BLAZE; HEMLOCK 20" DIA (BLM BT) BEARS S63°W, 93 LINKS (61.38 FEET), WITH HEALED BLAZE; SAWED HEMLOCK STUMP 32" DIA (BLM BT) BEARS N29°W, 64 LINKS (42.24 FEET), WITH SCRIBE MARKS "T13S R8W S16 BT" VISIBLE ON BURNED BLAZE.
- [04] BUREAU OF LAND MANAGEMENT (BLM) NOTES BY ROBERT L. AARSETH, CADASTRAL SURVEYOR, DATED OCTOBER 15, 1998. THE SECTION CORNER MONUMENTED WITH AN IRON POST, 2-1/2" DIA, FIRMLY SET, PROJECTING 10" ABOVE GROUND, WITH BRASS CAP MARKED "T13S R8W S16 S15 S21 S22 1960" FROM WHICH A FIR STUMP 48" DIA (GLO BT) BEARS N66°E, 75-1/2 LINKS (49.83 FEET), NO MARKS VISIBLE; FIR SNAG 20" DIA (GLO BT) BEARS S72°E, 19 LINKS (12.54 FEET), NO MARKS VISIBLE; YEW SNAG 13" DIA (GLO BT) BEARS S13°W, 13 LINKS (8.58 FEET), WITH OPEN BLAZE, NO MARKS VISIBLE; HEMLOCK STUMP 38" DIA (GLO BT) BEARS N28°W, 25 LINKS (16.50 FEET), WITH HEALED BLAZE; FIR STUMP 36" DIA (BLM BT) BEARS N23°E, 64 LINKS (42.24 FEET), WITH SCRIBE MARKS "T13S R8W S15 BT" VISIBLE ON BURNED BLAZE; HEMLOCK STUMP 30" DIA (BLM BT) BEARS S85°E, 33 LINKS (21.78 FEET), WITH ILLEGIBLE SCRIBE MARKS VISIBLE ON BURNED BLAZE; HEMLOCK 28" DIA (BLM BT) BEARS S63°W, 93 LINKS (61.38 FEET), WITH HEALED BLAZE; HEMLOCK STUMP 32" DIA (BLM BT) BEARS N29°W, 64 LINKS (42.24 FEET), WITH SCRIBE MARKS "T13S R8W S16 BT" VISIBLE ON BURNED BLAZE; FIR 7" DIA BEARS N29°E, 32 LINKS (21.12 FEET), MARKED "T13S R8W S15 BT"; FIR 7" DIA BEARS S67°E, 9-1/2 LINKS (6.27 FEET), MARKED "T13S R8W S22 BT"; FIR 7" DIA BEARS N56°W, 44 LINKS (29.04 FEET), MARKED "T13S R8W S16 BT".
- [05] LINCOLN COUNTY SURVEY NO. 19409 BY ROBERT ALAN COOK, P.L.S., DATED APRIL 22, 2014. FOUND 1960 BLM BRASS CAP, UP 2". D. FIR STUMP 48" DIA (GLO BT) BEARS N66°E, 75.5 LINKS (49.83 FEET), TIN LID; D. FIR STUMP 36" DIA (BLM BT) BEARS N23°E, 64 LINKS (42.24 FEET), TIN LID; HEMLOCK STUMP 38" DIA (GLO BT) BEARS N28°W, 25 LINKS (16.50 FEET), SCRIBES VISIBLE.
- [06] BENTON COUNTY SURVEY NO. 10974 BY ROBERT ALAN COOK, P.L.S., DATED JUNE 28, 2019, ALSO FILED AS LINCOLN COUNTY SURVEY NO. 20916. FOUND 1960 BLM BRASS CAP, UP 2". D. FIR STUMP 48" DIA (GLO BT) BEARS N66°E, 75.5 LINKS (49.83 FEET), WITH A TIN LID; D. FIR STUMP 36" DIA (BLM BT) BEARS N23°E, 64 LINKS (42.24 FEET), WITH A TIN LID; HEMLOCK STUMP 38" DIA (GLO BT) BEARS N28°W, 25 LINKS (16.50 FEET), WITH SCRIBES VISIBLE.

FIRM/AGENCY: BENTON COUNTY SURVEYOR'S OFFICE
ADDRESS: 360 S.W. AVERY AVE., CORVALLIS, OR 97333; PH. 541-766-6821
RESEARCH BY: DAVID L. MALONE, P.L.S.
DATA ENTRY BY: SAME